# Marking Tubes and Labels!



Electronic Lettering Machine

# LETATIVIN LM-550E

LMX10 SLD15

Professional choice for your cable marking job!

X69 X70 R1 S1



X10 X11 X10 X10 X10 X10 X10 X10 SELETINE



LETATWIN LM-550E

# **Longer Consumebles!**

Ink ribbon increased from 50m/roll to 110m/roll! Decreased ribbon exchanges lets you focus on other work!







## **Increased limit for REPEAT** function, 300 times per block!

Increased from 100 times to 300 times. You can decrease your data input time!




REPEAT function tube print example

LM-550E	LM-550E	LM-550E	LM-550E	LM-550E	LM-550E	

# **Increased printing speed!**

(35 pcs/min → 37 pcs/min, 1pc = 20mm pitch with half-cut)

Printing speed increased from 25mm/sec to 27.5mm/sec.



### Addition of 'SUPER' AUTO SIZE function, makes it more useful!

In addition to 'Auto' and 'Off', you can choose 'SUPER' AUTO SIZE function. 'SUPER' can make the length of printed words shorter than normal AUTO SIZE.



### SPECIFICATION

ITEMS	CONTENTS
Dimensions	295(W)×293(D)×94(H)mm
Weight	2.1kg
Printing method	Thermal transfer method (300dpi)
Display	LCD dot matrix : 64×160 Pixel (Backlit)
Printing speed	27.5 mm/s (Standard) 10.0 mm/s (Low temperature mode)
Maximum Printing length	Tube : 20 m, Tape : 5 m Tube : 100 m, Tape : 7 m (Multiple copies)
Maximum number of characters to input	1,225 characters per file
Character size	1.3, 2, 3, 4, 6mm height
Usable tube	φ2.5 to 6.5mm (PVC tube, Shrinkable tube)
Usable tape	Width 5, 9,12 mm (Max genuine tape)
Tube cutting method	Auto half cut, manual full cut
Internal memory	61,250 characters (1,225 characters × 50 files)
Power supply	DC12V, 3.0A *Use only specified AC Adapter (100V - 240V) included in the package.
Power consumption	15W (max.)
Operating environment	15 to 35°C





### CONSUMABLES



INK RIBBON REFILLS FOR HEAT						
SHRINKABLE TUE	BE 10 ROLLS/BOX					
LM-IR50BP (BLACK)	110m/ROLL					
LM-IR50W (WHITE)	70m/ROLL					

	meth de
<b>UL RECOGNIZED</b>	TUBE 1ROLL/BOX
LM-TU332N2 WHITE	φ3.2mm×100m/R0LL
LM-TU336N2 WHITE	φ3.6mm×100m/R0LL
LM-TU342N2 WHITE	φ4.2mm× 80m/R0LL
LM-TU352N2 WHITE	<i>φ</i> 5.2mm× 80m/R0LL
MAX HIGH QUAL	ITY TUBE 1ROLL/BOX
LM-TU432L WHITE	<i>ϕ</i> 3.2mm×200m/R0LL
LM-TU436L WHITE	<i>ϕ</i> 3.6mm×200m/R0LL
LM-TU442L WHITE	<i>ϕ</i> 4.2mm×200m/R0LL
LM-TU452L WHITE	φ5.2mm×135m/R0LL
LM-TU464L WHITE	φ6.4mm×100m/R0LL
LM-TU480L WHITE	<b> ∅</b> 8.0mm× 70m/R0LL

TAPE CASSETTE 10PCS./BOX				
LM-TP505W (WHITE)	5mm(W) × 16m(L)/PC			
LM-TP505Y (YELLOW)	5mm(W) × 8m(L)/PC			
LM-TP505T (TRANSPARENT)	5mm(W) × 8m(L)/PC			
LM-TP509W (WHITE)	9mm(W) × 16m(L)/PC			
LM-TP509Y (YELLOW)	9mm(W) × 8m(L)/PC			
LM-TP509T (TRANSPARENT)	9mm(W) × 8m(L)/PC			
LM-TP512W (WHITE)	12mm(W) × 16m(L)/PC			
LM-TP512Y (YELLOW)	12mm(W) × 8m(L)/PC			





The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



### MAX CO..LTD.

6-6,NIHONBASHI,HAKOZAKI-CHO,CHUO-KU,TOKYO,JAPAN PHONE: 81-3-3669-8131 FAX: 81-3-3669-7104 Web:http://www.max-Itd.co.jp/int/

Distributor: