


PRODUCT SELECTION GUIDE



- Meters • Power Factor Controllers • CTs • Protection Relays
- Time Switches • Timers • Counters • Temperature Controllers
- Process Indicators • MiBRX • PLCs • HMI • Power Supply • VFDs

SOLUTIONS OFFERED

Energy Management, Power Quality, Industrial Automation, Solar, Selec IoT

METERS	3
Multifunction Meters	
Energy Meters	
Digital Panel Meters (VAF Meter, Volt Amp meter, Voltmeter, Ammeter)	
Analog Meters	
Current Transformers	
Power Factor Controllers	
Ordering Information	
MONITORING / PROTECTION RELAYS	15
Line Monitoring Relay	
Auto Switch	
Earth Fault Relay / Thermistor Protection Relay	
Earth Fault Current Transformer	
Voltage Monitoring Relay / Current Monitoring Relay	
Earth Leakage Relay / Core Balance Current Transformer	
Motor Protection Relay	
Pump Protection Relay	
Motor Protection Current Transformer	
Liquid Level Controllers / Liquid Level Sensor	
Ordering Information	
DIGITAL TIME SWITCHES	23
Astronomical	
Daily / Weekly	
TIMERS	23
Analog Timers	
Digital Timers	
Time Interval Meter / Hour Meters	
Ordering Information	
COUNTERS & RATE INDICATORS	26
Digital Counters	
LCD / LED Counters	
Digital Timer-Counter	
Rate Indicator	
Speed Monitoring Relay	
Ordering Information	
TEMPERATURE & PROCESS	30
Temperature Controllers	
Cooling Controllers	
Process Indicators	
SOLID STATE RELAY	34
Ordering Information	
PLCs & HMI	37
MiBRX Series	
Flexys Series - Flexible I/O Solution	
Compact Series - UNIX, TWIX, DIGIX & MM303x	
Human Machine Interface	
Annunciator	
Power Supply - Din Rail, Open frame & Wall mount Series	
Battery Chargers	
Accessories	
- Relay Modules	
- Data Converters	
- Communication Adapters & Cables	
Ordering Information	
Variable Frequency Drives (VFD)	49
Selec Range of VFDs	
Atsel Range of VFDs	
Power Quality	52
Capacitors	
Advanced Static VAr Generators	
Static Voltage Regulators	
Solar On Grid Inverter	55
Panel Cutout Dimension	57



MFM384
96(H) x 96(W) x 50(D)mm



MFM284
72(H) x 72(W) x 90.15(D)mm



MFM383A
96(H) x 96(W) x 50(D)mm

FEATURES	• Bar graph representation for current • Single pulse output • %THD up to 31st level • Demand measurement	• Compact size • Single pulse output • %THD up to 31st level • Demand measurement	• Single pulse output • Energy (Active / Reactive / Apparent)
DISPLAY	LCD with backlight		
DIGITS	4 rows of 4 digits, Bar graph representation for current, 1 row of 8 digits for energy display	3 rows of 4 digits, 7½ digits for energy display	
ELECTRICAL CONNECTION	1Ø - 2W, 2Ø - 3W, 3Ø - 3W, 3Ø - 4W		
ACCURACY CLASS	Class 0.5S / Class 1	Class 1	
RATED INPUT VOLTAGE	11 to 300V AC (L - N), 19 to 519V AC (L - L)		
RATED INPUT CURRENT	Nominal 5A AC (Min - 11mA ; Max - 6A)		
RESOLUTION	For energy : 0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M (Depending upon CT ratio x PT ratio), For Power, Voltage & Current : Auto resolution, For Power factor : 0.001		For energy : 0.1k, 1k (Depending upon CT ratio x PT ratio) For Power, Voltage & Current : Auto resolution, For Power factor : 0.001
CT PRIMARY	1 / 5A to 10kA (Programmable for any value)		
CT SECONDARY	1 / 5A (Programmable)		
PT PRIMARY	100V to 500kV (Programmable for any value)	100V to 10kV (Programmable for any value)	
PT SECONDARY	100 to 500V AC (L - L) (Programmable for any value)		
COMMUNICATION	RS485 MODBUS RTU protocol (Optional)		
MEASURING PARAMETERS	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Power factor (Individual / Total), Active, Reactive & Apparent Power (Individual / Total), Active, Reactive & Apparent Energy (Total)		
ADDITIONAL FUNCTIONS	Current connection indication, Run Hour, Auxiliary interrupts, Import / Export energy		---
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	85 to 300V AC	100 to 240V AC, -15% to +12%	

Multifunction Meter

Single Phase Multifunction Meter



MFM376
96(H) x 96(W) x 49(D)mm



MFM391
96(H) x 96(W) x 49(D)mm



MX300
96(H) x 96(W) x 50(D)mm

FEATURES	• Single pulse output • Run hour & Auxiliary interrupts • Phase angle detection • Demand measurement • RS485 MODBUS RTU protocol (MFM376-C-CE)	• 3Ø (Voltage, Current, PF, Frequency) • 3Ø Power (Active, Reactive, Apparent) • RPM • Run Hour	• True RMS measurement • Voltage, Current, Power, Power factor, Frequency • Programmable CT & PT • Communication and Relay output (applicable only for MX300-1-C-CE)
DISPLAY	7 segment LED		
DIGITS	3 rows of 4 digits	3 rows of 3 digits	1 row of 4 digits
ELECTRICAL CONNECTION	1Ø - 2W, 2Ø - 3W, 3Ø - 3W, 3Ø - 4W	3Ø - 3W, 3Ø - 4W	1Ø - 2W
RATED INPUT VOLTAGE	11 to 300V AC (L - N), 19 to 519V AC (L - L)		20 - 300V AC (L - N), 34 - 519V AC (L - L)
RATED INPUT CURRENT	Nominal 5A AC (Min - 14mA ; Max - 6A)	Nominal 5A AC (Min - 20mA, Max - 6A)	Nominal 5AAC (Min- 40mA, Max- 6A)
RESOLUTION	For energy : 0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M (Depending upon CT ratio x PT ratio), For Current, Voltage, Power : Auto resolution, For Power factor : 0.001	For Power, Voltage, Current : Auto Resolution, For Power Factor : 0.01	
ACCURACY	Voltage (L - N / L - L) : ±0.5% of F.S., Current : ±0.5% of F.S., Power Factor : ±0.01 Frequency : ±0.1% For L - N Voltage >20V, For L - L Voltage >35V, Power (Active, Reactive, Apparent) : 1%, Energy (Active, Reactive, Apparent) : Class 1	Voltage (L - N / L - L) : ±0.5% of F.S., Current : ±0.5% of F.S., Power Factor : ±0.01 Frequency : ±0.1% For L - N Voltage >11V, For L - L Voltage >35V, Power (Active, Reactive, Apparent) : 1%,	Voltage & Current : ±0.5% of F.S., Frequency : ± 1%, Active power : ± 1%, Reactive power : ± 2%
CT PRIMARY	1 / 5A to 10kA (Programmable for any value)		5A - 9999A (Programmable for any value)
CT SECONDARY	1 / 5A (Programmable)		5A fix
PT PRIMARY	100V to 500kV (Programmable for any value)		
PT SECONDARY	100V to 500V AC (Programmable for any value)		

	MFM376	MFM391	MX300
COMMUNICATION	RS485 MODBUS RTU protocol (applicable for MFM376-C-CE)	---	RS485 MODBUS RTU protocol (applicable for MX300-1-C-CE)
MEASURING PARAMETERS	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Power factor (Individual / Total), Active, Reactive & Apparent Power (Individual / Total), Active, Reactive & Apparent Energy (Total)	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Powerfactor (Individual / Average), Active, Reactive & Apparent Power (Individual / Average)	Voltage, Current, Power factor, Frequency, Power (Active, Reactive Apparent)
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	40 to 300V AC / DC	85V to 270V AC	85 to 300V AC / DC

DIN Rail Multifunction Meter

Plug-N-Wire Multifunction Meter



MFM384-R-C
90(H) x 70(W) x 66.3(D)mm



MRJ4M-QUAD
90(H) x 70(W) x 66.3(D)mm

FEATURES	- Energy (Active, Reactive, Apparent) - RS485 MODBUS RTU protocol - Import / Export energy - Demand measurement	- Energy (Active, Reactive) - RJ45 connector current input - Single pulse output - Max demand of power - Self powered
DISPLAY	LCD with backlight	
DIGITS	1 row of 4 digits, 2 rows of 7 digits	
ELECTRICAL CONNECTION	1Ø - 2W, 2Ø - 3W, 3Ø - 3W, 3Ø - 4W	1Ø - 2W, 3Ø - 4W
RATED INPUT VOLTAGE	11 to 300V AC (L - N), 19 to 519V AC (L - L)	60 to 300V AC (L - N), 104 to 520V AC (L - L)
RATED INPUT CURRENT	Nominal 5A AC (Min - 11mA; Max - 6A)	---
FREQUENCY	45Hz to 65Hz	
RESOLUTION	For Energy : 0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M (Depending upon CT ratio x PT ratio), For Power, Voltage, Current : Auto resolution, For Power factor : 0.01, Frequency : 0.1Hz	0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M (depending upon CT ratio x PT ratio), For Power, Voltage : Auto resolution, For Power factor : 0.01
ACCURACY CLASS	Voltage (L - L / L - N), Current : $\pm 0.5\%$ of F.S., Power factor : ± 0.01 , Frequency : $\pm 0.1\%$ of F.S., Power (kW, kVA, kVAr) : 1% of F.S., Energy (Active, Reactive, Apparent) : 1% of F.S.	
CT PRIMARY	1 / 5A to 10kA (Programmable for any value)	1A to 1kA (Programmable for any value), Plug-N-Wire CTs to be used
CT SECONDARY	1 / 5A (Programmable)	330mV through Plug-N-Wire CT output
PT PRIMARY	100V to 500kV (Programmable for any value)	100V to 10kV (Programmable for any value)
PT SECONDARY	100V to 500V AC (L - L) (Programmable for any value)	
MEMORY RETENTION FOR ENERGY	10 years	
COMMUNICATION	RS485 MODBUS RTU protocol	
INDICATIONS	LCD : Max demand of power, Communication in progress; LED : Integration of energy	
MEASURING PARAMETERS	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Power factor (Individual / Total), Active, Reactive & Apparent power (Individual / Total), Active, Reactive & Apparent energy (Import / Export), Demand (Min / Max Active & Reactive Power, Max apparent power)	Voltage (L - L / L - N) (Individual / Average) of 4 Channels, Current (Individual / Average) of 4 Channels, Power (Active, Reactive & Apparent) (Individual) of 4 Channels, Power factor & Frequency of 4 Channels, Energy (Active, Reactive & Apparent) (Individual / Total) of 4 Channels
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	85 to 270V AC	60 to 300V AC, Self powered (V1, N)

Plug-N-Wire Multifunction Meter



MRJ4M
90(H) x 70(W) x 62(D)mm



MRJ4M-SL
90(H) x 70(W) x 62(D)mm



MRJ385
96(H) x 96(W) x 50(D)mm

FEATURES	- Energy (Active, Reactive) - RJ45 connector current input - Single pulse output - Max demand of power - Self powered	- Energy (Active, Reactive) - Split load, RJ45 connector current input 2 pulse outputs - Max demand of power - Self powered	- Energy (Active, Reactive, Apparent) - RJ45 connector current input - Single pulse output - Demand measurement - Self powered %THD up to 31st level
DISPLAY	LCD with backlight		
DIGITS	2 rows of 4 digits, 1 row of 7 digits to show electrical parameters		4 rows of 4 digits, Bar graph representation for current, 1 row of 8 digits for energy display

	MRJ4M	MRJ4M-SL	MRJ385
ELECTRICAL CONNECTION	1Ø - 2W, 3Ø - 4W		
RATED INPUT VOLTAGE	60 to 300V AC (L - N), 104 to 520V AC (L - L)		100 to 240V AC (L - N), 173 to 415V AC (L - L)
RESOLUTION	For Energy : 0.01K, 0.1K, 1K, 0.01M, 0.1M, 1M (Depending upon CT ratio x PT ratio), For Power, Voltage, Current : Auto resolution For Power factor : 0.01		
CT PRIMARY	5A to 10kA (Programmable for any value), Plug-N-Wire CTs to be used		
CT SECONDARY	330mV through Plug-N-Wire CT output		
PT PRIMARY	100V to 10kV (Programmable for any value)		100V to 500kV (Programmable for any value)
PT SECONDARY	100 to 500V AC (L - L) (Programmable for any value)		173 to 415V AC (L - L) (Programmable for any value)
COMMUNICATION	RS485 MODBUS RTU protocol		
INDICATIONS	LCD : Max demand of power, communication in progress ; LED : Integration of energy		LCD : Max / Min demand of power, communication in progress ; Integration of energy, Unit in configuration menu
MEASURING PARAMETERS	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Power factor (Individual / Average), Active, Reactive & Apparent power (Individual / Total), Active & Reactive energy, Demand (Max active power, Max apparent power)	Voltage (L - L / L - N) (Individual / Average), Current (Individual), Frequency, Power factor (Individual / Average), Active, Reactive, Apparent power (Individual / Total), Active & Reactive energy, Total, Active & Reactive energy (Current input-1 plus current Input-2), Demand (Max active power, Max apparent power)	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Power factor (Individual / Average), Active, Reactive, Apparent power (Individual / Total), Active, Reactive, Apparent energy (Phase wise (Import / Export) & Total (Import / Export)), Demand (Min / Max active power, Min / Max reactive power, Max apparent power), Harmonics individual for voltage & Current upto 31 st level.
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	60 to 300V AC, Self powered (V1, N)		100 to 240V AC, Self powered (V1, N)


Plug-N-Wire Current Transformer




PWCT - 15 / 30
Primary current : 60A to 160A



PWCT - 16 / 20
Primary current : 60A to 160A



PWCT - 21 / 25
Primary current : 60A to 250A



PWCT - 31 / 31
Primary current : 150A to 630A



PWCT - 54 / 50
Primary current : 800A to 1600A

FEATURES	• RJ45 connector, 330mV output • Safe to leave transformers on load with output disconnected • Foot, busbar or DIN rail mounting • Fits standard moulded circuit breaker frame sizes • Available in 21 x 25mm, 31 x 31mm, 54 x 50mm apertures • 15 x 30mm & 16 x 20mm aperture sizes available on special request
----------	--

Plug-N-Wire Accessories



PWCBL_CON-F-3
PWCBL_CON-F-1



PWCBL_CON-M/F-3
PWCBL_CON-M/F-1



PWCON-Male
PWCON-Female

DESCRIPTION	Power cable with Female type connector, 1 & 3 Meter length	Daisy chain cable to loop MRJ meters with Male & Female type connectors, 1 & 3 Meter length	Voltage connector Male / Female
	CTV Converter 1A/330mV	PWADP-5A	PWADP-1A
DESCRIPTION	Converter used with PLCTs for MRJ multifunction meter series	5A adapter to use with conventional CT for MRJ4M, MRJ4M-SL & MRJ385-G-PNW	1A adapter to use with conventional CT for MRJ4M-QUAD meter

Additional accessories : ACH-003, ACH-004, AC-IOEXP-03, AC-USB-RS485-02, AC-USB-RS485-03 (On page no. 45)



EM306
96(H) x 96(W) x 50(D)mm

EM306-C-D
96(H) x 96(W) x 50(D)mm



EM368
96(H) x 96(W) x 50(D)mm

FEATURES	3Ø Active energy - Single pulse output	- Dual Input Meter (Mains / D.G) 3Ø Power (Active / Reactive) 3Ø Energy (Active / Reactive) - Power factor (Phase / Average)	- Pulse output for energy - Power (Active / Reactive) - Energy (Active / Reactive / Apparent)
DISPLAY	7 segment LED		LCD with backlight
DIGITS	1 row of 6 digits		1 row of 8 digits
ELECTRICAL CONNECTION	1Ø - 2W, 2Ø - 3W, 3Ø - 3W, 3Ø - 4W		
RATED INPUT VOLTAGE	11 to 300V AC (L - N), 19 to 519V AC (L - L)		
RATED INPUT CURRENT	Nominal 5A AC (Min - 15mA ; Max - 6A)		Nominal 5A AC (Min - 11mA ; Max - 6A)
RESOLUTION	For Energy : 0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M For Power, Voltage, Current : Auto resolution, For Power factor : 0.001		For energy : 0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M, 10M (Depending upon CT ratio x PT ratio) For Power : Auto resolution, For Power factor : 0.01
ACCURACY	Voltage (L - N), Current : $\pm 0.5\%$ of F.S. Power factor : ± 0.01 , Frequency : $\pm 0.1\%$ of F.S. Power (kW, kVA, kVAR) : 1% of F.S., Active energy : Class 1, Reactive energy : Class 2		Active Energy : Class 1, Reactive / Apparent Energy : $\pm 1\%$ Active / Reactive power : $\pm 1\%$, PF & Avg. PF : $\pm 1\%$
POWER CONSUMPTION	8VA max		
CT PRIMARY	1 / 5A to 10kA (Programmable for any value)		
CT SECONDARY	1 / 5A (Programmable)		
PT PRIMARY	100V to 500kV (Programmable for any value)		
PT SECONDARY	100V to 500V AC (L - L) (Programmable for any value)		
COMMUNICATION	--- RS485 MODBUS RTU protocol		
MEASURING PARAMETERS	Active Energy	CT Reverse detection, Communication in progress, Kilo, Mega, DG sensing	Power (Total Active / Reactive), Energy (Total Active / Reactive / Apparent), Power factor (Individual & Average)
LED INDICATIONS	CT Reverse detection, Kilo, Mega	CT rev, Kilo, Mega, Communication, DG	Integration of energy, Resolution is 10, Reverse connected CT warning, Communication in progress, Pulse output (All Indications on LCD)
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	85 to 276 V AC		

Energy Meters



EM2M
90(H) x 35(W) x 66.3(D)mm



EM4M-3P-C-100A
90(H) x 70(W) x 66.3(D)mm

EM4M-3P-W-100A
90(H) x 70(W) x 66.3(D)mm

FEATURES	• 1Ø, 100A direct connection • Multifunction parameter monitoring • Import / Export energy • 2 Pulse outputs	• 3Ø, 100A direct connection • Dual input meter (Mains / D.G) • Multifunction parameter monitoring • Import / Export energy • 2 Pulse outputs • Secured in-built WiFi, MQTT protocol based (Applicable for EM4M-3P-W-100A)	
DISPLAY	LCD with backlight		Blind display with LED indications
DIGITS	1 row of 7 digits	1 row of 4 digits & 2 rows of 7 digits	---
ELECTRICAL CONNECTION	1Ø - 2W	1Ø - 2W, 2Ø - 3W, 3Ø - 3W, 3Ø - 4W	
RATED INPUT VOLTAGE	176 to 276V AC (L - N)	85 to 285V AC (L - N) ; 148-494V AC (L - L)	
RATED INPUT CURRENT	Ib : 10A (IMin - 500mA, IMax - 100A)		
RESOLUTION	For Energy : 0.01k, For Power, Voltage, Current : Auto resolution, For Power factor : 0.01		
ACCURACY	Voltage (L - N), Current : ±0.5% of F.S., Power factor : ±0.01, Frequency : ±0.1% of F.S. Power (kW, kVA, kVAr) : 1% of F.S., Active energy : Class 1, Reactive energy : Class 2		
POWER CONSUMPTION	8VA max		
COMMUNICATION	RS485 MODBUS RTU protocol		Secured in-built WiFi, MQTT protocol based
MEASURING PARAMETERS	Voltage, Current, Frequency, Power factor, Import / Export, Max demand for power	Mains/DG Voltage, Current, Frequency, Power factor, Power, Energy, Active, Reactive (Import/Export) Energy, Max demand power	
LED INDICATIONS	LCD Indication-communication in progress, Max demand of power, Import & export energy, LED-2 for Pulse output 1, Pulse output 2		LED- Power ON, Wi-Fi, Pulse output 1, Pulse output 2
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	176 to 276V AC (L-N), Self powered	Self - Powered, 85 to 285V AC (L - N), 120 to 494V AC (L - L) DG Sensing: 85 to 285V AC	



VAF391
96(H) x 96(W) x 49(D)mm



VAF36A
96(H) x 96(W) x 50(D)mm



VAF39A-1
96(H) x 96(W) x 50(D)mm

FEATURES	• 3Ø (True RMS) Voltage • 3Ø (True RMS) Current • 3Ø Power & Power factor • RUN hour / RPM measurement	• 3Ø (True RMS) Voltage • 3Ø (True RMS) Current • Frequency • RUN hour / RPM measurement • Bar graph for current representation	• 3Ø (True RMS) Voltage • 3Ø (True RMS) Current • Frequency • RUN hour / RPM measurement
DISPLAY	7 segment LED	LCD with backlight	7 segment LED
DIGITS	3 rows of 3 digits		
ELECTRICAL CONNECTION	3Ø - 3W, 3Ø - 4W	1Ø - 2W, 2Ø - 3W, 3Ø - 3W, 3Ø - 4W	
RATED INPUT VOLTAGE	11 to 300V AC (L - N), 19 to 519V AC (L - L)		
RATED INPUT CURRENT	Nominal 5A (Min - 20mA, Max - 6A)		Nominal 5A (Min - 30mA ; Max - 6A)
RESOLUTION	For Power, Voltage, Current : Auto Resolution For Power Factor : 0.01	Current & Voltage : Depending on CT & PT primary setting, RPM : 0.1, Run hour : 0.1hr	
ACCURACY	For Power, Voltage, Current : Auto Resolution, For Power Factor : 0.01	Voltage (L - N / L - L / Average) : ± 0.5% of F.S. ± 2 digits, Current & Average Current : ± 1% of F.S. ± 2 digits, Run hour : ± 1%, RPM : ± 0.5%, Frequency : ± 0.1 Hz ± 1 digit	
CT PRIMARY	1 / 5A to 10kA (Programmable for any value)	5A to 10kA (Programmable for any value)	
CT SECONDARY	1 / 5A (Programmable)	5A fix	
PT PRIMARY	100V to 500kV (Programmable for any value)	100V to 500kV (Programmable for any value)	
PT SECONDARY	100 to 500V AC (L - L) (Programmable for any value)	100 to 500V AC (L - L) (Programmable for any value)	
MEASURING PARAMETERS	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency, Powerfactor (Individual / Average), Active, Reactive & Apparent Power (Individual / Average)	Voltage (L - L / L - N) (Individual / Average), Current (Individual / Average), Frequency	
ADDITIONAL FUNCTIONS	Power & Power factor measurement	---	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	85V to 270V AC	230V AC ±20%	

Digital Voltmeters

Digital Ammeters



MV35
96(H) x 96(W) x 50(D)mm



MA32
96(H) x 96(W) x 50(D)mm

FEATURES	1Ø & 3Ø True RMS measurement - Wide auxiliary supply from 40 to 300V AC/DC - PT Primary programmable up to 999.0kV - K LED for kilo indication	1Ø & 3Ø True RMS measurement - Wide auxiliary supply from 40 to 300V AC/DC - CT Primary programmable up to 999.0kA - K LED for kilo indication
DISPLAY	7 segment LED	
DIGITS	4 digits	
ELECTRICAL CONNECTION	1Ø - 2W, 3Ø - 3W, 3Ø - 4W	
RATED INPUT VOLTAGE	11 to 300V AC (L - N), 19 to 516V AC (L - L)	---
RATED INPUT CURRENT	---	5AAC (Min - 50mA ; Max - 6.2A)
RESOLUTION	Auto resolution depend upon PT ratio	Auto resolution depend upon CT ratio
ACCURACY	$\pm 0.5\%$ of F.S.	
CT PRIMARY	---	1 / 5A to 999.0kA (Programmable for any value)
CT SECONDARY	---	1 / 5A (Programmable)
PT PRIMARY	100 to 999kV (Programmable for any value)	---
PT SECONDARY	100 to 500V (Programmable for any value)	---
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	40 to 300V AC / DC	



MV15
48(H) x 96(W) x 50(D)mm



MV205
72(H) x 72(W) x 50(D)mm



MV305
96(H) x 96(W) x 46(D)mm



MV334-230V
96(H) x 96(W) x 50(D)mm

FEATURES	• True RMS measurement • For 1Ø - 2 wire electrical network	• True RMS measurement • For 1Ø - 2 wire, 3Ø - 3 wire, 3Ø - 4 wire electrical network • Programmable PT primary & secondary
DISPLAY	7 segment LED	
DIGITS	3 digits	4 digits
ELECTRICAL CONNECTION	1Ø - 2W	1Ø - 2W, 3Ø - 3W, 3Ø - 4W
RATED INPUT VOLTAGE	50 to 480V AC (516V max)	11 to 300V AC (L - N), 19 to 516V AC (L - L)
RESOLUTION	1V	Auto resolution
ACCURACY	± 0.5% of F.S.	± 0.5% of F. S.
PT PRIMARY	---	100V - 999kV
PT SECONDARY	---	100V - 500V
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	240V AC ±20%	230V AC ±20%

Digital Ammeters



MA12
48(H) x 96(W) x 50(D)mm



MA202
72(H) x 72(W) x 50(D)mm



MA302
96(H) x 96(W) x 46(D)mm



MA12-75mV-DC
48(H) x 96(W) x 50(D)mm



MA12-20A-AC
48(H) x 96(W) x 50(D)mm



MA335-230V AC
96(H) x 96(W) x 50(D)mm

FEATURES	• True RMS measurement • For 1Ø - 2 wire electrical network • CT primary programmable up to 4000A	• True RMS measurement • For 1Ø - 2 wire electrical network	• True RMS measurement • For 1Ø - 2 wire, 3Ø - 3 wire, 3Ø - 4 wire electrical network • Programmable CT primary & secondary
DISPLAY	7 segment LED		
DIGITS	4 digits		
ELECTRICAL CONNECTION	1Ø - 2W		
INPUT TYPE	CT	Shunt	Direct
RATED INPUT CURRENT	5A AC (Min - 50mA ; Max - 6.2A)	0 to 75mV DC	20A Direct
RESOLUTION	0.001, 0.01, 0.1, 1A (Depending upon CT primary settings)	0.001, 0.01, 0.1, 1A (Depending upon shunt settings)	0.001, 0.01, 0.1, 1A
ACCURACY	± 0.5% of F.S.		
CT PRIMARY / SHUNT SETTING	5 to 4000A (Programmable in steps)	---	1 to 999.0kA (Programmable for any value)
CT SECONDARY	5A fix	---	1 / 5A (Programmable)
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	240V AC ±20%		
			230V AC ±20%

Digital Ammeters

Digital Voltmeters



MA501
48(H) x 48(W) x 68.5(D)mm



MA2301
72(H) x 72(W) x 50(D)mm



MV507
48(H) x 48(W) x 68.5(D)mm



MV2307
72(H) x 72(W) x 50(D)mm

FEATURES	• True RMS measurement • Bar graph for current representation • CT primary programmable up to 5000A	• True RMS measurement • Bar graph for current representation • CT primary programmable up to 5000A • Selector switch for page selection	• True RMS measurement • Bar graph for voltage representation	• True RMS measurement • Bar graph for voltage representation • Selector switch for page selection
DISPLAY	LCD with backlight			
DIGITS	4 digits		3 digits	
ELECTRICAL CONNECTION	1Ø - 2W	3Ø - 4W	1Ø - 2W	3Ø - 3W, 3Ø - 4W
RATED INPUT VOLTAGE	---		50 to 480V AC (Max : 516V)	
RATED INPUT CURRENT	5A AC (Min - 50mA; Max - 6.2A)		---	
RESOLUTION	0.001, 0.01, 0.1, 1A (Depending on CT primary settings)		1V	
ACCURACY	± 0.5% of F.S.			
CT PRIMARY	5 to 5000A (Programmable in steps)		---	
CT SECONDARY	5A fix		---	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	240V AC ±20%			

Voltage Ampere Meters



MVA591-30A
48(H) x 48(W) x 68.5(D)mm



MVA591-80A
48(H) x 48(W) x 68.5(D)mm



MVA593
48(H) x 48(W) x 79(D)mm

FEATURES	• True RMS measurement • 3 Digit 7 segment dual line display • Direct 30A & 80A measurement with Hanging CT	• True RMS measurement • Measure 1Ø & 3Ø voltage and current • 3 digit 7 segment dual line display • Works with 1 phase and 3 phase CT
DISPLAY PARAMETERS	Voltage & Current	
DISPLAY	3 digits 7 segment LED display with dual rows	
COLOUR	Red and Green	
ELECTRICAL CONNECTION	1Ø - 2W	1Ø - 2W, 3Ø - 3W, 3Ø - 4W
RESOLUTION	Voltage : 1V; Current : 0.1A	For Current <10A : 0.01A, <100A : 0.1A, >100A : 1A For Voltage <100V : 0.1V, >100V : 1V
RATED INPUT VOLTAGE	230V AC (± 20%)	
RATED INPUT CURRENT	1 to 30A	4 to 80A
OPERATING FREQUENCY	50Hz (±5%)	
CURRENT OVERLOAD	36A	96A
ACCURACY	±1% full scale	
SUPPLY VOLTAGE	230V AC, ±20%	

MVA593 Accessories



CT 3PH-D13MM-80A-G



CT 3PH-21X25MM-250A-G



CT 1PH-D13MM-80A-G



CT 1PH-30X10MM-250A-G



3PH 5A CONVERTER-G

RATED INPUT CURRENT	Nominal 80A AC (Min 4A - Max 96A)	Nominal 250A AC (Min 10A - Max 300A)	Nominal 80A AC (Min 4A - Max 96A)	Nominal 250A AC (Min 10A - Max 300A)	Nominal 5A AC (Min 50mA - Max 6A)
NO. OF PHASES	3		1		3
INNER DIA	13mm	21x 25mm	12mm	30x10mm	4.85mm
MOUNTING	Din rail & Wall mount				



AM - V
72(H) x 72(W) x 60(D)mm /
96(H) x 96(W) x 60(D)mm



AM - I
72(H) x 72(W) x 60(D)mm /
96(H) x 96(W) x 60(D)mm



AM - Direct Type Ammeter
72(H) x 72(W) x 60(D)mm /
96(H) x 96(W) x 60(D)mm



AM - Power Factor
72(H) x 72(W) x 60(D)mm /
96(H) x 96(W) x 60(D)mm



AM - Frequency
72(H) x 72(W) x 60(D)mm /
96(H) x 96(W) x 60(D)mm

FEATURES	• True RMS (Voltage) measurement • Scale inter changeability • Non linear scale • Easy installation / termination		• True RMS (Current) measurement • Scale inter changeability • Non linear scale • Easy installation / termination		• True RMS (Current) measurement • Non linear scale • Easy installation / termination	• Non linear scale • Easy installation / termination	• Linear scale • Easy installation / termination
MEASURING PARAMETERS	AC Voltage		AC Current		Direct meter	Power factor	Frequency
POINTER DEFLECTION			0 to 90°			45° - 0° - 45°	0 to 90°
SCALE CHARACTERISTICS			Non linear				Linear
SCALE LENGTH			72 x 72mm: 63 mm / 96 x 96mm: 97 mm				
MEASURING RANGE	0 to 300V / 500V		0 to 5A (CT Secondary), Suppress scale :0 to 5 / 30A (CT Secondary)		10A to 100A	0.5CAP - 1 - 0.5IND	45 - 65Hz
ACCURACY			Class 1.5				Class 1.0
FREQUENCY			50 / 60Hz				---

Current Transformers



Square



Split Core



Cable



Tape Wound

FEATURES	• Use with different bus bar size • Panel/DIN rail mount (Require optional accessory) • Accuracy : Class 0.5 to 5		• Nominal rating ranges from 100A to 6000A • Snap closing / opening feature • Mounting types : Base, Busbar & Wall mount		• Sealable terminal / Wire type output • Panel mount • Accuracy : Class 1 to 5	• Terminal output • Accuracy : Class 0.5 to 5
RATED PRIMARY RATING	30 to 4000A		10 to 6000A		30 to 600A	30 to 1600A
RATED SECONDARY OUTPUT			5A			
RATED BURDEN (VA)	1,1.25, 1.5, 2.5, 3, 3.75, 5, 7.5, 10, 15		1,1.5, 2.5, 3, 5, 7.5, 10, 15		1.5, 5	1.5, 5, 10
ACCURACY	0.5, 1, 3, 5		0.5, 1, 3		1, 5	0.5, 1, 5
OPERATING FREQUENCY			AC 50 / 60Hz			
SYSTEM VOLTAGE			720V max			
APPLICABLE STANDARD			IEC 61869-2			

Power Factor Controllers



APFC148 : With 3 CT sensing
144(H) x 144(W) x 50(D)mm



APFC146 : With 1 CT sensing
144(H) x 144(W) x 50(D)mm



APFC346 : With 1 CT sensing
96(H) x 96(W) x 55(D)mm



APFC147 : With 1 CT sensing
144(H) x 144(W) x 50(D)mm



APFC347 : With 1 CT sensing
96(H) x 96(W) x 55(D)mm

FEATURES	• 3 CT sensing with VAF metering function built in • Configurable up to 12/14* stages • Configurable alarm settings • Dual Colour Backlight for indicating Normal & Alarm function • RS485 MODBUS RTU protocol		• 1 CT sensing • Intelligent switching sequence • Configurable up to 12 stages • Alarm for No current, Phase current error & over temperature • Automatic sensing of capacitor bank values		• 1 CT sensing • Intelligent switching sequence • Configurable up to 8 stages • Alarm for No voltage, Phase current error • Automatic sensing of capacitor bank values	• 1 CT sensing • Intelligent switching sequence • Configurable up to 8 & 12 stages • Automatic sensing of capacitor bank values	• 1 CT sensing • Intelligent switching sequence • Configurable up to 8 • Automatic sensing of capacitor bank values
DISPLAY	LCD with dual colour backlight		LCD with backlight		7 segment LED		
DIGITS	3 rows, 4 digits to show electrical parameters				1 row, 4 digits to show power factor		
ELECTRICAL CONNECTION	1Ø - 2W, 2Ø - 2W, 3Ø - 3W, 3Ø - 4W		2Ø - 2W (L2-L3)		1Ø - 2W, 2Ø - 2W		

	APFC148 : With 3 CT sensing	APFC146 : With 1 CT sensing	APFC346 : With 1 CT sensing	APFC147 : With 1 CT sensing	APFC347 : With 1 CT sensing
RATED INPUT VOLTAGE	100 to 300V AC (L - N), 50 to 520V AC (L - L)	50 to 520V AC (L-L)		40 to 300V AC (L - N), 50 to 520V AC (L - L)	
RATED INPUT CURRENT	Nominal 5A AC (Min - 11mA; Max - 6A)		Nominal 5A AC (Min 50mA, Max 6A)		
POWER CONSUMPTION	15VA max		7VA max	15VA max	7VA max
FREQUENCY	45 to 65Hz				
MEASUREMENT RANGE	Power Factor : 0.8 lag to 0.8 lead				
ALARM SETTINGS	Over / Under voltage, Over / Under-compensation, CT polarity error, Over-temperature, Fan setting, No voltage, THDI.	Over Temperature Error, CURR : Phase current error	No Voltage Alarm, CURR : Phase current error	Over / Under voltage, Over / Under compensation, CT polarity error, CURR : Phase current error, No volt	
PHASE COMPENSATION	0°, 90°, 120°, 210°, 240°, 330°	---		0°, 90°, 120°, 210°, 240°, 330°	
ACCURACY	Power factor : ± 0.01, Voltage (L-N/L-L), Current : ±0.5% of F.S., Frequency : For L-N > 20V For L-L >35V : ±0.1% of F.S., Power (kW, kVA, kVAh) : 1%, Energy (kWh, kVAh, kVAh) : Class 1, Temperature : ±3°C of F.S.	Power factor : ±0.01, Temperature : ±3° of full scale	Power factor : ±0.01		
CT PRIMARY	5A to 9999A (Programmable for any value)	---		5A fix	
CT SECONDARY	5A fix	---		5A fix	
PT PRIMARY	100V to 500kV (Programmable for any value)	---			
PT SECONDARY	100 to 500V (Programmable for any value)	---			
STEPS	1 to 12 / 14* *(FAN & ALARM output can be used as 13° & 14° step)	1 to 12	1 to 8		
RELAY CONTACT	5A @ 250V AC				
SWITCHING PROGRAM	Automatic				
STEP TIME	1 to 999s				
DISCHARGE TIME	1 to 999s				
CONTROL MODE	Automatic / Manual				
CONTROL SENSITIVITY	60%	---		60%	
AUTO INITIALIZATION	Yes / No	Yes		Yes / No	
COMMUNICATION	RS485 MODBUS RTU protocol* *(Only for 12 stage variant)	---			
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 550V AC		85 to 270V AC	90 to 550V AC	85 to 270V AC

Ordering information

Multifunction Meters

PRODUCT CODE	SUPPLY VOLTAGE	OUTPUT		CERTIFICATION
		PULSE OUTPUT	COMM. (RS485)	
MFM384-C-CU	85 to 300V AC, ±5%	YES	YES	CE
MFM384-C-CE *	85 to 300V AC, ±5%	YES	YES	CE
MFM384-C-CE-CL05	85 to 300V AC, ±5%	YES	YES	CE
MFM384-R-C-CE *	85 to 270V AC	YES	YES	CE
MFM284-C-CE	85 to 270V AC	YES	YES	CE
MFM383A	100 to 240V AC, -15% to ±12%	YES	---	---
MFM383A-C-CE	100 to 240V AC, -15% to ±12%	YES	YES	CE
MFM376-CE	40 to 300V AC/DC	YES	---	---
MFM376-C-CE	40 to 300V AC/DC	YES	YES	CE
MFM391	85 to 270V AC	YES	---	CE
MX300-CE	85 to 300V AC	---	---	CE
MX300-1-C-CE	85 to 300V AC	---	YES	CE

Multifunction Meters

PRODUCT CODE	SUPPLY VOLTAGE	OUTPUT		CERTIFICATION
		PULSE OUTPUT	COMM. (RS485)	
MRJ4M *	Self powered (V1, N), 60 to 300V AC	YES	YES	CE
MRJ4M-SL *	Self powered (V1, N), 60 to 300V AC	YES	YES	CE
MRJ385-G-PNW *	Self powered (V1, N), 100V to 240V AC	YES	YES	CE
MRJ4M-QUAD	Self powered (V1, N), 60 to 300V AC	---	YES	CE

NOTE : * MID variants available

Current Transformers

PRODUCT CODE	PRIMARY	OUTPUT	CERTIFICATION
PWCT-15/30-60A/330mV	60A	330mV	CE
PWCT-15/30-100A/330mV	100A	330mV	CE
PWCT-15/30-125A/330mV	125A	330mV	CE
PWCT-15/30-160A/330mV	160A	330mV	CE
PWCT-16/20-60A/330mV	60A	330mV	CE
PWCT-16/20-100A/330mV	100A	330mV	CE
PWCT-16/20-125A/330mV	125A	330mV	CE
PWCT-16/20-160A/330mV	160A	330mV	CE
PWCT-16/20-200A/330mV	200A	330mV	CE
PWCT-21/25-60A/330mV	60A	330mV	CE
PWCT-21/25-100A/330mV	100A	330mV	CE
PWCT-21/25-125A/330mV	125A	330mV	CE
PWCT-21/25-160A/330mV	160A	330mV	CE
PWCT-21/25-200A/330mV	200A	330mV	CE
PWCT-21/25-250A/330mV	250A	330mV	CE
PWCT-31/31-250A/330mV	250A	330mV	CE
PWCT-31/31-300A/330mV	300A	330mV	CE
PWCT-31/31-400A/330mV	400A	330mV	CE
PWCT-31/31-500A/330mV	500A	330mV	CE
PWCT-31/31-600A/330mV	600A	330mV	CE

Current Transformers

PRODUCT CODE	PRIMARY	OUTPUT	CERTIFICATION
PWCT-31/31-630A/330mV	630A	330mV	CE
PWCT-54/50-800A/330mV	800A	330mV	CE
PWCT-54/50-1000A/330mV	1000A	330mV	CE
PWCT-54/50-1250A/330mV	1250A	330mV	CE
PWCT-54/50-1600A/330mV	1600A	330mV	CE

Plug-N-Wire Accessories

PRODUCT CODE	DESCRIPTION
PWCBL_CON-F-1	Power cable with Female type connector, 1 Meter length
PWCBL_CON-F-3	Power cable with Female type connector, 3 Meter length
PWCBL_CON-M/F-1	Daisy chain cable to loop MRJ meters with Male & Female type connectors, 1 Meter length
PWCBL_CON-M/F-3	Daisy chain cable to loop MRJ meters with Male & Female type connectors, 3 Meter length
PWCON-M	Voltage connector Male
PWCON-F	Voltage connector Female
CTV Converter 1A/330mV	Converter used with PLCTs for MRJ multifunction meter series
PWADP-5A	5A adapter to use with conventional CT for MRJ4M, MRJ4M-SL & MRJ385-G-PNW
PWADP-1A	1A adapter to use with conventional CT for MRJ4M-QUAD meter

Energy Meters

PRODUCT CODE	SUPPLY VOLTAGE	OUTPUT		CERTIFICATION
		PULSE OUTPUT	COMM. (RS485)	
EM306	100 to 240V AC, -15% to +12%	YES	---	---
EM306-C-D	100 to 240V AC, -15% to +12%	---	YES	---
EM368-C-CU	100 to 240V AC, -15% to +12%	YES	YES	CE
EM2M-1P-C-100A *	176 to 276V AC (Self powered)	YES	YES	CE
EM4M-3P-C-100A	85 to 285V AC (L-N), 150 to 494V AC (L-L)	YES	YES	CE
EM4M-3P-W-100A	85 to 285V AC (L-N), 150 to 494V AC (L-L)	YES	WI-FI	CE

Voltage Ampere Frequency Meters

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
VAF391	85 to 276V AC	---
VAF36A-230-CE	230V AC	CE
VAF39A-1-230V	230V AC	---
VAF39A-1-230V-CE	230V AC	CE
VAF39A-1-60V DC	20 to 60V DC	---

LCD (Ammeters / Voltmeters)

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
MV35-3-G-40/300V-CE	40-300V AC / DC	CE
MV35-1-G-40/300V-CE	40-300V AC / DC	CE
MA32-3-G-40/300V-CE	40-300V AC / DC	CE
MA32-1-G-40/300V-CE	40-300V AC / DC	CE

LED (Voltmeters)

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
MV15	240V AC, $\pm 20\%$	---
MV15-CE	240V AC, $\pm 20\%$	CE
MV205	240V AC, $\pm 20\%$	---
MV205-CE	240V AC, $\pm 20\%$	CE
MV305	240V AC, $\pm 20\%$	---
MV305-CE	240V AC, $\pm 20\%$	CE
MV334-230V	230V AC	---
MV334-230V-CE	230V AC	CE

LED (Ammeters)

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
MA12	240V AC, $\pm 20\%$	---
MA12-CE	240V AC, $\pm 20\%$	CE
MA12-20A-AC	240V AC, $\pm 20\%$	---
MA202	240V AC, $\pm 20\%$	---
MA202-CE	240V AC, $\pm 20\%$	CE
MA302	240V AC, $\pm 20\%$	---
MA302-CE	240V AC, $\pm 20\%$	CE
MA335-230VAC	230V AC	---
MA335-230VAC-CE	230V AC	CE

LCD (Ammeters / Voltmeters)

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
MA501-230V-CE	240V AC, $\pm 20\%$	CE
MA501-CU	240V AC, $\pm 20\%$	CE
MA2301-230V-CE	240V AC, $\pm 20\%$	CE
MV507-230V-CE	240V AC, $\pm 20\%$	CE
MV2307-230V-CE	240V AC, $\pm 20\%$	CE

Voltage Ampere Meters

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
MVA591-30A-230V	230V AC, $\pm 20\%$, 50/60Hz	---
MVA591-80A-230V	230V AC, $\pm 20\%$, 50/60Hz	---
MVA593-CE	85 - 276V AC, 50/60Hz	CE

MVA593 Accessories


PRODUCT CODE	CURRENT RANGE	CERTIFICATION
CT 1PH-D13MM-80A-G	80A	CE
CT 1PH-30X10MM-250A-G	250A	CE
CT 3PH-D13MM-80A-G	80A	CE
CT 3PH-21X25MM-250A-G	250A	CE
3PH 5A CONVERTER-G	800A	CE

Power Factor Controllers

PRODUCT CODE	SUPPLY VOLTAGE	OUTPUT		CERTIFICATION
		STEPS	COMM. (RS485)	
APFC148-312-90/550V	90 to 550V AC, 50 / 60Hz	12	YES	---
APFC147-108-90/550V	90 to 550V AC, 50 / 60Hz	8	---	---
APFC347-108-230V	85 to 270V AC, 50 / 60Hz	8	---	---
APFC148-312-90/550V-CE	90 to 550V AC, 50 / 60Hz	12	YES	CE
APFC147-108-90/550V-CE	90 to 550V AC, 50 / 60Hz	8	---	CE
APFC347-108-230V-CE	85 to 270V AC, 50 / 60Hz	8	---	CE
APFC146-112-90/550V-CE	90 to 550V AC, 50 / 60Hz	12	---	CE
APFC346-108-230V-CE	85 to 270V AC, 50 / 60Hz	8	---	CE

Analog Voltmeters

PRODUCT CODE	CERTIFICATION
AM-V-2-N-CE-RoHS	CE
AM-V-3-N-CE-RoHS	CE
AM-V-2-L-CE-RoHS	CE
AM-V-3-L-CE-RoHS	CE
AM-V-2-N	---
AM-V-3-N	---
AM-V-2-L	---
AM-V-3-L	---



NOTE : * MID variants available

Analog Ammeters

PRODUCT CODE (Meters without dial plates)	CERTIFICATION	
AM-I-2-5A-WD-CE-RoHS	CE	AM - I - 2 - 5A - 6S - WD Without dial plate 6 times suppress Secondary current (Size) 2 : 72 x 72mm, 3 : 96 x 96mm (Series) Ammeter (Category) Analog meter
AM-I-2-5A-6S-WD-CE-RoHS	CE	
AM-I-3-5A-WD-CE-RoHS	CE	
AM-I-3-5A-6S-WD-CE-RoHS	CE	
AM-I-2-5A-WD	---	
AM-I-2-5A-6S-WD	---	
AM-I-3-5A-WD	---	
AM-I-3-5A-6S-WD	---	

Analog Ammeters

PRODUCT CODE (Meters without dial plates)	CERTIFICATION	
SCL-AM-I-2-X/5A	---	SCL- AM - I - 2 - X / 5A - 6S 6 times suppress Secondary current (30A to 4000A) (Size) 2 : 72 x 72mm, 3 : 96 x 96mm (Series) Ammeter (Category) Analog meter Scale plate
SCL-AM-I-3-X/5A	---	
SCL-AM-I-2-X/5A-6S	---	
SCL-AM-I-3-X/5A-6S	---	
SCL-AM-I-3-X/5A-6S	---	

Analog Direct Type Ammeters

PRODUCT CODE	CERTIFICATION	
AM-I-D-2-X-CE-RoHS	CE	AM - I - D - 2 - X Display scale X: 10A to 100A (Size) 2: 72x72mm, 3: 96 x 96mm Direct type (Series) Ammeter (Category) Analog meter
AM-I-D-3-X-CE-RoHS	CE	
AM-I-D-2-X	---	
AM-I-D-3-X	---	

Analog Power Factor Meters

PRODUCT CODE	CERTIFICATION
AM-PF-3-3PIE-0.5CAP-1-0.5IND-X-5A-CE-RoHS	CE
AM-PF-2-3PIE-0.5CAP-1-0.5IND-X-5A-CE-RoHS	CE
AM-PF-3-3PIE-0.5CAP-1-0.5IND-X-5A	---
AM-PF-2-3PIE-0.5CAP-1-0.5IND-X-5A	---

AM - PF - 3 - 3PIE - 0.5CAP-1-0.5IND - X - 5A	
Operating current	
Operating voltage: 415, 440V	
Measuring range	
Three phase single element	
(Size) 2: 72 x 72mm, 3: 96 x 96mm	
(Series) Power factor	
(Product name) Analog meter	

Analog Frequency Meters

PRODUCT CODE	CERTIFICATION
AM-Hz-3-A-B-CE-RoHS	CE
AM-Hz-2-A-B-CE-RoHS	CE
AM-Hz-3-A-B	---
AM-Hz-2-A-B	---

AM - Hz - 3 - A - B	
(Voltage range) B: 220V, 440V	
(Frequency range) A: 45 - 65Hz	
(Size) 2 : 72 x 72mm, 3: 96 x 96mm	
(Series) Frequency	
(Product name) Analog meter	

RCT

PRODUCT CODE	WIRE APERTURE In mm	CURRENT RATIO	BURDEN IN VA	ACCURACY CLASS	NO. OF PRIMARY TURNS
RCT-T-D30-30/5 A VA 1.5 CL5	DIA 30	30/5	1.5	5	---
RCT-T-D30-30/5 A VA 5 (2T) CL5	DIA 30	30/5	5	5	2
RCT-T-D30-50/5 A VA 5 CL5	DIA 30	50/5	5	5	---
RCT-T-D30-75/5 A VA 5 CL5	DIA 30	75/5	5	5	---
RCT-T-D30-100/5 A VA 5 CL1	DIA 30	100/5	5	1	---
RCT-T-D30-150/5 A VA 5 CL1	DIA 30	150/5	5	1	---
RCT-T-D50-200/5 A VA 5 CL1	DIA 50	200/5	5	1	---
RCT-T-D50-250/5 A VA 5 CL1	DIA 50	250/5	5	1	---
RCT-T-D50-300/5 A VA 5 CL1	DIA 50	300/5	5	1	---
RCT-T-D50-400/5 A VA 5 CL1	DIA 50	400/5	5	1	---
RCT-T-D50-500/5 A VA 5 CL1	DIA 50	500/5	5	1	---
RCT-T-D50-600/5 A VA 5 CL1	DIA 50	600/5	5	1	---
RCT-W-D30-30/5 A VA 1.5 CL5	DIA 30	30/5	1.5	5	---
RCT-W-D30-30/5 A VA 5 (2T) CL5	DIA 30	30/5	5	5	2
RCT-W-D30-50/5 A VA 5 CL5	DIA 30	50/5	5	5	---
RCT-W-D30-75/5 A VA 5 CL5	DIA 30	75/5	5	5	---
RCT-W-D30-100/5 A VA 5 CL1	DIA 30	100/5	5	1	---
RCT-W-D30-150/5 A VA 5 CL1	DIA 30	150/5	5	1	---
RCT-W-D50-200/5 A VA 5 CL1	DIA 50	200/5	5	1	---
RCT-W-D50-250/5 A VA 5 CL1	DIA 50	250/5	5	1	---
RCT-W-D50-300/5 A VA 5 CL1	DIA 50	300/5	5	1	---
RCT-W-D50-400/5 A VA 5 CL1	DIA 50	400/5	5	1	---
RCT-W-D50-500/5 A VA 5 CL1	DIA 50	500/5	5	1	---
RCT-W-D50-600/5 A VA 5 CL1	DIA 50	600/5	5	1	---

TWCT

PRODUCT CODE	WIRE APERTURE In mm	CURRENT RATIO	BURDEN IN VA	ACCURACY CLASS
TWCT-T-D35 30/5 A VA 1.5 CL 5	DIA 35	30/5	1.5	5
TWCT-T-D35 50/5 A VA 5 CL 5	DIA 35	50/5	5	5
TWCT-T-D35 75/5 A VA 5 CL 5	DIA 35	75/5	5	5
TWCT-T-D35 100/5 A VA 5 CL 1	DIA 35	100/5	5	1
TWCT-T-D35 150/5 A VA 5 CL 1	DIA 35	150/5	5	1
TWCT-T-D55 150/5 A VA 5 CL 1	DIA 55	150/5	5	1
TWCT-T-D55 200/5 A VA 5 CL 1	DIA 55	200/5	5	1
TWCT-T-D55 250/5 A VA 5 CL 1	DIA55	250/5	5	1
TWCT-T-D55 300/5 A VA 5 CL 1	DIA 55	300/5	5	1
TWCT-T-D55 400/5 A VA 5 CL 1	DIA 55	400/5	5	1
TWCT-T-D65 500/5 A VA 5 CL 1	DIA 65	500/5	5	1
TWCT-T-D65 600/5 A VA 5 CL 1	DIA 65	600/5	5	1
TWCT-T-D110 800/5 A VA 10 CL 0.5	DIA 110	800/5	10	0.5
TWCT-T-D110 1000/5 A VA 10 CL 0.5	DIA 110	1000/5	10	0.5
TWCT-T-D120 1000/5 A VA 10 CL 0.5	DIA 120	1000/5	10	0.5
TWCT-T-D120 1200/5 A VA 10 CL 0.5	DIA 120	1200/5	10	0.5
TWCT-T-D120 1600/5 A VA 10 CL 0.5	DIA 120	1600/5	10	0.5

SPCT

PRODUCT CODE	WIRE APERTURE In mm	CURRENT RATIO	BURDEN IN VA	ACCURACY CLASS	CERTIFICATION
SPCT 50/30 60/5 A VA 1 CL 5	30x10	60 / 5	1	5	CE 
SPCT 50/30 75/5 A VA 1 CL 1	30x10	75 / 5	1	1	CE 
SPCT 50/30 80/5 A VA 1 CL 1	30x10	80 / 5	1	1	CE 
SPCT 50/30 100/5 A VA 1 CL 1	30x10	100 / 5	1	1	CE 
SPCT 50/30 125/5 A VA 1.25 CL 1	30x10	125 / 5	1.25	1	CE 
SPCT 50/30 160/5 A VA 1.5 CL 1	30x10	160 / 5	1.5	1	CE 
SPCT 50/30 200/5 A VA 3 CL 1	30x10	200 / 5	3	1	CE 
SPCT 50/30 250/5 A VA 3 CL 1	30x10	250 / 5	3	1	CE 
SPCT 50/30 400/5 A VA 5 CL 1	30x10	400 / 5	5	1	CE 
SPCT 62/22 30/5 A VA 1 CL 5	DIA 22	30/5	1	5	CE 
SPCT 62/30 50/5 A VA 1 CL 3	30x10	50/5	1	3	CE 
SPCT 62/30 50/5 A VA 1.5 CL 3	30x10	50/5	1.5	3	CE 
SPCT 62/30 75/5 A VA 1 CL 3	30x10	75/5	1	3	CE 
SPCT 62/30 75/5 A VA 3 CL 3	30x10	75/5	3	3	CE 
SPCT 62/30 100/5 A VA 1 CL 1	30x10	100/5	1	1	CE 
SPCT 62/30 100/5 A VA 3 CL 1	30x10	100/5	3	1	CE 
SPCT 62/40 100/5 A VA 1 CL 1	40x10	100/5	1	1	CE 
SPCT 62/40 125/5 A VA 1 CL 1	40x10	125/5	1	1	CE 
SPCT 62/40 150/5 A VA 1.5 CL 1	40x10	150/5	1.5	1	CE 
SPCT 62/40 150/5 A VA 3 CL 1	40x10	150/5	3	1	CE 
SPCT 62/40 160/5 A VA 1.5 CL 1	40x10	160/5	1.5	1	CE 
SPCT 62/40 200/5 A VA 2.5 CL 0.5	40x10	200/5	2.5	0.5	CE 
SPCT 62/40 200/5 A VA 3 CL 1	40x10	200/5	3	1	CE 
SPCT 62/40 250/5 A VA 2.5 CL 0.5	40x10	250/5	2.5	0.5	CE 
SPCT 62/40 250/5 A VA 3 CL 1	40x10	250/5	3	1	CE 
SPCT 62/40 300/5 A VA 3 CL 0.5	40x10	300/5	3	0.5	CE 
SPCT 62/40 400/5 A VA 3.75 CL 0.5	40x10	400/5	3.75	0.5	CE 
SPCT 62/40 400/5 A VA 5 CL 1	40x10	400/5	5	1	CE 
SPCT 100/60 500/5 A VA 5 CL 1	60x12	500/5	5	1	CE 
SPCT 100/60 600/5 A VA 5 CL 0.5	60x12	600/5	5	0.5	CE 
SPCT 100/60 600/5 A VA 7.5 CL 1	60x12	600/5	7.5	1	CE 
SPCT 100/60 800/5 A VA 10 CL 0.5	60x12	800/5	10	0.5	CE 
SPCT 100/60 1000/5 A VA 15 CL 0.5	60x12	1000/5	15	0.5	CE 
SPCT 100/60 1200/5 A VA 15 CL 0.5	60x12	1200/5	15	0.5	CE 
SPCT 140/100 800/5 A VA 15 CL 0.5	100x30	800/5	15	0.5	CE 
SPCT 140/100 1000/5 A VA 15 CL 0.5	100x30	1000/5	15	0.5	CE 
SPCT 140/100 1200/5 A VA 15 CL 0.5	100x30	1200/5	15	0.5	CE 
SPCT 140/100 1250/5 A VA 15 CL 0.5	100x30	1250/5	15	0.5	CE 
SPCT 140/100 1500/5 A VA 15 CL 0.5	100x30	1500/5	15	0.5	CE 
SPCT 140/100 1600/5 A VA 15 CL 0.5	100x30	1600/5	15	0.5	CE 
SPCT 140/100 2000/5 A VA 15 CL 0.5	100x30	2000/5	15	0.5	CE 
SPCT 140/100 2500/5 A VA 15 CL 0.5	100x30	2500/5	15	0.5	CE 
SPCT 140/100 3000/5 A VA 15 CL 0.5	100x30	3000/5	15	0.5	CE 
SPCT 140/100 3500/5 A VA 15 CL 0.5	100x30	3500/5	15	0.5	CE 
SPCT 140/100 4000/5 A VA 15 CL 0.5	100x30	4000/5	15	0.5	CE 

SCCT

PRODUCT CODE	APERTURE In mm	CURRENT RATIO	BURDEN IN VA	ACCURACY CLASS	CERTIFICATION
SCCT 30/20 100/5A VA 1 CL 1	20x30	100/5A	1	1	CE 
SCCT 30/20 100/5A VA 1.5 CL 3	20x30	100/5A	1.5	3	CE 
SCCT 30/20 150/5A VA 1 CL 0.5	20x30	150/5A	1	0.5	CE 
SCCT 30/20 150/5A VA 1.5 CL 3	20x30	150/5A	1.5	3	CE 
SCCT 30/20 200/5A VA 1 CL 0.5	20x30	200/5A	1	0.5	CE 
SCCT 30/20 200/5A VA 1.5 CL 1	20x30	200/5A	1.5	1	CE 
SCCT 30/20 250/5A VA 1.5 CL 0.5	20x30	250/5A	1.5	0.5	CE 
SCCT 30/20 300/5A VA 2.5 CL 0.5	20x30	300/5A	2.5	0.5	CE 
SCCT 30/20 400/5A VA 2.5 CL 0.5	20x30	400/5A	2.5	0.5	CE 
SCCT 80/50 250/5A VA 1.5 CL 1	50x80	250/5A	1.5	1	CE 
SCCT 80/50 300/5A VA 1.5 CL 1	50x80	300/5A	1.5	1	CE 
SCCT 80/50 400/5A VA 1.5 CL 0.5	50x80	400/5A	1.5	0.5	CE 
SCCT 80/50 500/5A VA 2.5 CL 0.5	50x80	500/5A	2.5	0.5	CE 
SCCT 80/50 600/5A VA 2.5 CL 0.5	50x80	600/5A	2.5	0.5	CE 
SCCT 80/50 750/5A VA 2.5 CL 0.5	50x80	750/5A	2.5	0.5	CE 
SCCT 80/50 800/5A VA 2.5 CL 0.5	50x80	800/5A	2.5	0.5	CE 
SCCT 80/50 1000/5A VA 5 CL 0.5	50x80	1000/5A	5	0.5	CE 
SCCT 120/80 500/5A VA 2.5 CL 0.5	80x120	500/5A	2.5	0.5	CE 
SCCT 120/80 600/5A VA 2.5 CL 0.5	80x120	600/5A	2.5	0.5	CE 
SCCT 120/80 750/5A VA 2.5 CL 0.5	80x120	750/5A	2.5	0.5	CE 
SCCT 120/80 800/5A VA 2.5 CL 0.5	80x120	800/5A	2.5	0.5	CE 
SCCT 120/80 1000/5A VA 5 CL 0.5	80x120	1000/5A	5	0.5	CE 
SCCT 120/80 1200/5A VA 7.5 CL 0.5	80x120	1200/5A	7.5	0.5	CE 
SCCT 120/80 1250/5A VA 7.5 CL 0.5	80x120	1250/5A	7.5	0.5	CE 
SCCT 120/80 1500/5A VA 7.5 CL 0.5	80x120	1500/5A	7.5	0.5	CE 
SCCT 120/80 1500/5A VA 10 CL 1	80x120	1500/5A	10	1	CE 
SCCT 120/80 1600/5A VA 10 CL 0.5	80x120	1600/5A	10	0.5	CE 
SCCT 160/80 1000/5A VA 10 CL 0.5	80x160	1000/5A	10	0.5	CE 
SCCT 160/80 1200/5A VA 10 CL 0.5	80x160	1200/5A	10	0.5	CE 
SCCT 160/80 1250/5A VA 10 CL 0.5	80x160	1200/5A	10	0.5	CE 
SCCT 160/80 1500/5A VA 15 CL 0.5	80x160	1500/5A	15	0.5	CE 
SCCT 160/80 2000/5A VA 15 CL 0.5	80x160	2000/5A	15	0.5	CE 
SCCT 160/80 2500/5A VA 15 CL 0.5	80x160	2500/5A	15	0.5	CE 
SCCT 160/80 3000/5A VA 15 CL 0.5	80x160	3000/5A	15	0.5	CE 
SCCT 160/80 4000/5A VA 15 CL 0.5	80x160	4000/5A	15	0.5	CE 
SCCT 160/80 5000/5A VA 15 CL 0.5	80x160	5000/5A	15	0.5	CE 
SCCT 160/80 6000/5A VA 15 CL 0.5	80x160	6000/5A	15	0.5	CE 



640PSRV-CE
90(H) x 17.5(W) x 60(D)mm



640PSR-CE
90(H) x 17.5(W) x 60(D)mm



600PSR
90(H) x 17.5(W) x 60(D)mm



800PSR
76.85(H) x 22.5(W) x 105.5(D)mm

FEATURES

- LED Indication : Healthy and Trip conditions
- Monitors Phase Failure, Sequence
- Selectable Asymmetry
- SPP / PSR selectable
- Variable trip time delay : 2 to 10 sec
- Under/ Over voltage - ON / OFF selectable

- LED Indication : Healthy and Trip conditions
- Monitors Phase Failure, Sequence, Asymmetry, Under Voltage and Over Voltage

- Monitor Phase Failure, Sequence & Asymmetry
- LED indication : Relay ON
- Slim space saving design

- Monitor Phase Failure, Sequence & Asymmetry
- LED indication : Relay ON

MODES

Phase failure : Yes,
Phase sequence : Yes,
Phase asymmetry : 40V / 65V selectable,
Reset : Auto reset on removal of fault condition,
Under voltage : 310V fixed,
Over voltage : 500V fixed

Phase failure : Yes,
Phase sequence : Yes,
Phase asymmetry : 40V fixed,
Reset : Auto reset on removal of fault condition

Phase failure : Yes,
Phase sequence : Yes,
Phase asymmetry : 30V fixed ,
Reset : Auto reset on removal of fault condition

TIME RANGES

Power ON delay : <400msec

Power ON delay : 200msec

ACCURACY

±5% of F.S.

±3% of F.S.

OUTPUT CONTACT

1 C/O (SPDT)

OUTPUT RATING

NC : 3A@250V AC / 30V DC , NO : 5A@250V AC / 30V DC

ELECTRICAL CONNECTION

3Ø - 3W

OPERATING VOLTAGE

154 to 520V AC (L - L)

154 to 500V AC (L - L)



642PSR
90(H) x 17.5(W) x 60(D)mm



SPPA2M2
90(H) x 35(W) x 60(D)mm



600SPP
90(H) x 17.5(W) x 60(D)mm

FEATURES

- Monitor Phase Failure, Sequence & Asymmetry
- LED indication : Power ON & Trip
- DIN rail & Wall mount

- Monitor Phase Failure, Asymmetry, Over voltage & Under voltage
- LED indication : Power ON & Trip

- Monitor Phase Failure & Asymmetry
- LED indication : Relay ON
- Slim space saving design

MODES

Phase failure : Yes, Phase sequence : Yes,
Phase asymmetry : 30V fixed,
Reset : Auto reset on removal of fault condition

Phase failure : Yes,
Phase sequence : Yes,
Phase asymmetry : 30V fixed,
Reset : Auto reset on removal of fault condition

TIME RANGES

Power ON delay : <500msec

Power ON delay : 3sec

ACCURACY

±1% of F.S.

OUTPUT CONTACT

1 C/O (SPDT)

2 C/O (DPDT)

1 C/O (SPDT)

OUTPUT RATING

NC : 3A@250V AC / 30V DC , NO : 5A@250V AC / 30V DC

ELECTRICAL CONNECTION

3Ø - 3W

OPERATING VOLTAGE

280 to 520V AC (L - L)

154 to 500V AC (L - L)



Auto switch-195/400V
76(H) x 20.5(W) x 85(D)mm



Auto switch-313/457V
76(H) x 20.5(W) x 85(D)mm

FEATURES	- Phase Failure, Sequence, Asymmetry ; Under Voltage, Over Voltage - Modes : Auto, Manual, Bypass - Pre-wired terminals	
MODES	Phase failure : Yes, Phase sequence : Yes, Under voltage (UV) : Healthy to trip $\leq 195V$, Trip to healthy $\geq 205V$ Over voltage (OV) : Healthy to trip $\geq 400V$, Trip to healthy $\leq 390V$	Phase failure : Yes, Phase sequence : Yes, Under voltage (UV) : Healthy to trip $\leq 313V$, Trip to healthy $\geq 323V$ Over voltage (OV) : Healthy to trip $\geq 457V$, Trip to healthy $\leq 447V$
MEASUREMENTS	Phase Failure, Sequence, Asymmetry, Under voltage, Over voltage	
OPERATING VOLTAGE RANGE	195V AC - 400V AC (L - L) 50 - 60Hz	313V AC - 457V AC (L - L) 50 - 60Hz
TIME SETTING	Over voltage , Under voltage & Voltage unbalance : 3.5sec ± 1.5 sec Phase loss : Instantaneous (<400msec), Phase sequence Power ON delay (min) , Recovery time (min) : 0-10min Knob setting : (0, 0.5, 1, 3, 5 & 10)	
OUTPUT RATING	1 NO relay	
RELAY RATING	Contacts @ AC 15, 250V AC : 2A , Contacts @ AC 12, 250V AC : 5A	
RELAY MODE	Fail safe mode only	
ACCURACY	Timing accuracy $\pm 5\%$ of reading, Voltage accuracy $\pm 1\%$ of full scale (as per rated voltage)	

Earth Fault Relay



900EFR-BL-U
90(H) x 35(W) x 70.5(D)mm

Thermistor Protection Relay



TPRA2M1-1-U-CE
90(H) x 35(W) x 60(D)mm

FEATURES	- Earth fault current monitoring - Two alarm relays with NO and NC operation selectable - Test and reset via Front / Remote	FEATURES	- PTC input - LED indication : Power ON, Trip, Open, Short - DPDT relay output
MEASUREMENT	Earth fault monitoring	LED INDICATION	Green : Power ON indication, Yellow : Sensor Indication, Red : Relay status
DISPLAY	3 digit liquid crystal display with backlight	INPUT TYPE	PTC sensor
ELECTRICAL CONNECTION	1Ø - 2W, 3Ø - 3W, 3Ø - 4W	SENSOR	Sensor short : $< 40 (\pm 1\Omega)$, Sensor healthy : $44\Omega (\pm 3\Omega)$ to $< 3.8K\Omega (\pm 150\Omega)$ Sensor trip : $\geq 3.8K\Omega (\pm 150\Omega)$ to $< 5.5K\Omega (\pm 150\Omega)$ Sensor open : $\geq 5.5K\Omega (\pm 150\Omega)$ & above, Sensor cut-in : $\leq 1.5K\Omega (\pm 60\Omega)$
FRAME RATING (CT PRIMARY)	160A, 250A, 630A	FUNCTIONAL	Relay operating mode : Fail-safe & Shunt-trip mode, Reset : Auto / Manual
TRIP SETTING	10% to 80% of selectable MCCB frame rating	OUTPUT CONTACT	2 C/O (DPDT)
TIME RANGES	Response time : $< 100ms$, Trip time delay : 0 to 99.9sec, Recovery time : 0 to 99.9sec, Power ON delay : 0.5 to 99.9sec	OUTPUT RATING	8A@250V AC
OUTPUT CONTACT & RATING	2 x 1 C/O (SPDT) NC : 3A@250V AC / 30V DC, NO : 5A@250V AC / 30V DC		

Earth Fault Current Transformer



Description	Common Accessory for Earth Fault Relay
Current ratio	160/1A, 250/1A, 630/1A
Rated burden	1 VA
Sizes (mm)	100 x 25, 140 x 35, 180 x 35, 220 x 50



600VPR-310/520V
90(H) x 17.5(W) x 60(D)mm



600VPR-170/290V
90(H) x 17.5(W) x 60(D)mm



800VPR-3
76.85(H) x 22.5(W) x 105.5(D)mm

FEATURES	- Monitors Under & Over Voltage - Monitors Phase Failure & Sequence - LED indication : Power ON, Fault condition - Space saving design		
MODES	Phase failure : Yes Phase sequence : Yes Under voltage : 310 to 405V AC Over voltage : 425 to 520V AC Reset : Auto reset on removal of fault condition	Phase failure : Yes Phase sequence : Yes Under voltage : 170 to 224V AC Over voltage : 236 to 290V AC Reset : Auto reset on removal of fault condition	Phase failure : Yes Phase sequence : Yes Under voltage : 310 to 405V AC Over voltage : 425 to 520V AC Reset : Auto reset on removal of fault condition
TIME RANGES	Trip time delay : 0.2 to 10s, Power On delay : 400msec		Trip Delay : 0 to 10s (For under voltage and over voltage) : Instantaneous (For phase failure & phase sequence)
ACCURACY	Trip Voltage : $\pm 0.5\%$ of F.S, Trip Time : $\pm 5\%$ of F.S		
OUTPUT CONTACT	1 C/O (SPDT)		
OUTPUT RATING	NC : 3A@250V AC / 30V DC, NO : 5A@250V AC / 30V DC		
ELECTRICAL CONNECTION	3Ø - 3W		
OPERATING VOLTAGE	310 to 520V AC (L - L)	170 to 290V AC (L - L)	310 to 520V AC (L - L)



900VPR-2-280/520V
90(H) x 35(W) x 70.5(D)mm

900VPR-2-280/600V-CE
90(H) x 35(W) x 70.5(D)mm



900VPR-BL-U
90(H) x 35(W) x 70.5(D)mm

FEATURES	- Monitors Phase Failure, Sequence, Asymmetry, Under voltage, Over voltage, Under frequency and Over frequency - Two separate alarm relays - LED indication : Power ON, Fault condition		- Monitors Phase Failure, Sequence, Asymmetry, Under voltage, Over voltage, Under frequency, Over frequency and Neutral loss - Two alarm relays with NO or NC operation selectable - LED indication : Fault condition
MEASUREMENTS	Phase Failure, Sequence, Asymmetry, Under / Over voltage, Under / Over frequency, (Neutral Loss not applicable for 900VPR-2-280/520V)		
DISPLAY	3 digit LCD		3 digit LCD with backlight
ALARM INDICATIONS	Trip		
ELECTRICAL CONNECTION	1Ø - 2W (Only applicable for 900VPR-2-280/600V-CE), 3Ø - 3W, 3Ø - 4W		
TRIP SETTING	Under / Over voltage : 280 to 520V AC L - L (for 3Ø-3W), 160 to 300V AC L - N (for 3Ø - 4W), Under / Over frequency : 45 / 65Hz, Voltage asymmetry : 5.0 to 99.9%	Under / Over voltage : 280 to 600V AC L-L (for 3Ø-3W), 160 to 300V AC L-N (for 3Ø-4W), Under / Over frequency : 45 / 65Hz, Voltage asymmetry : 5.0 to 99.9%	Under / Over voltage : 85 to 500V AC L - L (for 3Ø - 3W), 50 to 288V AC L - N (for 3Ø - 4W), Under / Over frequency : 45 / 65Hz, Phase asymmetry : 5.0 to 30.0%
TRIP TIME SETTING	Power ON delay : 0.5 to 99.9sec, Trip time delay : 0 to 99.9sec Recovery time delay : 0 to 99.9sec, Response time : <200ms	Power ON delay : 0.5 to 999sec, Trip time delay : 0 to 999sec Recovery time delay : 0 to 999sec, Response time : <200ms	Power ON delay : 0.5 to 300sec, Trip time delay : 0 to 300sec Recovery time delay : 0 to 300sec (In Auto Reset Mode), Response time : <120ms
HYSTERESIS	Voltage : 1.0 to 99.9V, Frequency : 0.2 to 2Hz, Asymmetry : 2 to 20%		Voltage : 1.0 to 40V, Frequency : 0.2 to 2Hz, Asymmetry : 2 to 20%
RESOLUTION	Voltage : 1V, Frequency : 0.1Hz		
ACCURACY	Voltage : $\pm 1\%$ of set value, Frequency : $\pm 0.3\%$, Time (Recovery time, Trip delay, Power on delay) : $\pm 5\%$ of setting ± 200 ms		Voltage : $\pm 1\%$ of set value ± 2 digits, Frequency : $\pm 0.5\%$ ± 1 digits, Time (Recovery Time, Trip delay, Power on delay) : $\pm 5\%$ of setting ± 120 ms
OUTPUT CONTACT	2 x 1 C/O (SPDT)		
OUTPUT RATING	NO : 5A@240V AC / 30V DC, NC : 3A@240V AC / 30V DC		NO : 5A@250V AC / 30V DC, NC : 3A@250V AC / 30V DC
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	Self powered, Operating voltage : 280 to 520V AC (L-L), 160 to 300V AC (L-N)	Self powered, Operating voltage : 280 to 600V AC (L-L), 160 to 300V AC (L-N)	85 to 270V AC / DC



VPRA2M
90(H) x 35(W) x 70.5(D)mm



VPRD2M
90(H) x 35(W) x 70.5(D)mm

FEATURES	- Monitors Under Voltage, Over Voltage - Monitors Phase Failure, Sequence & Asymmetry - Adjustable over and under voltage trip level - Adjustable trip time delay	- Monitors Under Voltage, Over Voltage - Monitors Phase Failure, Sequence & Asymmetry - Adjustable switching hysteresis - One relay with two change over alarm relay operation
MEASUREMENT	Phase Failure, Sequence, Asymmetry, Under voltage, Over voltage	
DISPLAY	Separate LED indications for Power ON, Phase failure, Phase sequence, Phase asymmetry, Under voltage, Over voltage,	3 digits LCD
ELECTRICAL CONNECTION	1Ø - 2W, 3Ø - 4W	
TRIP SETTING	Under voltage : 55 to 95% of Un [127 to 219V AC (L - N)] Over voltage : 105 to 125% of Un [242 to 288V AC (L - N)], Phase asymmetry : >10%	Under voltage : 127 to 219V AC (L - N) Over voltage : 242 to 288V AC (L - N), Phase asymmetry : 5 - 30 %
TRIP TIME SETTING	Power ON delay : 0 to 15sec, Trip time delay : 0 to 15sec Recovery time delay : 5sec ± 200ms, Phase sequence trip delay <250msec	Power ON delay : 0.5 to 300sec, Trip time delay : 0 to 300sec Recovery time delay : 0 to 300sec, Phase sequence trip delay <150msec
HYSTERESIS	Voltage : 7V (±2V) of trip voltage	Voltage : 1.0V - 99.9V, Asymmetry : 2 to 20%
ACCURACY	Trip setting : ±5% of F. S., Time setting : ±10% of F. S.	Voltage : ±1% ±2 digits, Time setting : ±5% of settings ± 150ms
OUTPUT CONTACT	2 C/O (DPDT)	
OUTPUT RATING	NC : 5A@250V AC / 30V DC, NO : 5A@250V AC / 30V DC	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	Self powered, Nominal input voltage (Un) : 230V AC (L - N), Operating voltage : 127 to 288V AC (L - N)	

Current Monitoring Relays



900CPR-1-BL-U
90(H) x 35(W) x 70.5(D)mm



900CPR-3-1-BL
90(H) x 35(W) x 70.5(D)mm



900CPR-1
90(H) x 35(W) x 70.5(D)mm



900CPR-3
90(H) x 35(W) x 70.5(D)mm

FEATURES	• Monitors Under, Over Current protection for 1Ø system • True RMS measurement • Two alarm relay with NC or NO operation selectable • LED indication : Fault condition	• Monitors Under, Over Current & Current Asymmetry protection for 1Ø & 3Ø system • True RMS measurement • One alarm relay with NC or NO operation selectable • LED indication : Fault condition	• Monitors Under, Over Current protection for 1Ø system • True RMS measurement • One alarm relay with NC or NO operation • LED indication : Fault condition	• Monitors Under, Over Current & Current Asymmetry protection for 1Ø & 3Ø system • True RMS measurement • One alarm relay with NC or NO operation • LED indication : Fault condition
MEASUREMENTS	Under current, Over current (Current asymmetry applicable only for 900CPR-3, 900CPR-3-1-BL)			
DISPLAY	3 digit LCD with backlight		3 digits LCD	
ELECTRICAL CONNECTION	1Ø - 2W	1Ø - 2W, 3Ø - 3W, 3Ø - 4W	1Ø - 2W	1Ø - 2W, 3Ø - 3W, 3Ø - 4W
CT SETTING	CT Primary : 1A / 5A - 999A, CT Secondary : 1A / 5A (Selectable)			
TRIP SETTING	Under current : 0-999A, Over current : 0.5 - 1.19kA, (Current asymmetry : 5.0 – 99.9% applicable only for 900CPR-3, 900CPR-3-1-BL)			
TRIP TIME SETTING	Power ON delay : 0.5 – 99.9sec, Trip time delay : 0 - 99.9sec, Recovery time delay : 0 - 99.9sec, Response time : < 200ms			
HYSTERESIS	Current : 0.1 to 99.9A			
ACCURACY	Current : ±1% of setting ± 2 digits, Time (Recovery time, Trip delay, Power ON delay) : ±5% of setting ±200ms			
OUTPUT CONTACT	2 x 1 C/O (SPDT)	1C/O SPDT		
OUTPUT RATING	NO : 5A @ 250V AC / 30V DC; NC : 3A @ 250V AC / 30V DC			
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	85 to 270V AC / DC	230V AC (±15%)		



600ELR
90(H) x 17.5(W) x 60(D)mm



ELRA2M
90(H) x 35(W) x 60(D)mm



900ELR-2
90(H) x 35(W) x 70.5(D)mm

FEATURES	- Monitors true RMS earth leakage current (Up to 500mA) in 1Ø & 3Ø system - Leakage current (In) & Time delay (ΔT) adjustable - LED indication for power ON and relay status - Test and reset function via front key	- Monitor true RMS earth leakage current up to 30A in 1Ø & 3Ø system - CBCT connection monitoring - Test and reset via Front / Remote - Sensitivity and time delay adjustable	- Monitor true RMS earth leakage current up to 30A in 1Ø & 3Ø system - CBCT connection monitoring - Test and reset via Front / Remote - Two separate alarms relays with NO or NC operation selectable
MEASUREMENT	Earth leakage current (Via external CBCT)		
DISPLAY	2 LED Indications (Power On and Relay Status)	5 LED indication	3 digit LCD with backlight, 2 LED for trip indication
ELECTRICAL CONNECTION	1Ø - 2W, 3Ø - 3W, 3Ø - 4W		
TRIP SETTING	30mA, 100mA, 300mA, 500mA	30mA to 30A	
TIME RANGES	Variable time settings (0, 2, 4, 6, 8, 10 sec) for 100mA, 300mA & 500mA current setting (For 1x1n) and <30ms for 5xIn.	Trip time delay : 0 to 9 sec (NA when In=0.03A)	Power ON delay : 0.5 to 99.9 sec, Trip time delay : 0 to 99.9 sec, Delay On release : 0 to 99.9 sec
ACCURACY	Current : 5% of In , Time : 5% of Set time	Current : ± 5% of Set Trip current Time : ± 5% of set Time + Response time	Current : ±5% of setting, Time (Recovery time, Trip delay, Power on delay) : ±5% of setting ±200ms
OUTPUT CONTACT	1 SPDT relay		2 x 1 C/O (SPDT)
OUTPUT RATING	NO : 5A @ 250VAC / 24V DC , NC: 3A @ 250VAC / 24V DC		NO : 10A@277V AC / 28V DC NC : 3A@250V AC / 24V DC, NO : 5A@250V AC / 24V DC
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	230V AC (± 15%)		



ELR-341
96(H) x 96(W) x 50(D)mm



ELCTR35
105(H) x 74(W) x 27(D)mm

FEATURES	• Monitor true RMS earth leakage current up to 30A in 1Ø & 3Ø system • CBCT connection monitoring • Test and reset via Front / Remote • Pre-alarm indication selectable	• Monitors True RMS earth leakage current in 1Ø & 3Ø system • Inbuilt CBCT • Test and reset function
MEASUREMENT	Earth leakage current (Via external CBCT)	Earth leakage current (Internal CBCT)
DISPLAY	3 digits, 7 segments LED display	2 LED indication
ELECTRICAL CONNECTION	1Ø - 2W, 3Ø - 3W, 3Ø - 4W	
TRIP SETTING	30mA to 30A	75% of 30mA or 300mA
TIME RANGES	Power ON delay : 1 to 999 sec, Trip time delay : 0 to 9999 sec, Recovery time : 1 to 99 min	Reset time : Instantaneous
ACCURACY	Current : ± 5% of Set Trip current Time : ± 5% of set Time + Response time	Current : ± 5% of Input current Time : ± 5% of Response time
OUTPUT CONTACT	1 C/O SPDT	
OUTPUT RATING	NC : 3A@250V AC / 28V DC, NO : 5A@250V AC / 28V DC	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC	230V AC (± 15%)



Core Balance Current Transformers

Description	Common Accessory for ELR
Operating current range	30mA - 30A
Sizes (inner diameter)	35mm, 70mm, 120mm, 210mm, 310mm



MPR-3M
90(H) x 52.5(W) x 73(D)mm



MPR-341-2
96(H) x 96(W) x 50(D)mm

FEATURES	- Single phasing, Phase Sequence & Asymmetry - Under Current, Overload trip Current - Test and reset function via Front / Remote	- Monitors Overload (As per NEMA class curve), Over, Under current, Current asymmetry, Lock current, Earth fault, Phase Failure, Sequence - LED indication : Power ON, Trip relay - Test & reset function via Front / Remote
DISPLAY	3 LED indication	7 segment, 4 digits LED
AUXILLARY SUPPLY	230 / 415V AC $\pm 15\%$	90V to 270V AC / DC
ELECTRICAL CONNECTION	3 ϕ - 3W	
TRIP SETTING	Phase asymmetry : 50% of motor current (Fixed) T(sec) setting : To select 2, 4, 6, 8, 10 sec trip time curve in overload trip curve graph. Under current : 50% of Motor current, X Imax : To select motor current rating	Over load : Class 5,10,15,20,30, Over current : 4A to 480A, Under Current : 1A to 79A, Current asymmetry : 1A to 79A, Lock current : 4A to 480A, Earth fault : 1A to 160A
TIME SETTINGS	Single phase trip : 5 sec, Phase sequence : 5 sec, Phase asymmetry : 5 sec Over load trip : As per (IDMT Curve), Under current trip : 5 Sec	Power On delay : 1-999 sec, Trip time : 0-999 sec, Recovery time : 1-999 sec, Response time : <120ms, 3 Reset attempt time : 0-999 min
MODE	Auto / Manual / Remote	
ACCURACY	Time : $\pm 5\%$ of setting ± 100 ms, Current : $\pm 5\%$ of set value	Current : $\pm 5\%$ of Ir ± 1 digit, Timing : $\pm 5\%$ + 100msec
OUTPUT CONTACT	2 C/O (DPDT)	2 x1 C/O (SPDT)
OUTPUT RATING	NC : 5A@ 240V AC / 28V DC, NO : 5A@240V AC / 28V DC	

3 ϕ - Pump Protection Relays



PPRD-4M-3-415V
90(H) x 70(W) x 60(D)mm



PPRA-4M-3-415V
90(H) x 70(W) x 60(D)mm

FEATURES	- Monitors Overload (As per NEMA class curve), Over, Under current, Current asymmetry, Lock current - Phase Failure, Sequence, Asymmetry, Over voltage and Under voltage - LED indication : Power ON, Trip relay - Test & reset function via Front / Remote	
DISPLAY	7 segment, 3 digits LED	4 LED & 4 knob for variable setting
AUXILLARY SUPPLY	280V-500V (L-L)	
ELECTRICAL CONNECTION	3 ϕ - 3W	
CT SETTING	10A, 40A, 80A	
TRIP SETTING	Over load : NEMA class curve 5,10,15,20,30, Over current : 4A to 480A, Under current : 1A to 79A, Current asymmetry : 1A to 79A, Lock current : 4A to 480A, Over voltage : 280V-500V, Under voltage : 280V-500V, Voltage asymmetry : 5V TO 50V	Over load : NEMA class curve 5,10,15,20,30, Over current : 10%-70% of Ir (Rated current) Under current : 20%-80% of Ir (Rated current), Current asymmetry : Fixed: 50% of Ir (Rated current) Lock current : Fixed 300% of Ir (Rated current), Over voltage : Fixed (480V), Under voltage : Fixed (350V), Voltage asymmetry : Fixed (30V)
TIME SETTINGS	Power On delay : 1 sec, Trip time : 0-999 sec, Recovery time : 1-999 sec , Response time : <120ms, 3 Reset attempt time : 0-999 min	Power ON delay : 1 sec (Fixed), Trip Time (sec) : 0,2,4,6,8 & 10, Recovery time : 15min, Response time : <240ms, 3 Reset attempt time : 60min (Fixed)
HYSTERESIS	Voltage : 0 to 10 V	Voltage : 6V (fixed)
ACCURACY	Current : $\pm 5\%$ of Ir ± 1 digit, Timing : $\pm 5\%$ ± 100 msec, Voltage : $\pm 1\%$ of 500V ± 1 digit	
OUTPUT CONTACT	1 C/O (SPDT)	
OUTPUT RATING	5A@250V AC / 28V DC	

Motor Protection Current Transformer



MPCT
73(H) x 100(W) x 60(D)mm

Description	Common Accessory for MPR & PPR
Current range	10A, 40A, 80A



PPRD-4M-1-230V
90(H) x 70(W) x 60(D)mm



PPRWD-4M-1-230V
90(H) x 70(W) x 60(D)mm



PPRA-4M-1-230V
90(H) x 70(W) x 60(D)mm

FEATURES	- Monitors Over load (As per NEMA class curve), Over, Under current, Locked current - Over voltage, Under voltage - Direct current measuring up to 32A - LED indication : Power ON, Trip relay - Test & Reset function via key & terminal	- Monitors Over load (As per NEMA class curve), Over, Under current, Locked current - Over voltage, Under voltage - Automatic pump on & off as per water level detection - Direct current measuring up to 32A - Capacitor cut off features	- Monitors Over load (As per NEMA class curve), Over, Under current, Locked current - Over voltage, Under voltage, 4 Knob for variable setting - Direct current measuring up to 32A - LED indication : Power ON, Trip relay
DISPLAY	3 Digits, 7 Segment LED display	3 Digits, 7 Segment LED display	3 LED & 4 Knob for variable Setting
ELECTRICAL CONNECTION	1Ø - 2W		
MEASURING RANGE	A) Motor rated current Measuring : 1A to 30 A B) Voltage measuring range : 180 to 300VAC (L - N)		
TRIP SETTING	Over load : NEMA class curve 5, 10, 15, 20, 30 , Over current : 2A to 32A, Under current : 0.2 to 29A, Locked current : 2A to 32A Over voltage : 180V - 300V (L - N), Under voltage : 180V - 300V (L - N)		Over load : NEMA class curve 5, 10, 15, 20, 30 , Over current : 10% to 70%, Under current : 20% to 80% Locked current : 300% of Ir, Over voltage : 280V (fixed) Under voltage : 180V (fixed)
TIME SETTINGS	Power ON delay : 1 sec (Fixed), Trip time delay : 0 - 999 sec Recovery time : 1 - 999 sec, Reset attempts 3 (fixed) : 1 - 999 min		Power ON delay : 1 sec (fixed), Trip time delay : 0 - 10 sec Auto Reset Time : 15 min, Reset attempts 3 (fixed) : 60 min
ACCURACY	Current accuracy : $\pm 5\%$ of rated current ± 1 digit, Voltage accuracy : $\pm 1\%$ of 300V ± 1 digit, Time accuracy : $\pm 5\% \pm 100\text{msec}$		
OUTPUT CONTACT	1 NO relay	2 NO relay	1 NO relay
OUTPUT RATING	30A@277V AC		
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	180 to 300V AC (L - N)		

Liquid Level Controllers



WLCA2M1
90(H) x 35(W) x 60(D)mm



WLCA-2M-U-CE
90(H) x 35(W) x 60(D)mm




LLCA-2M-U-CE
90(H) x 35(W) x 60(D)mm

FEATURES	• Used for drain & fill control • 3 No's stainless steel prods • 10A SPDT output (Resistive)	• Selectable suction and delivery mode in single tank operation • Used for two tank monitoring, Single tank water level monitoring • Manual start facility • Trip relay & alarm relay indication	• Selectable suction and delivery mode in single tank operation • Used for single and two tank liquid level monitoring • Pump protection from dry run and overflow • Adjustable trip & recovery time delay • Manual start facility	
	DISPLAY	2 LED indication	4 LED indication	
	AUXILLARY SUPPLY	85 to 270V AC / DC		
	TRIP SETTING	According to the levels of sensor placed in the water tank		
	SENSITIVITY	1 ohms to 200Kohms	Auto	0 ohms to 500Kohms
TRIP TIME	0.5s	2s	0.5s to 10s	
MODE	Auto	Auto / Manual	Auto / Manual	
ACCURACY	±5% + 100msec			
OUTPUT CONTACT	1 C/O (SPDT)	2 N/O (2 SPST)	1 N/O & 1 N/C	
OUTPUT RATING	10A@250V AC / 28V DC	5A@ 250V AC / 28V DC	6A@ 277 V AC / 28V DC	

Liquid Level Sensor



- Stainless steel
- Suitable for conductive liquids



Line Monitoring Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
640PSR-CE	154 to 520V AC	CE
640PSR-V-CE	154 to 520V AC	CE
600PSR-CE	154 to 500V AC	CE
800PSR	154 to 500V AC	---
642PSR	280 to 520V AC	---
600SPP	154 to 500V AC	---
SPPA2M2	280 to 520V AC	---

Auto Switch

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
Auto switch-195/400V	195 to 400V AC	---
Auto switch-313/457V	313 to 457V AC	---

Earth Fault Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
900EFR-BL-U-CE	85 to 270V AC / DC	CE

Earth Fault Current Transformer

PRODUCT CODE	DIMENSION IN MM	CURRENT TRANSFORMER RATIO
EFCT 100/25 160/1A VA CL1	100x25	160/1A
EFCT 140/35 160/1A VA CL1	140x35	160/1A
EFCT 140/35 250/1A VA CL1	140x35	250/1A
EFCT 180/35 250/1A VA CL1	180x35	250/1A
EFCT 180/35 630/1A VA CL1	180x35	630/1A
EFCT 220/50 630/1A VA CL1	220x50	630/1A

Thermistor Protection Relay

PRODUCT CODE	OUTPUT	SUPPLY VOLTAGE	CERTIFICATION
TPRA2M1-1-U-CE	RELAY	90 to 270V AC / DC	CE

Voltage Monitoring Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
600VPR-170/290-CU	170 to 290V AC	CE
600VPR-310/520-CE	310 to 520V AC	CE
800VPR-3	310 to 520V AC	---
900VPR-2-280/520V	280 to 520V AC	---
900VPR-2-280/520V-CU-RoHS	280 to 520V AC	CE
900VPR-2-280/600V-CU-RoHS	280 to 600V AC	CE
900VPR-BL-U-CE	85 to 270V AC / DC	CE
VPRA2M-CE	127 to 288V AC	CE
VPRD2M	127 to 288V AC	---
VPRD2M-BL-CE	127 to 288V AC	CE

Current Monitoring Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
900CPR-1-BL-U-CE	85 to 270V AC / DC	CE
900CPR-3-1-BL-230V-CE	230V AC (±15%)	CE
900CPR-1-230V	230V AC (±15%)	---
900CPR-3-230V	230V AC (±15%)	---

Earth Leakage Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
600ELR-1-30/500mA-230V	230V AC (±15%)	---
900ELR-2-230V-CE	230V AC (±15%)	CE
ELRA2M2-1-230V-CE	230V AC (±15%)	CE
ELR-341-1	90 to 270V AC / DC	---
ELCTR35-1-30mA-230V-CE	230V AC (±15%)	CE
ELCTR35-1A-30mA-230V	230V AC (±15%)	---
ELCTR35-1-300mA-230V-CE	230V AC (±15%)	CE
ELCTR35-1A-300mA-230V	230V AC (±15%)	---

Core Balance Current Transformer

PRODUCT CODE	INNER DIAMETER (IN MM)	CERTIFICATION
CBCT-35-1-CE	35	CE
CBCT-70-1-CE	70	CE
CBCT-120-1-CE	120	CE
CBCT-210-1-CE	210	CE
CBCT-310-1-CE	310	CE

Motor / Pump Protection Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
MPR-3M-2-230V	230V AC (± 15%)	---
MPR-3M-2-415V	415V AC (± 15%)	---
MPR-341-2	90 to 270V AC / DC	---
PPRD-4M-3-415V	415V AC (± 15%)	---
PPRA-4M-3-415V	415V AC (± 15%)	---
PPRD-4M-1-230V	180 to 300V AC	---
PPRWD-4M-1	180 to 300V AC	---
PPRA-4M-1-230V	180 to 300V AC	---

Motor Protection Current Transformer

PRODUCT CODE	INPUT CURRENT	CERTIFICATION
MPCT D15 10 A	10 A	---
MPCT D15 40 A	40 A	---
MPCT D15 80 A	80 A	---

Liquid Level Controller & Accessories

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
WLCA2M1-CE-RoHS	85 to 270V AC / DC	CE
WLCA-2M-U-CE	85 to 270V AC / DC	CE
LLCA-2M-1-U-CE-RoHS	85 to 270V AC / DC	CE
PRODUCT CODE	DESCRIPTION	
WLC SENSOR	Set of 3 Numbers	

Astronomical Time Switch

Daily / Weekly Time Switches



ATS2M1-1-16A
90(H) x 35(W) x 60(D)mm



TS2M1-2-16A
90(H) x 35(W) x 60(D)mm



TS2M1-1-16A
90(H) x 35(W) x 60(D)mm



TS1W1-1-20A
60(H) x 60(W) x 47.65(D)mm

FEATURES	- Latitude / Longitude precise to the minute with time zone - Automatic calculation of sunrise & sunset times - DST offset / power saving mode 1 channel 10 years power reserve (replaceable battery)	1 sec least count 30 ON - 30 OFF steps per day 2 channel - Auto / Permanent override ON / Permanent Override OFF 10 years power reserve (replaceable battery)	1 sec least count 50 ON - 50 OFF steps per day 1 channel - Auto / Permanent override ON / Permanent Override OFF 10 years power reserve (replaceable battery)
DISPLAY	Text LCD (Without backlight)		
RTC SHIFT	6 minutes a year @ 25°C		
OUTPUT CONTACT	1 C/O SPDT	2 x 1 C/O SPDT	1 C/O SPDT
CONTACT RATING	16A @ 250V AC	16A @ 250V AC	20A @ 250V AC
WEEKLY PROGRAM	---	For Relay 1 - Total 30 ON steps and 30 OFF steps 1 program 30 steps, 2 programs 15 steps, 3 programs 10 steps, 4 programs 07 steps, 5 programs 06 steps. (Same for Relay 2)	Total 50 ON steps and 50 OFF steps - 2 program 25 steps, 3 programs 16 steps, 4 programs 12 steps, 5 programs 10 steps, 6 programs 08 steps, 7 programs 07 steps, 8 programs 06 steps
MINIMUM SETTING UNIT	---		1 second
HOLIDAY SETTINGS	---		16 dates
CLOCK	12hr (AM / PM) and 24hr selection		
RELAY OPERATING MODE	Auto / Permanent override ON / Permanent override OFF		
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	230V AC $\pm 10\%$		

Analog Timers



600ST
90(H) x 17.5(W) x 60(D)mm



600XU
90(H) x 17.5(W) x 60(D)mm



600SD
90(H) x 17.5(W) x 60(D)mm



642SQ-A
90(H) x 17.5(W) x 63.5(D)mm



642XA
90(H) x 17.5(W) x 63.5(D)mm

FEATURES	- Single function - ON delay 10 Time ranges	- Multi function (13 Functions) - Precise analog time setting - Universal supply voltage	- Star Delta 1 C/O Relay each for Star & Delta	2 Functions 8 Time ranges
MODES	ON delay	A, B, C, Ci, D, E, F, H, I, J, K, Ai, Bi	Star - Delta	ON delay / Interval
TIME RANGES	0.1 - 1sec, 0.3 - 3sec, 1 - 10sec, 3 - 30sec, 0.1 - 1min, 0.3 - 3min, 1 - 10min, 3 - 30min, 0.1 - 1hr, 0.3 - 3hr		Run up time : 3 - 30sec, 6 - 60sec Change over : 50/100ms	0 - 3sec / min, 0 - 10sec / min, 0 - 30sec / min, 0 - 60sec / min
RESOLUTION	0.1sec	0.1sec	---	0.3sec
ACCURACY	Setting : $\pm 5\%$ of F.S Repeat : $\pm 0.5\%$ F.S Pause time accuracy : $\pm 5\% \pm 5ms$			
OUTPUT CONTACT	1 C/O SPDT	1 C/O SPDT	1 C/O Relay each for Star & Delta	1 C/O SPDT
CONTACT RATING	5A @ 250V AC / 24V DC			
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	240V AC	20 to 240V AC, 12 to 240V DC	230V AC	230V AC, 24V AC / DC
Modes	600XU A - ON delay, B - Interval, C - Repeat cycle equal OFF first, Ci - Repeat cycle equal ON first, D - Pulse output 500ms fixed, E - Delay on break, F - Delay on make / Delay on break, H - Interval after break, I - Single shot, J - Retriggerable single shot, K - Latching relay, Ai - Delay on break with Totalise, Bi - Interval with Totalise			



800XU
75(H) x 22.5(W) x 105.5(D)mm



800XA
75(H) x 22.5(W) x 105.5(D)mm



800SQ-A
75(H) x 22.5(W) x 105.5(D)mm



800S
75(H) x 22.5(W) x 105.5(D)mm

FEATURES	2 Functions 12 Time ranges - Universal supply voltage		2 Functions 8 Time ranges - Universal supply voltage	2 Functions 8 Time ranges	- Single function - Fixed time range (60sec)
MODES	ON delay / Interval				ON delay
TIME RANGES	1 / 3 / 10 / 30sec / min / hr	3 / 10 / 30 / 60sec / min	3 / 10 / 30 / 60sec / min	3 / 10 / 30 / 60sec / min	60sec
RESOLUTION	0.1sec	0.3sec	0.3sec	0.3sec	6sec
ACCURACY	Setting : $\pm 5\%$ of F.S. Repeat : $\pm 0.5\%$ or 50ms (Whichever is greater)				
OUTPUT CONTACT	2 C/O SPDT	2 C/O SPDT	1 C/O SPDT	1 C/O SPDT	1 C/O SPDT
CONTACT RATING	5A @ 250V AC / 24V DC				
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	20 to 240V AC, 12 to 240V DC		230V AC & 24V AC / DC		230V AC, 415V AC



800SD-2
75(H) x 22.5(W) x 105.5(D)mm



800XC
75(H) x 22.5(W) x 105.5(D)mm



800XMR
75(H) x 22.5(W) x 105.5(D)mm



800POD
75(H) x 22.5(W) x 105.5(D)mm

FEATURES	- Star delta 1 C/O Relay each for Star & Delta	- Asymmetrical cyclic 6 Time ranges	- Forward pause reverse 1 C/O Relay each for Forward & Reverse	- True power OFF delay - Fixed time range (180sec)
MODES	Star - Delta	Asymmetrical Cyclic ON first or OFF first	Forward - Pause - Reverse	True Power OFF Delay
TIME RANGES	Run up time : 30 / 60sec Change over : 50 / 100msec	1 / 10sec / min / hr for both ON & OFF time	ON time : 1 / 2 / 4 / 8min Pause time : 10 / 20 / 40 / 80s	180sec
RESOLUTION	---	0.1sec	ON time : 6s Pause time : 0.1s	7.5sec
ACCURACY	Setting : $\pm 5\%$, Repeat : $\pm 0.5\%$ of F.S or 50ms			
OUTPUT CONTACT	1 C/O Relay each for Star & Delta	2 C/O SPDT	1 C/O Relay each for Forward & Reverse	2 C/O SPDT
CONTACT RATING	5A @ 250V AC / 24V DC			
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	110V AC, 230V AC 230 to 415V AC	20 to 240V AC, 12 to 240V DC		110 to 240V AC / DC



55XU
48(H) x 48(W) x 70.5(D)mm



55XC
48(H) x 48(W) x 70.5(D)mm



55ES
48(H) x 48(W) x 70.5(D)mm

FEATURES	- Plug / Panel mount - ON delay / Interval 12 Time ranges	- Plug / Panel mount - Asymmetrical Cyclic ON - OFF 6 Time ranges	- Plug / Panel mount - ON delay / Interval 8 Time ranges
BASE TYPE	P8 - 8 Pin plug, T8 - Screw terminal		
MODES	ON delay / Interval	Asymmetrical Cyclic ON first or OFF first	ON delay / Interval
TIME RANGE	1 / 3 / 10 / 30sec / min / hr	1 / 10sec / min / hr for both ON & OFF time	3 / 10 / 30 / 60sec / min
RESOLUTION	0.1sec		0.3sec
ACCURACY	Setting : $\pm 5\%$ of F.S., Repeat : $\pm 0.5\%$ or 50 ms		
OUTPUT CONTACT	2 C/O SPDT		1 C/O SPDT
CONTACT RATING	5A @ 250V AC / 24V DC		
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	20 to 240V AC, 12 to 240V DC		230V AC, 24V AC / DC



55MF
48(H) x 48(W) x 70.5(D)mm



600DT
90(H) x 17.5(W) x 62(D)mm

FEATURES	- Multi function (10 Functions) - Wide time range (0.05sec to 300hr) - Universal supply voltage	- Multi function (15 Functions) - Wide time range (0.1sec to 999hr) - Universal supply voltage
DISPLAY	---	3 + 3 digits
SET POINT	---	Single set point
MODES	A, B, C, D, E, F, G, H, I, J	A, B, C, D, E, F, H, J, K, L, P, Q, R, T, U
TIME RANGES	0.05sec to 300hr	9.99 / 99.9 / 999sec, 9 : 59min : sec, 99.9 / 999min, 9 : 59hr : min, 99.9 / 999hr
RESOLUTION	0.05sec	0.01sec
TIME SETTING	Front knobs	Front keypad
RESET / START INPUT	Start : Gate/Pulse start (Depending on modes) Reset : Terminal / Remote	Start : Gate/Pulse start (Depending on modes) Reset : Front panel, On power interruption
ACCURACY	Setting : $\pm 5\%$ of F.S., Repeat : $\pm 0.5\%$ or 50 ms	Setting : $\pm 0.1\%$ of F.S. or $\pm 50\text{ms}$, For Y contact operation : $+100\text{ms}$, Repeat : $\pm 0.1\%$
OUTPUT CONTACT	2 x 1 C/O SPDT	1 C/O SPDT
CONTACT RATING	6A @ 250V AC / 24V DC, resistive	8A @ 250V AC
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	20 to 240V AC / DC	20 to 240V AC / DC
Modes	600DT	A - ON delay, B - Interval, C - Asymmetrical cyclic OFF first, D - Asymmetrical cyclic ON first, E - Repeat cycle equal OFF first, F - Repeat cycle equal ON first, H - Pulse output, J - Delay on break, K - Delay on make/Delay on break, L - Interval after break, P - Single shot, Q - Retriggerable single shot, R - Latching relay, T - Delay on break with totalise, U - Interval with totalise
	55MF-P11	A - Signal ON delay, B - Interval, C - Cyclic Equal OFF first, D - Cyclic Equal ON first, E - Signal OFF delay, F - Signal ON / OFF delay, G - Interval after break H - Single shot, I - Retriggerable single shot, J - Delay on make/Delay on break
	55MF-P8	A - ON delay, B - Pulse output with instantaneous limit, C - ON delay instantaneous limit, D - Interval with instantaneous limit, E - Cyclic equal OFF first, F - Cyclic equal OFF first with instantaneous limit, G - Cyclic equal ON first, H - Cyclic equal ON first with instantaneous limit, I - Star delta with 50ms pause time, J - Star delta with 100ms pause time

Ordering information

Digital Time Switches

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
ATS2M1-1-16A-230V-CE	230V AC	CE
TS2M1-2-16A-230V-CE	230V AC	CE
TS2M1-1-16A-230V V2	230V AC	---
TS2M1-1-16A-230V-CE	230V AC	CE
TS1W1-1-20A-230V	230V AC	---
TS1W1-1-20A-230V-CE	230V AC	CE

Analog Timers

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
800XU-CU	20 to 240V AC, 12 to 240V DC	CE, RoHS
800XA	20 to 240V AC, 12 to 240V DC	---
800XA-CE	20 to 240V AC, 12 to 240V DC	CE
800SQ-A	230V AC, 24V AC/DC	---
800S-1-ON-60S-230	230V AC	---
800S-1-ON-60S-415	415V AC	---
800SD-2-230	230V AC	---
800SD-2-230-CE	230V AC	CE
800SD-2-110	110V AC	---
800SD-2-415	230 to 415V AC	---
800XC	20 to 240V AC, 12 to 240V DC	---
800XC-CE	20 to 240V AC, 12 to 240V DC	CE
800XMR	20 to 240V AC, 12 to 240V DC	---
800POD-180S	110 to 240V AC / DC	---

Analog Timers

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
600XU-A-1-CU	20 to 240V AC, 12 to 240V DC	CE, RoHS
600SD-2-230	230V AC	CE
600ST	240V AC	CE
600ST-CU	240V AC	CE, RoHS
642SQ-A	230VAC, 24V AC / DC	---
642XA	20 to 240V AC, 12 to 240V DC	---
55XU-P8-230V-G	20 to 240V AC, 12 to 240V DC	CE, RoHS
55XU-T-230V-G	20 to 240V AC, 12 to 240V DC	CE, RoHS
55XC-P8-230V-G	20 to 240V AC, 12 to 240V DC	CE, RoHS
55XC-T-230V-G	20 to 240V AC, 12 to 240V DC	CE, RoHS
55ES-P8-230V-G	230V AC, 24V AC / DC	CE, RoHS
55ES-T-230V-G	230V AC, 24V AC / DC	CE, RoHS
55MF-P11	20 to 240V AC / DC	CE
55MF-P8	20 to 240V AC / DC	CE

Digital Timers

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
600DT	20 to 240V AC / DC	CE
600DT-CU	20 to 240V AC / DC	CE, RoHS



XT543N
48(H) x 48(W) x 100(D)mm



XT56-N
48(H) x 48(W) x 60(D)mm



XT264-3
72(H) x 72(W) x 115(D)mm



XT364-3
96(H) x 96(W) x 90(D)mm

FEATURES	- Multi function (4 Functions) 9 Time ranges - Single set point	- Thumbwheel setting 6 Time ranges - Single set point
DISPLAY	3 digits	
SET POINT	Single set point	
MODES	ON delay / Interval / Cyclic ON first / Cyclic OFF first	ON delay / Interval
TIME RANGES	9.99 / 99.9 / 999sec, 9 : 59min : sec, 99.9 / 999min, 9 : 59hr : min, 99.9 / 999hr	9.99 / 99.9 / 999sec, 99.9 / 999min, 99.9hr
RESOLUTION	0.01sec	
TIME SETTING	Front keypad	Thumbwheel
RESET / START INPUT	Start : Gate / Pulse start (Programmable)	Start : Pulse start
	Reset : Front panel, Remote reset, On power interruption	
ACCURACY	±0.5% of F.S. or 50ms	
OUTPUT CONTACT	2 C/O SPDT	
CONTACT RATING	5A @ 250V AC or 24V AC / DC	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC [24V DC (Optional) - For XT56-N]	



XT546BX
48(H) x 48(W) x 76(D)mm



XT546
48(H) x 48(W) x 94(D)mm



XT246
72(H) x 72(W) x 83.7(D)mm



XT346
96(H) x 96(W) x 73(D)mm



XT5042
48(H) x 48(W) x 100(D)mm



PT380
96(H) x 96(W) x 100(D)mm

FEATURES	- Short depth - Multi function (4 Functions) 9 Time ranges - Single set point	- Multi function (4 Functions) 9 Time ranges - Single set point	- Multi function (7 Functions) - Pulse start (Input through PNP / NPN sensor) - Dual set point - Individual time setting for relays	8 Channels 4 Functions - Parallel / Sequential operation - Cascade output for channel expansion
DISPLAY	3 + 3 digits		4 + 4 digits	2 + 4 digits
SET POINT	Single set point		Dual set point	Single set point
MODES	ON delay / Interval / Cyclic ON first / Cyclic OFF first		ON delay / Interval / Cyclic ON first / Cyclic OFF first / Forward-Pause-Reverse / Instantaneous + Delayed / Timer / Batch	ON delay / Interval / Cyclic ON first / Cyclic OFF first (Start up delay & no. of cycles programmable for cyclic mode)
TIME RANGES	9.99 / 99.9 / 999sec, 9.59min : sec, 99.9 / 999min, 9.59hr : min, 99.9 / 999hr		99.99 / 999.9 / 9999sec, 99.59min : sec, 999.9 / 9999min, 99.59hr : min, 999.9 / 9999hr	99.99sec, 999.9sec, 99.59min : sec, 99.59hr : min, 999.9hr
RESOLUTION	0.01sec			
DIRECTION	Up / Down	Down	Up / Down	Up
TIME SETTING	Front keypad			
NO. OF CHANNELS	—			8 Channels
RESET/START INPUT	Start : Gate / Pulse start (Programmable) Reset : Front panel, Remote reset, On power interruption			
ACCURACY	±0.05% of F.S. or 50ms			±0.5% of F.S. or 50ms
OUTPUT CONTACT	2 C/O SPDT		2 C/O SPST	8 NOs with 1 Com
CONTACT RATING	5A @ 250V AC or 24V DC			
MEMORY RETENTION	10 years (User selectable)			
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	85 to 270V AC / DC [24V DC (Optional) - For XT546 & XT246]		90 to 270V AC / DC or 24V DC	85 to 270V AC / DC



TT103C
48(H) x 96(W) x 88(D)mm



TT412
36(H) x 72(W) x 74.5(D)mm



TT412B
36(H) x 72(W) x 74.5(D)mm



LT920A
24(H) x 48(W) x 48(D)mm



LT945A
24(H) x 48(W) x 48(D)mm
With Clamp
48(H) x 48(W) x 48(D)mm

FEATURES	• Time Interval Meter • Range : Auto ranging, Fixed ranges	• LED Hour Meter • Selectable least count	• Time totaliser • Selectable least count • Inbuilt sensor supply • Universal power supply	• LCD Hour Meters • Battery powered • Contact / Voltage input	
DISPLAY	4 digits	6 digits	6 digit 7 segment LED Display	7½ digits	
TIME RANGES	a)Auto ranging : .0001 to 9999sec b) Fixed ranges : .9999, 9.999, 99.99, 999.9,9999sec	99999.9 / 999999sec / min / hr	a) 99999.9 sec, b) 999999 sec c) 99999.9 min, d) 999999 min e) 99999.9 hrs, f) 999999 hrs	a) 1999.59.59hr.min:sec b) 199999.99hr	
ACCURACY	±0.05% + 1 count		±0.05%		
INPUT	Potential free contact & 3 to 30V DC from solid state devices	Mains, Potential free contact, PNP sensor	Potential free contact, PNP Sensor	a) 24 to 260V AC / DC b) Contact input	
RESET	Front, Remote (Reset time : 20ms), Auto	Remote (Reset time : 20ms)	Terminal	Front, Remote	Remote
MEMORY	---	10 years		5 years	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC			Battery powered	

Digital Counters



XC22B V2
72(H) x 72(W) x 115(D)mm



XC1200
48(H) x 96(W) x 88(D)mm



XC2200
72(H) x 72(W) x 91(D)mm

FEATURES	• Thumbwheel setting • Auto reset • Battery backup • Memory retention	• Counter with rate indicators • Programmable input scaling • Up, Down, Quadrature & Bi-directional modes • Dual set point	• Counter with rate indicator • Programmable input scaling • Unidirectional, Bi - directional & Quadrature modes • Batch counter
DISPLAY	4 digits	6 digits	6 + 4 digits
MODES	ON delay / Interval / Auto reset	ON delay / Interval / Auto reset / Time pulse repeat	
RANGES	9999 counts	Selectable least count : 0.0001, 0.001, 0.01, 0.1 & 1 Rate : 4.00 to 99999 RPM / RPH	-999 to 999999 counts
RESET	Front, Remote, Auto (Optional)	Front (user selectable), Remote	Front, Remote, Power interruption
MEMORY	Yes (Optional)	Yes	
DIRECTION	Up	Up, Down, Bi-directional, Quadrature	
SET POINT	Single set point	Dual set point	
INPUT SPEED	30Hz, 5kHz (Selectable via dip switch)	30Hz, 2.5kHz, 5kHz (Programmable)	30Hz, 5kHz (Programmable)
SCALE FACTOR	---	0.00001 to 9.99999 x 10 ⁿ , n= -5, -4, -3, -2, -1, 0, 1, 2	
SENSOR SUPPLY	Inbuilt, 12V DC @30mA		
OUTPUT CONTACT	2 C/O SPDT	2 C/O SPDT	
CONTACT RATING	5A @ 250V AC or 24V DC	5A @ 250V AC or 24V DC	
INPUT	NPN, PNP sensor, Potential free contacts	NPN / PNP sensor, Potential free contacts, Encoder	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC		

LCD Counters

LED Counters



LTC9A
24(H) x 48(W) x 48(D)mm



LXC900A
24(H) x 48(W) x 48(D)mm



XC410B
36(H) x 72(W) x 74.5(D)mm



XC10D
48(H) x 96(W) x 88(D)mm

FEATURES	• Time / Count totaliser • Battery powered • Contact / Voltage input selectable	• LCD counter • Battery powered • Contact / Voltage input	• Count Totaliser • Compact size • Inbuilt sensor supply • Universal power supply	• LED counter • Inbuilt sensor supply • Compact size
DISPLAY	7 ^{1/2} digits		6 digit 7 segment LED Display	6 digits
MODES	Timer / Counter	Counter	---	---
RANGES	Hour meter : a) 1999.99.99 hr:min:sec ; b) 199999.99hr Counter : 19999999 counts	19999999 counts	999999 counts	999999 counts
RESET	Front, Remote		Front, Terminal	Front, Remote
MEMORY	5 years		Yes, 10 Years	Yes
DIRECTION	Up			
SET POINT	---			
INPUT SPEED	14Hz, 100Hz (Selectable via jumper)		20Hz, 5kHz	3Hz, 30Hz, 1kHz (Selectable via jumper)
SENSOR SUPPLY	---		12VDC@30mA	
INPUT	a) 24 to 260V AC / DC b) Contact input		NPN, PNP sensor, Potential free contacts	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	Battery powered		90 to 270V AC / DC	

Digital Timer - Counter

Time / Count Totaliser



XTC5400
48(H) x 48(W) x 100(D)mm



XTC4102
36(H) x 72(W) x 74.5(D)mm

FEATURES	- Multi function - Timer / Counter (programmable) - Batch counter	- Up / Down counting for counter - Dual set point	- LED count/ time totalizer - Compact size - Inbuilt sensor supply
DISPLAY	4 + 4 digits		6 digits White LED display
MODES	Timer : ON delay / Interval / Cyclic ON first / Cyclic OFF first / Batch. Counter : ON delay / Interval / Auto reset / Time pulse repeat / Batch		- - -
RANGES	Timer : 99.99/999.9/9999sec, 99:59min:sec, 999.9/9999min, 99:59hr:min, 999.9/9999hr, Counter : -999 to 9999 counts		Counter : 999999 counts Timer : 99999.9 sec, 999999 sec, 99999.9 min,999999 min, 99999.9 hrs, 999999 hrs
RESET	Front, Remote, Power interruption		Counter - Front key, Timer - Terminal
MEMORY	Yes		10 years retention
DIRECTION	Timer : Down, Counter : Up / Down		Up
SET POINT	Dual set point		...
INPUT SPEED	3Hz, 30Hz, 5kHz (Programmable)		20Hz, 5KHz
SENSOR SUPPLY	Inbuilt, 12V DC @30mA		
SCALE FACTOR	0.001 to 9.999 x 10" n = -3, -2, -1, 0, 1, 2		...
OUTPUT CONTACT	2 C/O SPST		...
CONTACT RATING	5A @ 250V AC or 24V DC		...
INPUT	NPN, PNP sensor, Potential free contacts		Counter : 5 to 30V DC from Proximity switches, Encoders, Potential free contacts, Limit switches etc. Timer : Potential free contact
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC		90 to 270V AC/DC or 12 to 24V DC (Non isolated)



RC5100
48(H) x 48(W) x 100(D)mm



SMRD4M1
90(H) x 70(W) x 62(D)mm

FEATURES	- Measures up to 9999 RPM - Inbuilt sensor supply	- Under, Over, Dual speed modes - Dual set point - RPH, RPM, RPS ranges - Scalable input, Auto ranging
DISPLAY	4 digits	
RANGE	4.00 to 9999 RPM	Auto ranging, RPH, RPM or RPS
INPUT SPEED	4 to 9999 pulses per minute	
SCALE FACTOR	---	0.001 to 9.999 x 10 ⁿ (n= -3, -2, -1, 0, 1, 2)
SENSOR SUPPLY	Inbuilt, 12V DC, ±10%, 30mA	
COUNTING DIRECTION	Up	
INPUT	PNP sensors, Encoders, Potential free contact	
SUPPLY VOLTAGE (AC : 50 / 60Hz)	90 to 270V AC / DC	

Ordering information

Digital Timers

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
XT543-N	90 to 270V AC / DC	---
XT56-N	90 to 270V AC / DC	---
XT56-N-24	24V DC	---
XT56-N-CE	90 to 270V AC / DC	CE
XT264-3	90 to 270V AC / DC	---
XT364-3	90 to 270V AC / DC	---
XT546BX	85 to 270V AC	---
XT546	85 to 270V AC	---
XT546-24V	24V DC	---
XT546-CE	85 to 270V AC	CE
XT246	85 to 270V AC	---
XT246-24V	24V DC	---
XT346	85 to 270V AC	---
XT5042	90 to 270V AC / DC	---
XT5042-24	24V DC	---
XT5042-CU	90 to 270V AC / DC	CE, RoHS
PT380	85 to 270V AC / DC	---

Digital Counters

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
XC22B V2	90 to 270V AC / DC	---
XC1200	90 to 270V AC / DC	CE
XC2200	90 to 270V AC / DC	---
XC2200-CE	90 to 270V AC / DC	CE

Digital Timer-Counter

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
XTC5400	90 to 270V AC / DC	CE
XTC5400-CU	90 to 270V AC / DC	CE, RoHS
XTC4102-CE	90 to 270V AC / DC	CE

LCD / LED Counters

PRODUCT CODE	INPUT TYPE		CERTIFICATION
	CONTACT	VOLTAGE	
LTC9A	YES	YES	---
LXC900A-C	YES	---	---
LXC900A-V	---	YES	---
LXC900A-C-CE	YES	---	CE
LXC900A-V-CE	---	YES	CE
PRODUCT CODE	SUPPLY VOLTAGE		CERTIFICATION
XC410A-1-230	230V AC		---
XC410B	90 to 270V AC / DC		---
XC10D	90 to 270V AC / DC		---

Time Interval Meter / Hour Meters

PRODUCT CODE	SUPPLY VOLTAGE		CERTIFICATION
TI103C	90 to 270V AC / DC		---
TT412	90 to 270V AC / DC		---
TT412B	90 to 270V AC / DC		---
PRODUCT CODE	INPUT TYPE		CERTIFICATION
	CONTACT	VOLTAGE	
LT920A-C	YES	---	---
LT920A-V	---	YES	---
LT945A-C	YES	---	---
LT945A-V	---	YES	---
LT920A-C-CE	YES	---	CE
LT920A-V-CE	---	YES	CE
LT945A-C-CE	YES	---	CE
LT945A-V-CE	---	YES	CE

Rate Indicators

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
RC5100A	90 to 270V AC / DC	---

Speed Monitoring Relay

PRODUCT CODE	SUPPLY VOLTAGE	CERTIFICATION
SMRD4M1-2-U-CE	90 to 270V AC / DC	CE



TC544C
48(H) x 48(W)
x 76(D)mm

TC244CX
72(H) x 72(W)
x 83.7(D)mm

TC344CX
96(H) x 96(W)
x 73(D)mm



TC513CX
48(H) x 48(W)
x 76(D)mm

TC203CX
72(H) x 72(W)
x 83.7(D)mm

TC303CX
96(H) x 96(W)
x 73(D)mm



TC538CX
48(H) x 48(W)
x 76(D)mm

FEATURES	- Dual bright display, Dual set point - TC / RTD input - Control output : Relay or SSR - Auxiliary output : Relay - Dwell timer, Heat cool PID - IDM applicable	- Single White display, Single set point - Control output : Relay or SSR - High power Relay - TC / RTD input - IDM applicable	- Dual display, Single set point - Short depth TC - TC / RTD input - Control output : Relay or SSR
DISPLAY	4 + 4 digits, 7 segment LED dual (White+Green) display		4 + 4 digits, 7 segment LED dual display
INPUT TYPE	Thermocouple (J, K, T, R, S) / RTD (PT100)		
RESOLUTION	0.1/ 1° for TC / RTD (fixed 1° for R & S TC)		Fixed 1° resolution
ACCURACY	For TC inputs : 0.25% of F.S. $\pm 1^\circ$; For R & S inputs : 0.5% of F.S. $\pm 1^\circ$ (20 min of warm up time); For RTD input : 0.1% of F.S. $\pm 1^\circ$		
SETPOINT	Dual set point		Single Set point
CONTROL MODE	Auto/Self tune PID or ON - OFF		
CONTROL OUTPUT	Relay : SPDT 5A (SPST for TC544C) resistive @ 250V AC / 30V DC or SSR (Field Selectable) : 12V DC, 50mA		Relay : SPDT 10A resistive @ 250V AC / 30V DC or SSR : 12V DC, 50mA
AUXILIARY OUTPUT	Relay : SPDT 5A (SPST for TC544C) resistive @ 250V AC / 30V DC		---
SPECIAL FUNCTIONS	Heat cool PID, Dwell timer, IDM applicable		---
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC		

Temperature Controllers



TC544B
48(H) x 48(W) x 76(D)mm



TC513BX
48(H) x 48(W) x 76(D)mm



TC533BX
48(H) x 48(W) x 76(D)mm



TC538BX
48(H) x 48(W) x 76(D)mm



TC544-CT
48(H) x 48(W) x 76(D)mm

FEATURES	• TC / RTD input • ON-OFF / PID control (Auto tune / self tune) • Dual set point • Selectable control output : Relay / SSR • Auxiliary output : Relay	• Single display, Single set point • Short depth TC • TC / RTD input • Control output : Relay or SSR	• Dual display, Single set point • Short depth TC • TC / RTD input • Control output : Relay or SSR	• Dual display, Single set point • Short depth TC • TC / RTD input • Control output : Relay or SSR	• Dual display, Dual set point • TC / RTD & CT input • Control output : Relay or SSR • Auxiliary output : Relay • 0-100A AC input CT range
DISPLAY	4 + 4 digits, 7 segment LED dual display	3 digits, 7 segment LED single display	3 + 3 digits, 7 segment LED dual display	4 + 4 digits, 7 segment LED dual display	
INPUT TYPE	Thermocouple (J, K, T, R, S) / RTD (PT100)				Thermocouple (J, K, T, R, S) / RTD (PT100)/ CT
RESOLUTION	0.1/1° for TC/RTD inputs (fixed 1° for R & S type TC input)	Fixed 1° resolution			0.1/ 1° for TC / RTD (fixed 1° for R & S TC)
ACCURACY	For TC input : 0.25% of F.S. ±1° ; For R & S inputs : 0.5% of F.S. ±2° (20 min of warm up time for TC inputs); For RTD input : 0.1% of F.S. ±1°				
SETPOINT	Dual set point	Single set point			Dual set point
CONTROL MODE	Auto tune / Self tune PID or ON-OFF				Autotune PID or ON - OFF or Heat-Cool
CONTROL OUTPUT	Relay : SPST : 5A resistive @ 250V AC/ 30V DC or SSR : 12V DC, 30mA	Relay : SPDT : 10A resistive @ 250V AC / 30V DC or SSR : 12V DC, 50mA			Relay : SPDT 5A resistive @ 250V AC / 30V DC or SSR (Field Selectable) : 12V DC, 50mA
AUXILIARY OUTPUT	Relay : 5A resistive @ 230V AC / 30V DC	---			Relay : SPDT 5A resistive @ 250V AC /30V DC
SPECIAL FUNCTIONS	Heat cool PID, Dwell timer	---			Single phase, full wave monitoring of load currents controlled by auxiliary output LA/HA/BAND Alarm
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC				



TC544A
48(H) x 48(W)
x 94(D)mm

TC244AX
72(H) x 72(W)
x 83.7(D)mm

TC344AX
96(H) x 96(W)
x 73(D)mm



TC513AX
48(H) x 48(W)
x 94(D)mm

TC203AX
72(H) x 72(W)
x 83.7(D)mm

TC303AX
96(H) x 96(W)
x 73(D)mm



TC533AX
48(H) x 48(W)
x 94(D)mm

TC233AX
72(H) x 72(W)
x 83.7(D)mm

TC333AX
96(H) x 96(W)
x 73(D)mm

FEATURES	- Dual display, Dual set point - TC / RTD input - Control output : Relay or SSR - Auxiliary output : Relay - Dwell timer, Heat cool PID	- Single display, Single set point - TC / RTD input - Control output : Relay or SSR	- Dual display, Single set point - TC / RTD input - Control output : Relay or SSR
DISPLAY	4 + 4 digits, 7 segment LED dual display		
INPUT TYPE	Thermocouple (J, K, T, R, S) / RTD (PT100)		
RESOLUTION	0.1/1° for TC / RTD (fixed 1° for R & S TC)		Fixed 1° resolution
ACCURACY	For TC inputs : 0.25% of F.S. $\pm 1^\circ$; For R & S inputs : 0.5% of F.S. $\pm 2^\circ$ (20 min of warm up time); For RTD input : 0.1% of F.S. $\pm 1^\circ$		
SETPOINT	Dual set point		Single set point
CONTROL MODE	Autotune PID or ON - OFF		
CONTROL OUTPUT	Relay : SPDT (SPST for TC544A) : 5A resistive @ 250V AC / 30V DC or SSR (Field Selectable) : 12V DC, 50mA		Relay : SPDT (SPST for TC303A) : 10A resistive @ 250V AC / 30V DC or SSR : 12V DC, 50mA (except TC303A)
AUXILIARY OUTPUT	Relay : SPDT (SPST for TC544A) : 5A resistive @ 250V AC / 30V DC		---
SPECIAL FUNCTIONS	Heat cool PID, Dwell timer		---
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC, 24V DC (Optional for TC544 Only)		90 to 270V AC / DC & 24VDC (Optional for TC513AX only)



DTC503
48(H) x 48(W) x 76(D)mm



DTC231
72(H) x 72(W) x 83.7(D)mm



DTC331
96(H) x 96(W) x 38.8(D)mm



DTC204A-2
72(H) x 72(W) x 83.7(D)mm



DTC324A-2
96(H) x 96(W) x 73(D)mm

FEATURES	3 Digit single display - J, K TC input - ON-OFF / PID control	3 Digit single display - J, K TC input - ON-OFF mode	- Single display, Dual set point - TC / RTD input - Control output : Relay or SSR - Auxiliary output : Relay
DISPLAY	3 digits, 7 segment LED single display		
INPUT TYPE	Thermocouple (J, K)		
RESOLUTION	Fixed 1° resolution		
ACCURACY	For J, K inputs : 0.25% of F.S. $\pm 1^\circ\text{C}$	0.25% of F.S. $\pm 1^\circ$ (20 min warm up time)	For TC Inputs : 0.25% of F.S. $\pm 1^\circ$; For R & S Inputs : 0.5% of F.S. $\pm 2^\circ$ (20 min of warm up time); For RTD Input : 0.1% of F.S. $\pm 1^\circ$
SETPOINT	Single set point		
CONTROL MODE	ON-OFF / PID	ON-OFF	Autotune PID or ON - OFF
CONTROL OUTPUT	Relay : SPDT : 10A resistive @ 250V AC / 30V DC	Relay : SPST : 10A resistive @ 250V AC / 30V DC	Relay : SPDT : 10A resistive @ 250V AC / 30V DC or SSR : 12V DC, 30mA
AUXILIARY OUTPUT	---		Relay : SPDT : 5A resistive @ 250V AC / 30V DC
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC		

Analog Temperature Controller



TC52
48(W) x 48(H)
x 100(D)mm

FEATURES	- Dial setting - TC input - Single Relay Output - Easy to Use
DISPLAY	Dial Setting
INPUT TYPE	Thermocouple (J)
RESOLUTION	Fixed 1° resolution

ACCURACY	Setting : $\pm 3\%$ of full scale , $\pm 0.5\%$ of full scale
SETPOINT	Single set point
CONTROL MODE	Time Proportional & ON-OFF
CONTROL OUTPUT	SPST : 7A resistive @ 230V AC
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	230V AC



PID500-T
48(H) x 48(W) x 100(D)mm



PID500
48(H) x 48(W)
x 100(D)mm



PID110
96(H) x 48(W)
x 74.5(D)mm



PID330
96(H) x 96(W)
x 74.5(D)mm



PID528
48(H) x 48(W) x 100(D)mm

FEATURES	- TC / RTD input - Single step ramp soak - Max 3 outputs - Retransmission (Optional)	- Advanced PID control - Universal input - Single step ramp soak - Max 3 outputs - Retransmission (Optional) - RS485 MODBUS RTU protocol (Optional)	- Dual display, Dual set point - TC / RTD input - Control output : Relay - Auxiliary output : Relay
DISPLAY	4 + 4 digits, 7 segment LED dual display		
INPUT TYPE	Thermocouple : J, K, T, R, S, C, E, B, N, L, U, W, Platinel II RTD : PT100	Thermocouple : J, K, T, R, S, C, E, B, N, L, U, W, Platinel II RTD : PT100 Signal inputs (DC) : -5 to 56 mV, 0 to 10 V DC, 0 to 20 mA DC	Thermocouple (J, K, T, R, S) / RTD (PT100)
RESOLUTION	TC / RTD : 1 / 0.1°	TC / RTD : 1 / 0.1°; Analog input : 1 / 0.1 / 0.01 / 0.001	0.1 / 1° for TC / RTD inputs (Fixed 1° for R & S type TC input)
ACCURACY	For TC input : 0.25% of F.S. $\pm 1^\circ$; For R & S inputs : 0.5% of F.S. $\pm 2^\circ$ (20 min of warm up time); For RTD input : 0.1% of F.S. $\pm 1^\circ$; Signal input : $\pm 0.5\%$, ± 1 digit (Except PID500-T)		
SET POINT	Maximum 3		
CONTROL MODE	Autotune PID or ON - OFF		
CONTROL OUTPUT	Relay : SPST : 5A @ 250V AC / 30V DC or SSR : 12V DC, 20mA or Current : 4 to 20 mA DC (Max load 500E) or Voltage : 0 to 10V DC (Min load 10K) (Depends on product code selection)		Relay : SPST : 5A resistive @ 250V AC / 30V DC
AUXILIARY OUTPUT	(Maximum 2) Relay or SSR (Mode : Set point or alarm mode) Relay : SPST : 5A @ 250V AC / 30V DC; SSR : 12V DC, 20mA		Relay : SPST : 5A resistive @ 250V AC / 30V DC
OPTIONAL FEATURES	---	Extra alarm output, Retransmission analog output, RS485 MODBUS RTU protocol	---
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC		

Universal PID



PID500-U
48(H) x 48(W) x 84(D)mm

FEATURES	- White + Green Dual Display - Capacitive Touch Keypad - Compact Size with Short Depth - Universal input, Universal output	- Adaptive Tune PID control - Profile controller up to 128 steps - RS485 MODBUS RTU protocol (Optional) - IDM applicable
DISPLAY	4 + 4 digits, 7 segment LED dual display	
INPUT TYPE	Thermocouple : J, K, T, R, S, C, E, B, N, L, U, W, Platinel II RTD : PT100; Signal inputs (DC) : -5 to 56 mV, 0 to 5/10 V DC, 0/4 to 20 mA DC	
RESOLUTION	TC / RTD : 1 / 0.1; Analog input : 1 / 0.1 / 0.01 / 0.001	
ACCURACY	For TC input : 0.25% of F.S. ± 10 ; For R & S inputs : 0.5% of F.S. $\pm 2^\circ$ (20 min of warm up time); For RTD input : 0.1% of F.S. ± 10 ; Signal input : $\pm 0.5\%$, ± 1 digit	
SET POINT	3 Set Point	
CONTROL MODE	Autotune PID or ON - OFF	
CONTROL OUTPUT	Relay : SPST : 5A @ 250V AC / 30V DC SSR : 12V DC, 20mA Current : 4 to 20 mA DC (Max load 500E); Voltage : 0 to 10V DC (Min load 10K)	
AUXILIARY OUTPUT	2 X Relay : SPST : 5A @ 250V AC / 30V DC	
OPTIONAL FEATURES	Extra alarm output, Retransmission analog output, RS485 MODBUS RTU protocol, IDM applicable	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC	

Independent Downloader Module



- Easy programming
- Compact size
- LED indication

RATED SUPPLY VOLTAGE	1.8V DC to 5.5V DC
UPLOADING TIME	1 Sec
DOWNLOADING TIME	1 Sec



CH403B
36(H) x 72(W) x 65.3(D)mm



CH403C
36(H) x 72(W) x 65.3(D)mm

FEATURES	• 2½ Digits single display • NTC input type • Restart time delay • Auto / Manual defrost selection • Door open mode • Cyclic timer (Optional)	• 3 Digits single display • Capacitive touch keypad • Defrost management • IDM applicable • Compact size
DISPLAY	2½ digits, 7 segment display	3 digits, 7 segment display
INPUT TYPE	NTC type sensor	
RESOLUTION	1 / 0.1°	
ACCURACY	±1% of F.S.	
SETPOINT	Single set point	
CONTROL MODE	ON - OFF	
CONTROL OUTPUT	SPDT: 10A @ 250V AC / 30V DC or SPST/ LUG Type : 20A @ 250V AC / 30V DC (Depends on product code selection)	SPDT: 10A @ 250V AC / 30V DC or SPST/ LUG Type : 20A @ 250V AC / 30V DC (Depends on product code selection)
AUXILIARY OUTPUT	SSR: 12V DC, 10mA or Relay: SPST: 5A @ 230V AC / 30V DC (Depends on product code selection)	---
HYSTERESIS	0.1 to 9.9°	
DISPLAY OFFSET	-19.9° to 19.9°	-19.9° to 20.0°
RESTART TIME DELAY	Adjustable from 0 to 19.9 min	Adjustable from 0 to 99 min
RELAY ACTION	Heat & Cool mode	
DEFROST TIME	Programmable from 0 to 99 min	
DEFROST FREQUENCY	Programmable from 0 to 99 (hr / min / sec)	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	230V AC	

Process Indicators



PIC152A-VI
48(H) x 96(W) x 76(D)mm



PIC101N
48(H) x 96(W) x 76(D)mm



PIC101A-T-230
48(H) x 96(W) x 76(D)mm



PIC101A-VI-230
48(H) x 96(W) x 76(D)mm

FEATURES	• User programmable universal input • Retransmission output • LED status indicator : Alarm ON • 2 Alarm indication • Inbuilt 24V DC sensor supply	• 4 digits, Single display • User programmable universal input • Scalable voltage / current input	• Simple temperature indicator • TC / RTD input type	• 4 Digits single display • User programmable voltage & current input
DISPLAY	4 digits, 7 segment LED single display			
INPUT TYPE	Thermocouple : J, K, T, R, S, RTD : PT100 Signal inputs (DC) : -5 to 56mV, 0 to 10V, 0/4 to 20mA		Thermocouple : J, K, T, R, S RTD : PT100	
RESOLUTION	TC / RTD : 1 / 0.1, Analog input : 1 / 0.1 / 0.01 / 0.001		1 / 0.1° (Fix 1° resolution for R & S type TC)	
ACCURACY	For TC inputs : 0.25% of F.S. ±1°; For R & S inputs : 0.5% of F.S. ±2° (20 min of warm up time); For RTD input : 0.1% of F.S. ±1°; Cold junction accuracy ± 5°C ; Signal input : ±0.5% of F.S. ± 1 digit		For TC inputs : 0.25% of F.S. ±1°; For R & S input : 0.5% of F.S. ±2° (20 min of warm up time); RTD input : 0.1% of F.S. ±1°	
OUTPUT	2 Alarms : SPDT : 5A @ 250V AC / 24V DC Alarm modes : High, Low, Band, Fail output & fault diagnosis. Hysteresis, Annunciator : Programmable, Reset action : Automatic or latched		---	
SPECIAL FEATURES	Retransmission output : 0 / 4 to 20mA DC, 0 to 5V DC, 0 to 5 / 10V DC, (Software selectable) RS485 MODBUS RTU protocol (Optional)		---	
SENSOR SUPPLY	24V DC, 30mA (Output to power the sensor)		---	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	90 to 270V AC / DC, 24V DC (Optional)		230V AC, ±20%	



RSS-TD1A125ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TD1A140ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TD1A225ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TD1A240ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TD1A225ZPL
58(H) x 45(W)
x 27.3(D)mm



RSS-TD1A240ZPL
58(H) x 45(W)
x 27.3(D)mm

FEATURES

- Resistive Output Load
- Compact Size
- Zero Cross Switching
- For Resistive + Slightly Inductive load

- Resistive + Inductive Output Load
- Compact Size
- Zero Cross Switching
- For Resistive + Inductive load

CONTROL INPUT VOLTAGE

4 to 32V DC

LOAD OUTPUT VOLTAGE

24 to 330V AC

48 to 480V AC

MAX LOAD CURRENT

25A

40A

25A

40A

25A

40A

CONTACT CONFIGURATION

1 NO

OUTPUT DEVICE

TRIAC

DC to AC - Solid State Relay

AC to AC - Solid State Relay



RSS-SD1A290ZPL
58(H) x 46.75(W)
x 41(D)mm



RSS-SD1A2125ZPL
58(H) x 46.75(W)
x 41(D)mm



RSS-TA1A125ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TA1A140ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TA1A225ZP
58(H) x 45(W)
x 27.3(D)mm



RSS-TA1A240ZP
58(H) x 45(W)
x 27.3(D)mm

FEATURES

- Resistive + Inductive Output Load
- Compact Size
- Zero Cross Switching
- For Resistive + Inductive load

- Resistive Output Load
- Compact Size
- Zero Cross Switching
- For Resistive + Slightly Inductive load

CONTROL INPUT VOLTAGE

4 to 32V DC

90 to 280V AC

LOAD OUTPUT VOLTAGE

48 to 480V AC

24 to 330V AC

48 to 480V AC

MAX LOAD CURRENT

90A

125A

25A

40A

25A

40A

CONTACT CONFIGURATION

1 NO

OUTPUT DEVICE

SCR's

TRIAC

Ordering information

Temperature Controllers

PRODUCT CODE	OUTPUT 1		OUTPUT 2	SUPPLY VOLTAGE	CERTIFICATION
	RELAY	SSR			
TC544C	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	CE
TC244CX	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC344CX	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC513CX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC203CX	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC303CX	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC538CX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC544B	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC544B-CE	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	CE
TC513BX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC513BX-CE	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	CE
TC533BX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC533BX-CE	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	CE
TC538BX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC544-CT	RELAY (10A)	---	RELAY (5A)	90 to 270V AC / DC	---

Temperature Controllers

PRODUCT CODE	OUTPUT 1		OUTPUT 2	SUPPLY VOLTAGE	CERTIFICATION
	RELAY	SSR			
TC544A	RELAY (10A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC544A-24V	RELAY (10A)	SSR (12V DC)	RELAY (5A)	24V DC	CE
TC544A-CU	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	CE
TC244AX	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC344AX	RELAY (5A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC513AX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC513AX-CU	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	CE
TC513AX-24V	RELAY (10A)	SSR (12V DC)	---	24V DC	CE
TC533AX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC233AX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC333AX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC203AX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC303AX	RELAY (10A)	SSR (12V DC)	---	90 to 270V AC / DC	---
TC303A	RELAY (10A)	---	---	90 to 270V AC / DC	---
IDM	---	---	---	---	---

PRODUCT CODE	OUTPUT 1	OUTPUT 2	OUTPUT 3	COMM. (RS485)	SUPPLY VOLTAGE	CERTIFICATION
PID500-T-0-0-01	RELAY (5A)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-T-1-0-01	SSR (12V DC)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-T-2-0-01	4-20mA	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-2-0-04	4-20mA	RELAY (5A)	RELAY (5A)	YES	90 to 270V AC / DC	---
PID500-2-0-04 V2-CE	4-20mA	RELAY (5A)	RELAY (5A)	YES	90 to 270V AC / DC	CE
PID500-3-0-00	0 - 10V	RELAY (5A)	---	---	90 to 270V AC / DC	---
PID500-3-0-00 V2-CE	0 - 10V	RELAY (5A)	---	---	90 to 270V AC / DC	CE
PID500-0-0-01 V2-CE	RELAY (5A)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	CE
PID500-0-0-01	RELAY (5A)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-0-0-04	RELAY (5A)	RELAY (5A)	RELAY (5A)	YES	90 to 270V AC / DC	---
PID500-0-0-04 V2-CE	RELAY (5A)	RELAY (5A)	RELAY (5A)	YES	90 to 270V AC / DC	CE
PID500-2-0-01	4-20mA	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-2-0-01 V2-CE	4-20mA	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	CE
PID500-1-0-01	SSR (12V DC)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-1-0-01 V2-CE	SSR (12V DC)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	CE
PID500-1-0-00	SSR (12V DC)	RELAY (5A)	---	---	90 to 270V AC / DC	---
PID500-1-0-00 V2-CE	SSR (12V DC)	RELAY (5A)	---	---	90 to 270V AC / DC	CE
PID330-2-0-04	4-20mA	RELAY (5A)	RELAY (5A)	YES	90 to 270V AC / DC	---
PID330-0-0-01	RELAY (5A)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID110-2-0-04	4-20mA	RELAY (5A)	RELAY (5A)	YES	90 to 270V AC / DC	---
PID110-0-0-01	RELAY (5A)	RELAY (5A)	RELAY (5A)	---	90 to 270V AC / DC	---
PID500-U-C-1	UNIVERSAL	UNIVERSAL	---	YES	90 to 270V AC / DC	CE
PID500-U-0-1	UNIVERSAL	UNIVERSAL	---	---	90 to 270V AC / DC	CE

PRODUCT CODE	OUTPUT 1		OUTPUT 2	SUPPLY VOLTAGE	CERTIFICATION
	RELAY	SSR			
DTC503	RELAY (10A)	---	---	90 to 270V AC / DC	---
DTC231	RELAY (10A)	---	---	90 to 270V AC / DC	---
DTC331	RELAY (10A)	---	---	90 to 270V AC / DC	---
PID528-1	RELAY (5A)	---	RELAY (5A)	90 to 270V AC / DC	---
PID528-1 V2-CE	RELAY (5A)	---	RELAY (5A)	90 to 270V AC / DC	CE
DTC204A-2	RELAY (10A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
DTC324A-2	RELAY (10A)	SSR (12V DC)	RELAY (5A)	90 to 270V AC / DC	---
TC52-400-J-230	RELAY (7A)	---	---	230V AC	---

Cooling Controllers


PRODUCT CODE	OUTPUT		SUPPLY VOLTAGE	CERTIFICATION
	CONTROL OUTPUT	ALARM OUTPUT		
CH403B-1-NTC	RELAY (10A)	---	90 to 270V AC / DC	---
CH403B-2-NTC	RELAY (20A LUG Type)	---	90 to 270V AC / DC	---
CH403B-3-NTC	RELAY (20A)	RELAY (5A)	90 to 270V AC / DC	---
CH403C-1-NTC	RELAY (10A)	---	90 to 270V AC / DC	CE
CH403C-1-NTC V2	RELAY (10A)	SSR (12V)	90 to 270V AC / DC	CE
CH403C-2-NTC	RELAY (20A LUG Type)	---	90 to 270V AC / DC	CE
CH403C-3-NTC	RELAY (10A)	RELAY (5A)	90 to 270V AC / DC	CE

Process Indicators

PRODUCT CODE	RETRANSMISSION	COMM. (RS485)	SUPPLY VOLTAGE	CERTIFICATION
PIC152A-VI	YES	---	90 to 270V AC / DC	---
PIC152A-VI-CE	YES	---	90 to 270V AC / DC	CE
PIC152A-VI-C-24V	YES	YES	24V DC	---
PIC101-N	---	---	90 to 270V AC / DC	CE
PIC101N-24V	---	---	24V DC	CE
PIC101N-CU	---	---	90 to 270V AC / DC	CE, RoHS
PIC101A-T-230	---	---	230V AC	---
PIC101A-VI-230	---	---	230V AC	---

Solid State Relay

Nomenclature



PRODUCT CODE	CURRENT RATINGS	CONTROL INPUT VOLTAGE	LOAD OUTPUT VOLTAGE	CERTIFICATION
RSS-TD1A125ZP	25	4 to 32V DC	24 to 330V AC	CE
RSS-TD1A140ZP	40	4 to 32V DC	24 to 330V AC	CE
RSS-TD1A225ZP	25	4 to 32V DC	48 to 480V AC	CE
RSS-TD1A240ZP	40	4 to 32V DC	48 to 480V AC	CE
RSS-TA1A125ZP	25	90 to 280V AC	24 to 330V AC	CE
RSS-TA1A140ZP	40	90 to 280V AC	24 to 330V AC	CE
RSS-TA1A225ZP	25	90 to 280V AC	48 to 480V AC	CE
RSS-TA1A240ZP	40	90 to 280V AC	48 to 480V AC	CE
RSS-TD1A225ZPL	25	4 to 32V DC	48 to 480V AC	CE
RSS-TD1A240ZPL	40	4 to 32V DC	48 to 480V AC	CE
RSS-SD1A290ZPL	90	4 to 32V DC	48 to 480V AC	CE
RSS-SD1A2125ZPL	125	4 to 32V DC	48 to 480V AC	CE




2M
90(H) x 35(W) x 60(D)mm



4M
90(H) x 70(W) x 66.4(D)mm



6M
90(H) x 105(W) x 66.4(D)mm

FEATURES	- Modular PLC with pluggable display - RTC with time switch functions (Optional) - Flexible IO card selection		- Modular PLC with pluggable display - Flexible IO card selection - Expandable - RTC with time switch functions		- Modular PLC with pluggable display - Flexible IO card selection - Expandable - RTC with time switch functions	
DISPLAY TYPE	7 Segment LED		LCD with green backlight & black font		LCD with green backlight & black font	
DIGITS	4 Red	1 Red	2 lines x 8 characters (Font size 5x7mm)		1 Red	2 lines x 8 characters (Font size 5x7mm)
LED BANKS	6 Red LED		---		6 Red LED	---
NO. OF KEYS	3 Keys (2 User configurable)		5 keys (4 User configurable)		1 key	6 keys (5 User configurable)
NO. OF SLOTS	2		4		6	
SUPPLY VOLTAGE	18 to 30V AC	12 to 30V DC	100 to 270V AC		12 to 30V DC	100 to 270V AC 12 to 30V DC
DIGITAL INPUTS	3		4 + 1*		10 + 1*	
INPUT TYPE & RANGE			PNP (5-30V)			
FAST INPUT			1			
MAXIMUM COUNTING FREQUENCY			5kHz (PNP)			
ANALOG INPUT	As per Slot I/O card				1 (Voltage 0-10V)	
RESOLUTION	As per Slot I/O card				12 BIT	
DIGITAL OUTPUT			As per Slot I/O card		4 Relay	
TYPE AND RATING			As per Slot I/O card		5A NO Type@ 250VAC/30VDC	
COMMUNICATION INTERFACE	RS485 Modbus RTU Protocol (Slave)				RS485 Modbus RTU Protocol (Master - Slave)	
PROGRAM MEMORY	112 Kb				240 Kb	
RTC	Optional				Yes	
PLUGGABLE DISPLAY MODULES	 MiBRX-DSP-2M-7-1-04-A		 MiBRX-DSP-2M-0-1-06-A		 MiBRX-DSP-4M-8-2-08-A	
					 MiBRX-DSP-4M-0-1-06-A	
					 MiBRX-DSP-6M-8-2-08-A	

*Digital input can be configured as analog input (0-10V)



48 x 96
48(H) x 96(W) x 69(D)mm



72 x 72
72(H) x 72(W) x 71.35(D)mm



96 x 96
96(H) x 96(W) x 99.1(D)mm

FEATURES	- Modular PLC with pluggable display - RTC with time switch functions (Optional) - Flexible IO card selection		- Modular PLC with pluggable display - Flexible IO card selection - RTC with time switch functions		- Modular PLC with pluggable display - Flexible card selections - Expandable - RTC with time switch functions	
DISPLAY TYPE	7 Segment LED		LCD with blue backlight & black font	7 Segment LED-White+Green	LCD with Green backlight	LCD with White backlight
DIGITS	(3 + 4) Red + 4 Green	(4 + 4) Red + 6 Green	2 lines x 8 characters (Font size 5x7mm)	6 White + 4 Green	4 lines x 16 characters (Font side 5x7mm)	Customized segments
LED BANKS	LED banks 6 Red round LEDs + 10 Red LEDs (Bar graph)	4 Red + 4 Green LED	---	4 Red	---	
NO. OF KEYS	5 Touch keys (4 User configurable)		4 Touch keys (3 User configurable)		8 Touch keys (7 User configurable)	5 Touch keys (4 User configurable)
NO. OF SLOTS	2		2		6	
SUPPLY VOLTAGE	100 to 270V AC	12 to 30V DC	100 to 270V AC	12 to 30V DC	100 to 270V AC	12 to 30V DC
DIGITAL INPUTS	5 + 1*	5 + 2*	3 + 1*		3 + 1*	5 + 1*
INPUT TYPE & RANGE	PNP (5-30V)					
FAST INPUT	1					
MAXIMUM FREQUENCY	5kHz (PNP)					
ANALOG INPUT	1 (Voltage 0-10V)	3 (2 Voltage & 1 current 0-10V & 0-20mA)	1 (Voltage 0-10V)	2 (Voltage & Current 0-10V & 0-20mA)	1 (Voltage 0-10V)	2 (1 Voltage & 1 Current 0-10V & 0-20mA)
RESOLUTION	12 BIT					
DIGITAL OUTPUT	As per Slot I/O card		3 Relay	4 Relay	As per Slot I/O card	
TYPE AND RATING	As per Slot I/O card		5A NO Type@ 250VAC/30VDC		As per Slot I/O card	
COMMUNICATION INTERFACE	RS485 Modbus RTU Protocol (Slave)				RS485 Modbus RTU Protocol (Master - Slave)	
PROGRAM MEMORY	240 Kb					
RTC	Optional		Yes			
SENSOR SOURCE	24V, 50mA (230VAC Variant)					
PLUGGABLE DISPLAY MODULES	 MiBRX-DSP-48-7-2-11-A	 MiBRX-DSP-48-7-2-14-B	 MiBRX-DSP-72-8-2-08-B	 MiBRX-DSP-72-7-2-10-B	 MiBRX-DSP-96-8-4-16-B	

*Digital input can be configured as analog input (0-10V)

MiBRX Series - Independent Display



MiBRX-DSP-IND-96-8-0-00-B
96(H) x 96(W) x 40(D)mm



MiBRX-DSP-IND-96-8-4-16-B
96(H) x 96(W) x 40(D)mm



MiBRX-DSP-IND-96-8-2-16-B
96(H) x 96(W) x 40(D)mm

FEATURES	● 3.5" segment LCD ● White back light ● Positive Mode ● Black segments	● 16 columns and 2 rows ● Positive mode ● 32 characters ● Yellow green backlight ● Black character	● 16 columns and 4 rows ● Positive mode ● 64 characters ● Yellow green backlight ● Black character
DISPLAY TYPE	3.5" segment LCD with backlight	16 columns and 2 rows LCD	16 columns and 4 rows LCD
DISPLAY MODE	Positive, Transmissive, STN		
KEYS	Yes (5 nos)	Yes (8 nos)	Yes (8 nos)
KEYS TYPE	Capacitive Touch Pad type with integrated yellow green LEDs		
SUPPLY VOLTAGE	24 V DC (non-isolated)		

Independent display can be used only with MiBRX rail mount series with respective adapter plate & ACH004 (6Pin cable)

Digital I/O specifications

Digital input

	Input voltage range	Response time	Debounce time
MiBRX-SC-DI04 MiBRX-SC-DI06	5-30V	Depends on debounce time & ladder execution time	10ms

Fast input

	Input type	Input frequency
MiBRX-SC-FI02	PNP / NPN (Jumper selectable)	10kHz

Digital output

	Contact rating	Response time	Contact-Isolation
MiBRX-SC-RO04 MiBRX-SC-RO03 MiBRX-SC-RO05	5A 250VAC/30VDC	10ms	Yes

	Rated voltage	Output current	Response time	Isolation between outputs
MiBRX-SC-TO04	18V to 30V DC (External)	100mA	10ms	4kV

Fast output

	Output type	Output frequency
MiBRX-SC-FO01-TO01	PNP / NPN (Terminal selectable)	10kHz

Analog I/O specifications

Analog inputs

	Analog type	Resolution	Conversion time	Accuracy
MiBRX-SC-AI02-I	CURRENT (0-20mA)	12BIT	100ms	0.25%
MiBRX-SC-AI02-V	VOLTAGE (0-10V)	12BIT	100ms	0.25%
MiBRX-SC-AI02-NTC	NTC	12BIT	100ms	0.25%
MiBRX-SC-AI02-PTC	PTC	12BIT	100ms	0.25%
MiBRX-SC-AI02-TC	J, K, T, R, S, C, E, B, N, L, U, W, PLTNL, mVolt (-5 to 65mV), RTD (PT100)	12BIT	100ms	0.25%
MiBRX-SC-AI02-PT1000	RTD (PT1000)	12BIT	100ms	0.25%
MiBRX-SC-LC02	Loadcell	24BIT	50ms to 400ms	---

Analog output

	Output type	Resolution	Digital resolution	Conversion time
MiBRX-SC-AO01-V/I	VOLTAGE (0-10V) / CURRENT (0-20mA)	12BIT	0.0 to 100.0% = 0 to 10V / 0.0 to 100.0% = 0 to 20mA	100ms

Mixed - Digital Input & Output


	Input voltage range	Response time	Debounce time	Contact rating	Response time	Contact-Isolation
MiBRX-SC-DI02-RO02 MiBRX-SC-DI02-TO02	5-30V	Depends on debounce time & ladder execution time	10ms	5A 250VAC/30VDC	10ms	Yes

Mixed - Digital & Analog Input

	Rated voltage	Output current	Response time	Isolation between outputs	Analog type	Resolution	Conversion time	Accuracy
MiBRX-SC-DI02-AI01-T	18V to 30V DC (External)	100mA	10ms	4kV	J, K, T, R, S, C, E, B, N, L, U, W, PLTNL, mVolt (-5 to 65mV), RTD (PT100)	12BIT	100ms	0.25%



FLEXYS GT35
99(H) x 99(W) x 110(D)mm



FLEXYS PANEL TX4
99(H) x 99(W) x 110(D)mm



FLEXYS RAIL
67(H) x 140(W) x 107(D)mm



EXP FLEX 2M **EXP FLEX 2M V3**
94(H) x 35(W) x 103(D)mm

FEATURES	3.5" LCD with touch screen - Flexible I/O card selection - Real time clock - Expandable	- PLC with built in HMI - Flexible I/O card selection - Real time clock - Expandable	- PLC with flexible I/O card selection - Real time clock - Expandable	- Any flexys card can be configured - Selectable baudrate and slave ID
DISPLAY	TFT 3.5" diagonal touch screen, Resolution 320x240	LCD with backlight, 4x16 character display, Font size 5x7mm	7 segment display for slot number & card status. Multipurpose LED bank	LED indication for power ON & communication status
NO. OF KEYS	5 function keys +1 system key	18 keys (14 user configurable)	One key to scroll through different slots	---
I/Os	3 I/O slots (Please refer I/O card for flexys series)	4 I/O slots (Please refer I/O card for flexys series)	---	---
DIGITAL INPUTS	4 / 10 / 14 per card, PNP (6 - 30V DC)			
MAXIMUM COUNTING FREQUENCY	FC0 (I0 & I1) & FC1 (I2 & I3) - 5KHz (on power supply card only), Normal digital inputs - 30KHz			---
ANALOG INPUTS	3 / 4 / 6 Channels per card (TC, RTD, 0-10V, 0 - 20mA, NTC)			
RESOLUTION	12 Bits			
RELAY OUTPUTS	4 / 8 per card, NO type 5A @ 230V AC / 30V DC (Resistive)			
TRANSISTOR OUTPUTS	8 per card, Source type 100mA @ 24V DC			
ANALOG OUTPUTS	2 / 4 Channels per card (0 - 10V, 0 - 20mA)			
RESOLUTION	14 Bits (0.0 to 100.0% = 0 to 10.000V, 0.0 to 100.0% = 0 to 20.000mA)			
PROGRAM MEMORY	221KB	351KB	---	---
EXPANSION	Yes			
COMMUNICATION INTERFACE	RS485 MODBUS RTU protocol	RS485 MODBUS RTU, Proprietary protocol	RS485 MODBUS RTU, Proprietary protocol (Selec master PLC)	RS485 MODBUS RTU (Third party master PLC)
RTC	Yes			---
BAUDRATE	---			19200 / 115200 bps (Selectable)
RESPONSE TIME	---			100msec to 2sec + IO card Response
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	18 - 30V DC, 100 - 240V AC			18 - 30V DC

Compact Series - UNIX & TWIX



UNIX-1
75.5(H) x 75.5(W) x 91(D)mm



TWIX-1
50(H) x 98(W) x 78(D)mm

TWIX-2
50(H) x 98(W) x 78(D)mm

TWIX-3
50(H) x 98(W) x 78(D)mm

FEATURES	• Compact PLC with built in HMI • RS485 MODBUS RTU protocol	• Compact PLC with built in HMI • Configurable LED display • RS485 MODBUS RTU protocol		
DISPLAY	6 digits red & 4 green digits 7 segment LED	4 + 4 digits red & 6 green digits 7 segment LED		
NO. OF KEYS	3 keys (2 - User configurable)	5 keys (4 - User configurable)		
DIGITAL INPUTS	3 + 1*	6	6 + 2*	8
INPUT TYPE	PNP (5 - 30V DC)	PNP (6 - 30V DC)		
MAXIMUM COUNTING FREQUENCY	FC0 (I0 & I1) - 5KHz, Normal digital input: 30Hz			
ANALOG INPUTS	3 Channels, 1 (TC / RTD) , 1 (0-10V), 1(0-20mA)	1 Channel (TC / RTD)	6 Channels, 2 (TC / RTD) , 2 (0-10V), 2(0-20mA)	1 Channel (TC / RTD)
ANALOG OUTPUTS	---		1 Channel (0-10V/0-20mA)	---
RESOLUTION	12 Bits			
DIGITAL OUTPUTS	2 Relay, 2 Transistor	4 Relay	5 Relay	6 Transistor
TYPE & RATING	For Relay O/P : 5A NO type @230V AC / 30V DC (Resistive), For Transistor O/P : Source type 100mA@24V DC			
PROGRAM MEMORY	240KB	112KB	240KB	112KB
COMMUNICATION INTERFACE	RS485 MODBUS RTU Protocol			
SUPPLY VOLTAGE (AC : 50 / 60Hz)	90 - 270V AC	90- 270V AC, 18-28 V DC		18 - 30V DC



DIGIX-1
94(H) x 70(W) x 67(D)mm



DIGIX-1-B
90(H) x 70(W) x 67(D)mm



DIGIX-2
90(H) x 70(W) x 67(D)mm



DIGIX-4
90(H) x 70(W) x 67(D)mm

FEATURES	• Compact PLC with built in HMI • 2 Line 8 character LCD • Real time clock** • RS485 MODBUS RTU protocol		• LED indications for input & output • RS485 MODBUS RTU protocol		• Compact PLC with built in HMI • 2 Line 8 character LCD • Real time clock** • RS485 MODBUS RTU protocol	
DISPLAY	2 X 8 Character LCD		LED indication for input, Output & communication status		2 X 8 Character LCD	
NO. OF KEYS	5 keys (4 - User configurable)		---		5 keys (4 - User configurable)	
DIGITAL INPUTS	8		10 + 2*		10	
INPUT TYPE	PNP (6 - 30V DC)					
MAXIMUM COUNTING FREQUENCY	FC0 (I0 & I1) - 5KHz, Normal digital input: 30Hz					
ANALOG INPUTS	---	Through expansion	---	2 Channels (0-10V)		Through expansion
RESOLUTION				12 Bits		
DIGITAL OUTPUTS	5 Relay			8 Relay		6 Transistor
TYPE & RATING	5A NO type @230V AC / 30V DC (Resistive)					100 mA each @24V DC
ANALOG OUTPUTS	---	Through expansion	---	Through expansion		
RESOLUTION		As per expansion modules		As per expansion modules		
RTC	NO	YES	NO	NO		YES
EXPANSION	NO	YES	NO	YES		YES
PROGRAM MEMORY	112KB			240KB		
COMMUNICATION INTERFACE	RS485 Modbus RTU Protocol					
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	18 - 30V DC**, 100 - 270V AC/DC	100 - 270V AC	18 - 30V DC			

*Voltage Analog Inputs can be configured as Digital Inputs **Please refer Datasheet for exact Order code

PLC - Fixed IO Configuration



MM3030-4
110(H) x 99(W) x 62(D)mm



MM3032-2-0-0-230V V2
110(H) x 99(W) x 62(D)mm

FEATURES	• Low cost • Panel / DIN rail mounting • Fast inputs / outputs • Windows based user friendly software for ladder programming and HMI configuration	• Compact PLC with built-in HMI • Panel / DIN rail mounting • Windows based user friendly software for ladder programming and HMI configuration	
DISPLAY	4x16 Character LCD	2x16 Character LCD	
NO. OF KEYS	15 keys (12 User configurable)	8 keys (6 User configurable)	
DIGITAL INPUTS	10 PNP (11 - 30V DC)	8 PNP (6 - 30V DC)	
COUNTING FREQUENCY	FC0 (I0 & I1) – 12KHz, FC1 (I2 & I3) & FC2 (I4 & I5) – 7.5KHz Normal input – 30Hz.	FC0 (I0 & I1) – 5KHz, Normal input – 30Hz.	
ANALOG INPUTS	2 Channel (0 - 10V or 0 to 20mA) selectable via jumpers	2 Channels (0 - 20mA) / (0-10V)	2 Channels (0 - 20mA / (0-10V) + 1 NTC Channel
RESOLUTION	10 Bits	12 Bits	
DIGITAL OUTPUTS	8 Transistor	6 Relay	
TYPE AND RATING	O0-O1 Sink 50mA @ 24V DC (Fast Outputs 50KHz), O2-O7- Source 100mA @ 24V DC	5A NO type @ 230V AC / 30V DC (Resistive)	
ANALOG OUTPUTS	Through expansion	1 Channel, (0 - 10V)	
RESOLUTION	As per expansion modules	14 Bits (0.0% to 100.0% = 0 – 10.000V)	
RTC	YES	NO	
EXPANSION	YES	NO	
PROGRAM MEMORY	351KB	240KB	
COMMUNICATION INTERFACE SLAVE	RS485 MODBUS RTU protocol		
COMMUNICATION INTERFACE MASTER	RS485 MODBUS RTU protocol	---	
SUPPLY VOLTAGE (AC : 50 / 60 Hz)	18 - 30V DC	100-270V AC without retention 180-270V AC with retention	18 – 30V DC



SP3-GT35
98(H) x 98(W) x 54(D)mm



SP112-GT40
102(H) x 138(W) x 32(D)mm



SP112-GT70
146(H) x 200(W) x 32(D)mm



SP112-GT100
193(H) x 273(W) x 32(D)mm

FEATURES	• 10 Password levels • Serial printing • Data logging • Built in buzzer • Recipe management	• 4.3", 7" & 10" Touch screen • Ethernet / Serial communication • User management • Recipe management	• Data logging functionality • Update program by USB flash • In-Built third party PLC protocols • In-Built symbol library • In-Built buzzer for alarm condition	
DISPLAY	3.5" Diagonal resistive touch screen	4.3" Diagonal resistive touch screen	7" Diagonal resistive touch screen	10" Diagonal resistive touch screen
RESOLUTION	320 x 240 pixels	480 x 272 pixels	800 x 480 pixels	1024 x 600 pixels
USER MEMORY	16 MB	256MB Flash + 256MB DRAM	256M Flash+256M DRAM	256M Flash+128M DRAM
DATA LOGGING	2 GB (External SD card)	Yes		
COMM. PORT 1	Master port - RS485 MODBUS RTU protocol	RS485 / RS422 MODBUS RTU protocol		
COMM. PORT 2	Slave port - RS232 MODBUS RTU protocol	RS232 MODBUS RTU protocol, Multiple communication protocols		
COMM. PORT 3	Serial printer ESC / PAUSE protocol	RS485 MODBUS RTU protocol		
ETHERNET	---	Ethernet - 10M / 100M Self adaptation		
USB HOST	---	USB2.0 x 1, Support USB flash disk to update firmware, Configure and store data		
USB SLAVE	---	Type C, Support power supply & program download / upload	Type B, program download / upload	
KEYS	5 Function keys + 1 System key	---		
RTC	Yes	Yes		
BACKUP BATTERY	3V CR2032	3V CR2032		
OPERATING TEMPERATURE	0° - 55° C	0° - 50° C		
SUPPLY VOLTAGE	18 - 30V DC	24V DC (20.4~28.8V DC)		

Annunciator



AN-8-0-0-230V
147(H) x 76(W) x 63(D)mm

FEATURES	8 Programmable windows 6 Colour selection - RS485 MODBUS RTU protocol
DISPLAY	Multicolour LED's - Fault annunciation
NO. OF KEYS	4
DIGITAL INPUTS	13
OPERATING RANGE	5 - 30V DC
INPUT CURRENT	3mA @ 12V
DIGITAL OUTPUTS	2
OUTPUTS TYPE	NO contact type - Relay
OUTPUT CURRENT	7A @ 30VDC (Resistive), 7A @ 250VAC (Resistive)
COMMUNICATION PROTOCOL	RS485 MODBUS RTU protocol
MOUNTING	Panel mount
SUPPLY VOLTAGE	90 - 270V AC
SENSOR SUPPLY	12V, 50mA (for looping)



RP-2M-1.1A-24VDC
90(H) X 35(W) x 60(D)mm



RPS60
109.8(H) X 43(W) x 102.7(D)mm



RPS120
109.8(H) X 43(W) x 102.7(D)mm



RPS240
136(H) X 50(W) x 135(D)mm



RPS480
154(H) X 60(W) x 158(D)mm

FEATURES	• IEC 61010-1 safety standards • Protection: Overload / Over voltage • Power OK indication • Cooling by free air convection		• Designed to meet UL 62368-1 • IEC 61010-1 safety standard • Protection : Overload, Over voltage, Output Short Circuit, Over Temperature • Power OK Indication • Cooling by free air convection		• Designed to meet UL 62368-1 • Active PFC • Protection : Overload, Over voltage, Output Short Circuit, Over Temperature • Power OK indication • DC OK relay contact • Cooling by free air convection	
	LED indication for DC OK					
VOLTAGE RANGE	100 - 270 VAC, 100 - 300 VDC		90 - 264 VAC / 127 - 370 VDC			
FREQUENCY RANGE	50 / 60 Hz					
AC CURRENT	100 V - 0.6 A, 270 V - 0.3 A	115 V - 1.2 A, 230 V - 0.8 A	115 V - 2.2 A, 230 V - 1.5 A	115 V - 2.4 A, 230 V - 1.2 A	115 V - 4.8 A, 230 V - 2.4 A	
EFFICIENCY	Up to 75 % to 85 %	Up to 87 %	Up to 89 %	Up to 93 %	Up to 94 %	
INRUSH CURRENT	30 A	< 48 A @ 264 VAC			< 60 A @ 264 VAC	
AVAILABLE RANGE DC VOLTAGE/CURRENT	24 V / 1.1 A	05 V / 10 A, 12 V / 5 A, 15 V / 4 A, 24 V / 2.5 A, 48 V / 1.25 A	12 V / 8 A, 15 V / 8 A, 24 V / 5 A, 48 V / 2.5 A	12 V / 18 A, 24 V / 10 A, 48 V / 5 A	24 V / 20 A, 48 V / 10 A	
RATED POWER	26.4 W	60 W	120 W	240 W	480 W	
RIPPLE & NOISE MAX (mVp.p)	200 mV	< 1% of Vout				
WEIGHT	140 g	285 g	350 g	645 g	1050 g	

Power Supply - Open Frame Series



OPS2x3-40
76.2(L) X 50.8(W) x 30(H)mm



OPS2x4-60
101.6(L) X 50.8(W) x 30(H)mm

FEATURES	• 3 x 2 x 1.16 Inches Form factor • 40 Watts convection	• 4 x 2 x 1.16 Inches Form factor • 60 Watts Convection
	• No Load power < 0.5 W • - 40°C to + 70°C Operating temperature • Designed to meet IEC/ UL 62368-1 and IEC/ EN 60601-1 • Class II option available • Medical (BF) safety approvals • Approved to household, ITAV & medical standards	
Voltage range	90 - 264 VAC (127 - 370 VDC)	
Available Range (Convection) DC Voltage/Current	5 V / 5 A, 12 V / 3.33 A, 15 V / 2.67 A, 24 V / 1.67 A, 48 V / 0.83 A	5 V / 10 A, 12 V / 5 A, 15 V / 4 A, 24 V / 2.5 A, 48 V / 1.25 A
FREQUENCY RANGE	50 / 60 Hz	
AC CURRENT	0.85 A @ 115 VAC; 0.45 A @ 230 VAC	1.2 A @ 115 VAC; 0.8 A @ 230 VAC
EFFICIENCY @230V	Up to 86 %	Up to 87 %
INRUSH CURRENT	< 60 Amps; Measured at 264 VAC, 25°C Ambient, Cold start	
RATED POWER	40 W	60 W
RIPPLE & NOISE (max)	< 1 % of Vout	
DIMENSION	Overall: 3" x 2" x 1.16" (L x W x H); Height above PCB : 1"	Overall: 4" x 2" x 1.16" (L x W x H); Height above PCB : 1"
WEIGHT	< 100 g	< 150 g



OPS2x4-150
101.6(L) X 50.8(W) x 30(H)mm



OPS2x4-200
101.6(L) X 50.8(W) x 30(H)mm



OPS3x5-350
127(L) X 76.2(W) x 30(H)mm

FEATURES	• 4 x 2 x 1.16 Inches Form factor • 150 Watts with Forced Air Cooling & 100 Watts Convection cooling	• 4 x 2 x 1.16 Inches Form factor • 200 Watts with Forced Air Cooling & 130 Watts Convection Cooling	• 5 x 3 x 1.16 Inches Form factor • 350 Watts with Forced Air Cooling & 200 Watts Convection Cooling • Remote Inhibit available
	• 12 V / 0.5 A Fan Output, Thermal Shut-Down feature • No Load power < 0.5 W • - 40°C to + 70°C Operating temperature • Designed to meet IEC/ UL 62368-1 and IEC/ EN 60601-1 • Class II option available • Medical (BF) safety approvals • Approved to household, ITAV & medical standards		
Voltage range	90 - 264 VAC (127 - 370 VDC)		
Available Range (Convection) DC Voltage/Current	12 V / 8.33 A, 15 V / 6.67 A, 24 V / 4.17 A, 48 V / 2.1 A	12 V / 10.84 A, 15 V / 8.67A, 24 V / 5.42 A, 48 V / 2.71 A	12 V / 16.67 A, 15 V / 13.33 A, 24 V / 8.33 A, 48 V / 4.17 A
Available Range (Forced Air) DC Voltage/Current	12 V / 12.5 A, 15 V / 10 A, 24 V / 6.25 A, 48 V / 3.13 A	12 V / 16.67 A, 15 V / 13.34 A, 24 V / 8.34 A, 48 V / 4.17 A	12 V / 25.00 A, 15 V / 23.34 A, 24 V / 14.59 A, 48 V / 7.30 A
FREQUENCY RANGE	50 / 60 Hz		
AC CURRENT	1.5 A @ 115 VAC; 0.74 A @ 230 VAC	2.0 A @ 115 VAC; 1.1 A @ 230 VAC	3.6 A @ 115 VAC; 1.8 A @ 230 VAC
EFFICIENCY @230V	Up to 90 %	Up to 93 %	
INRUSH CURRENT	< 60 Amps; Measured at 264 VAC, 25°C Ambient, Cold start		
RATED POWER	150 W	200 W	350 W
RIPPLE & NOISE (max)	<1% of Vout		
DIMENSION	Overall: 4" x 2" x 1.16" (L x W x H); Height above PCB : 1"	Overall: 4" x 2" x 1.16" (L x W x H); Height above PCB : 1"	Overall: 5" x 3" x 1.16" (L x W x H); Height above PCB : 1"
WEIGHT	< 200 g	< 180 g	< 300 g

Power Supply - Wall Mount Series

Battery Chargers



PPS240-24
190(H) X 80(W) x 139.6(D)mm



BC1-1210
190(H) X 60(W) x 140.75(D)mm



BC2-2410
190(H) X 80(W) x 140.75(D)mm

FEATURES	- Wall Mount SMPS - DC OK Indication		
	- CVCC Charging profile - Charging indication with LED - Prevents over charging of battery - Full power between 0°C & + 50°C - Wide-range input 150 - 270 VAC		
DISPLAY	LED induction for DC OK		
VOLTAGE RANGE	150 - 270 VAC		
FREQUENCY RANGE	50 / 60 Hz		
AC CURRENT	2.8 A @ 150 VAC; 2.1 A @ 230 VAC	150 V - 2.4 A, 230 V - 1.7 A	150 V - 4.1 A, 230 V - 3.1 A
EFFICIENCY	Up to 85 %	Up to 80 % @ 230 VAC	Up to 85 % @ 230 VAC
INRUSH CURRENT	< 60 Amps; Measured at 270 VAC	< 70 A @ 270 VAC	< 80 A @ 270 VAC
DC VOLTAGE	24 VDC	12 VDC	24 VDC
RATED CURRENT	10 A		
RATED POWER	240 W	120 W	240 W
RIPPLE & NOISE MAX (mVp.p)	< 1 % of Vout		
WEIGHT	1150 g	1050 g	1280 g



RLYMD-1-S4-1CO-24VDC
87(H) x 69(W) x 69(D)mm



RLYMD-2-S8-1CO-24VDC
87(H) x 138(W) x 138(D)mm



RLYMD-1-S4-2CO-24VDC
87(H) x 69(W) x 69(D)mm



RLYMD-2-S8-2CO-24VDC
87(H) x 138(W) x 138(D)mm



ERLYMD-2-1-S8-1CO-24V
87(H) x 138(W) x 138(D)mm

FEATURES	• LED and freewheeling diode across coils • Reverse polarity protection • Jumpers for coil looping • Pluggable relays				• RS485 Comm. over MODBUS-RTU • Selectable baudrate and slave ID • Pluggable relays
NO. OF CHANNELS	4	8	4	8	8
CONTACTS	1 C / O		2 C / O		1 C / O
CONTACT RATING	10A @ 277V AC / 30V DC (Resistive)				
NOMINAL VOLTAGE	24V DC				
MUST VOLTAGE	18V DC				
MAX VOLTAGE	33V DC				
OPERATE TIME	15 msec				
RESET TIME	5 msec				
COMMUNICATION PROTOCOL	---				RS485 MODBUS RTU protocol
STATUS DISPLAY	LED indication for relay ON status				LED indication for relay ON status, Power ON & communication status
SUPPLY VOLTAGE	---				24V DC

Accessories - Data Converters



AC-RS485-RS232-ISO



AC-USB-RS232-01



AC-USB-RS485-02



AC-USB-RS485-03



AC-S2E-02



AC-S2W-01

FEATURES	- LED indication for communication status - Interface converter	- Port powered - Communication status available on LED Indication	- Web configuration telnet protocol - TCP / IP protocol	- Web based configuration utility - MQTT protocol
DISPLAY	LED indication for power on, Tx & Rx	LED indication for Tx & Rx		LED indication for power ON, Tx, Rx, & Reset switch
INTERFACE 1	Serial (RS485 MODBUS RTU protocol)	USB 2.0 compliance		Serial (RS485 MODBUS RTU protocol)
CONNECTOR	2 wire	USB type A		2 wire (Data+, Data-)
INTERFACE 2	Serial (RS232 MODBUS RTU protocol)	Serial (RS485 MODBUS RTU protocol)		Ethernet (TCP / IP, Telnet)
CONNECTOR	DB9	2 wire open RJ 25 (6 Pin)		Wireless
TRANSMISSION SPEED	2400 to 115200 bps	2400 to 115200 bps		RS485 : 300 to 115000 bps Ethernet : 10 / 100 Mbps
CABLE LENGTH	---	1 meter		---
POWER CONSUMPTION	0.5 W	75mA @ 5V		0.5 W
SUPPLY VOLTAGE	90 - 270V AC	Port powered		12 - 30V DC

Accessories - Communication Adapters & Cables



AC-IOEXP-01



AC-IOEXP-03



ACH-002



ACH-003



ACH-004

DESCRIPTION	Expansion adapter for MM303X PLCs	Adapter for directing RJ25 to open terminal and also for network looping	DB9 to RJ25 cable	Both Side RJ45 type connector	Both Side RJ25 Type Connector
-------------	-----------------------------------	--	-------------------	-------------------------------	-------------------------------

MiBRX Series - Rail Mount

PRODUCT CODE	DESCRIPTION	CERTIFICATION
MiBRX-2M-1-0-0-24VDC	MiBRX 2M PS - 2 Slots, 3DI (incl 1FI)	CE
MiBRX-4M-1-0-0-230V	MiBRX 4M PS - 4 Slots, 5DI (incl 1FI, 1AI-V), NTC	CE
MiBRX-4M-1-1-1-230V	MiBRX 4M PS - 4 Slots, 5DI (incl 1FI, 1AI-V), NTC, RTC, Master	CE
MiBRX-4M-1-0-0-24VDC	MiBRX 4M PS - 4 Slots, 5DI (incl 1FI, 1AI-V), NTC	CE
MiBRX-4M-1-1-1-24VDC	MiBRX 4M PS - 4 Slots, 5DI (incl 1FI, 1AI-V), NTC, RTC, Master	CE
MiBRX-6M-1-1-1-230V	MiBRX 6M PS - 6 Slots, 11DI, (incl 1FI, 1AI-V) + 4RO, NTC, RTC, Master	CE

MiBRX Series - Panel Mount

PRODUCT CODE	DESCRIPTION	CERTIFICATION
MiBRX-48-0-0-230V	MiBRX 48x96 PS - 2 slots, 6DI (incl 1FI, 1AI-V), NTC	CE
MiBRX-48-0-0-24VDC	MiBRX 48x96 PS - 2 slots, 7DI (incl 1FI, 2AI-V), 1AI-I, NTC	CE
MiBRX-72-0-0-230V	MiBRX 72x72 PS - 2 slots, 4DI (incl 1FI, 1AI-V) + 3RO, NTC	CE
MiBRX-72-0-0-24VDC	MiBRX 72x72 PS - 2 slots, 4DI (incl 1FI, 1AI-V) + 4RO, 1AI-I, NTC	CE
MiBRX-72-0-1-230V	MiBRX 72x72 PS - 2 slots, 4DI (incl 1FI, 1AI-V) + 3RO, NTC, RTC	CE
MiBRX-72-0-1-24VDC	MiBRX 72x72 PS - 2 slots, 4DI (incl 1FI, 1AI-V) + 4RO, 1AI-I, NTC, RTC	CE
MiBRX-96-1-0-24VDC	MiBRX 96x96 PS - 6 slots, 6DI (incl 1FI, 1AI-V), 1AI-I, NTC, Master	CE
MiBRX-96-1-1-24VDC	MiBRX 96x96 PS - 6 slots, 6DI (incl 1FI, 1AI-V), 1AI-I, NTC, RTC, Master	CE
MiBRX-96-1-0-230V	MiBRX 96x96 PS - 6 slots, 4DI (incl 1FI, 1AI-V), NTC, Master	CE
MiBRX-96-1-1-230V	MiBRX 96x96 PS - 6 slots, 4DI (incl 1FI, 1AI-V), NTC, RTC, Master	CE

MiBRX Series - Independent Display

PRODUCT CODE	DESCRIPTION	CERTIFICATION
MiBRX-DSP-IND-96-8-0-00-B	MiBRX Independent Display 96x96 - Customized, 14 & 7 Seg, Bar Graphs, Speedometer	CE
MiBRX-DSP-IND-96-8-2-16-B	MiBRX Independent Display 96x96 - LCD (16x2)	CE
MiBRX-DSP-IND-96-8-4-16-B	MiBRX Independent Display 96x96 - LCD (16x4)	CE

Supported I/O cards

PRODUCT CODE	DESCRIPTION	CERTIFICATION
MiBRX-SC-DI04	MiBRX Slot Card - 4 Digital Inputs	CE
MiBRX-SC-DI06	MiBRX Slot Card - 6 Digital Inputs	CE
MiBRX-SC-RO03	MiBRX Slot Card - 3 Relay Outputs	CE
MiBRX-SC-RO04	MiBRX Slot Card - 4 Relay Outputs	CE
MiBRX-SC-RO05	MiBRX Slot Card - 5 Relay Outputs (1.5 A)	CE
MiBRX-SC-TO04	MiBRX Slot Card - 4 Transistor Outputs	CE
MiBRX-SC-DI02-RO02	MiBRX Slot Card - 2 Digital Inputs & 2 Relay Outputs	CE
MiBRX-SC-DI02-TO02	MiBRX Slot Card - 2 Digital Inputs & 2 Transistor Outputs	CE
MiBRX-SC-DI02-AI01-T	MiBRX Slot Card - 2 Digital Inputs & 1 Analog Input - TC/RTD	CE
MiBRX-SC-AI02-V	MiBRX Slot Card - 2 Analog Inputs - Voltage	CE
MiBRX-SC-AI02-I	MiBRX Slot Card - 2 Analog Inputs - Current	CE
MiBRX-SC-AI02-V-I	MiBRX Slot Card - 2 Analog Inputs - 1 Voltage & 1 Current	CE
MiBRX-SC-AI02-TC	MiBRX Slot Card - 2 Analog Inputs - Thermocouple	CE
MiBRX-SC-AI02-RTD	MiBRX Slot Card - 2 Analog Inputs - RTD	CE
MiBRX-SC-AI02-PT1000	MiBRX Slot Card - 2 Analog Inputs - PT1000	CE
MiBRX-SC-AI02-PTC	MiBRX Slot Card - 2 Analog Inputs - PTC	CE
MiBRX-SC-AI02-NTC	MiBRX Slot Card - 2 Analog Inputs - NTC	CE
MiBRX-SC-AO01-V/I	MiBRX Slot Card - 1 Analog Output	CE
MiBRX-SC-FI02	MiBRX Slot Card - 2 Fast Inputs (10KHz)	CE
MiBRX-SC-FO01-TO01	MiBRX Slot Card - 1 Fast Output (10KHz) & 1 Transistor Output	CE
MiBRX-SC-LC02	MiBRX Slot Card - 2 Analog Inputs - Load Cell (24 Bit)	CE
MiBRX-SC-DL	MiBRX Slot Card - Datalogging (2MB) & RTC	CE
MiBRX-SC-WIFI	MiBRX Slot Card - WIFI	CE

MiBRX - Accessories

PRODUCT CODE	DESCRIPTION	CERTIFICATION
MiBRX-SC-PD	MiBRX Portable Downloader	CE

MiBRX - Adapter Plate

PRODUCT CODE	DESCRIPTION	CERTIFICATION
MiBRX-DSP-AP-2M	MiBRX 2M Adapter Plate	CE
MiBRX-DSP-AP-4M	MiBRX 4M Adapter Plate	CE
MiBRX-DSP-AP-6M	MiBRX 6M Adapter Plate	CE

Flexible IO Solution

PRODUCT CODE	CERTIFICATION
FL-GT35-DI04-PS-230V-CE-RoHS	CE
FL-GT35-DI04-PS-24V-CE-RoHS	CE
FL-GT35-DSP-CE-RoHS	CE
FL-GT35-LG-1-0-1-CE-RoHS	CE
FL-TX4-DI04-PS-230V-CE-RoHS	CE
FL-TX4-DI04-PS-24V-CE-RoHS	CE
FL-TX4-LG-1-0-1-V2-CE-RoHS	CE
FL-RL-DI04-PS-24V-CE-RoHS	CE
FL-RL-BS-6-CE-RoHS	CE
FL-RL-LG-1-0-1-V2-CE-RoHS	CE
FL-RL-PS-230V	---

Compact Series

PRODUCT CODE	CERTIFICATION
DIGIX-1-0-0-24VDC-B	CE in process
DIGIX-1-230V	CE
DIGIX-1-0-0-24VDC	CE in process
DIGIX-1-1-1-230V	CE
DIGIX-2-1-0-24VDC	CE
DIGIX-4-1-1-24VDC	CE
UNIX-1-230V	CE in process
TWIX-1-230V	CE in process
TWIX-1-24VDC	CE in process
TWIX-2-230V	CE in process
TWIX-2-24V	CE in process
TWIX-3-24VDC	CE in process

Fixed IO Configuration

PRODUCT CODE	CERTIFICATION
MM3030-4	CE in process
MM3032-2-0-0-230V V2	CE in process
MM3032-2-0-0-24V V2	CE in process

Human Machine Interface

PRODUCT CODE	DESCRIPTION	CERTIFICATION
SP3-GT35	SP3-GT35	CE in process
SP112-GT40-S-CE	4.3" Touch screen HMI with Serial ports	CE in process
SP112-GT40-ET-CE	4.3" Touch screen HMI with Ethernet & Serial ports	CE in process
SP112-GT70-S1-CE	7" Touch screen HMI with Serial ports	CE
SP112-GT70-ET1-CE	7" Touch screen HMI with Ethernet & Serial ports	CE
SP112-GT100-ET-CE	10" Touch screen HMI with Ethernet & Serial ports	CE

Add ons - PLC IO's

PRODUCT CODE	DESCRIPTION	CERTIFICATION
EXP-FLEX 2M	Expansion slot - Flexys IO cards	CE
EXP-FLEX 2M V3	Expansion slot - Flexys IO cards	CE in process
FL-SC-DI10-CE-RoHS	10 Digital inputs card	CE
FL-SC-DI14-CE-RoHS	14 Digital inputs card	CE
FL-SC-RO08-CE-RoHS	8 Channel relay output card	CE
FL-SC-TO08-CE-RoHS	8 Channel transistor output card	CE
FL-SC-DI04-RO04-CE-RoHS	4 Digital input, 4 Relay output card	CE
FL-SC-AI04-U	4 Channel analog input card - Universal	CE in process
FL-SC-AI04-RTD-CE-RoHS	4 Channel analog input card - RTD (PT-100)	CE
FL-SC-AI04-TC-CE-RoHS	4 Channel analog input card - Thermocouple	CE
FL-SC-AIDF04-TC-CE-RoHS	4 Channel differential analog input card - Thermocouple	CE
FL-SC-AI06-V-CE-RoHS	6 Channel analog input card - Voltage	CE
FL-SC-AI06-I-CE-RoHS	6 Channel analog input card - Current	CE
FL-SC-AI03-NTC-AI03-I	3 Channel analog input - NTC, 3 channel analog input - Current card	CE in process
FL-SC-AO04-V-CE-RoHS	4 Channel analog output card - Voltage	CE
FL-SC-AO04-I-CE-RoHS	4 Channel analog output card - Current	CE
FL-SC-AI03-U-AO02-U	3 Channel analog input - Universal, 2 Channel analog output - Universal card	CE in process
FL-SC-LC04	4 Channel loadcell input card	CE in process

Annunciator

PRODUCT CODE	CERTIFICATION
AN-8-0-0-230V	---

Battery Chargers

PRODUCT CODE	CERTIFICATION
BC1-1210	---
BC2-2410	---

Relay Module

PRODUCT CODE	CERTIFICATION
RLYMD-1-S4-1CO-24VDC-CE-RoHS	CE
RLYMD-1-S4-2CO-24VDC-CE-RoHS	CE
RLYMD-2-S8-1CO-24VDC-CE-RoHS	CE
RLYMD-2-S8-2CO-24VDC-CE-RoHS	CE
ERLYMD-2-1-S8-1CO-24V-CE-RoHS	CE

DIN Rail Power Supply Nomenclature

Eg.: RPS60-24 RPS60 - XX - YY → Certification : CE : CE CU : CE  No fields indicates no certification → Output Voltage : 05 : 5V 12 : 12V 15 : 15V 24 : 24V 48 : 48V → 60W
Eg.: RPS120-24-CE RPS120 - XX - YY → Certification : CE : CE CU : CE  No fields indicates no certification → Output Voltage : 12 : 12V 15 : 15V 24 : 24V 48 : 48V → 120W
Eg.: RPS240-24-CU RPS240 - XX - YY → Certification : CE : CE CU : CE  No fields indicates no certification → Output Voltage : 12 : 12V 24 : 24V 48 : 48V → 240W
Eg.: RPS480-24-CU RPS480 - XX - YY → Certification : CE : CE CU : CE  No fields indicates no certification → Output Voltage : 24 : 24V 48 : 48V → 480W

Note : Create the code according to the requirement.

Wall Mount Power Supply

PRODUCT CODE	CERTIFICATION
PPS240-24	---

Open Frame Power Supply

PRODUCT CODE	CERTIFICATION
OPS2x3-40-05-A-1-CU	 in process
OPS2x3-40-12-A-1-CU	 in process
OPS2x3-40-24-A-1-CU	 in process
OPS2x3-40-48-A-1-CU	 in process
OPS2x4-60-05-A-1-CU	 in process
OPS2x4-60-12-A-1-CU	 in process
OPS2x4-60-24-A-1-CU	 in process
OPS2x4-60-48-A-1-CU	 in process
OPS2x4-150-12-A-1-CU	 in process
OPS2x4-150-24-A-1-CU	 in process
OPS2x4-150-48-A-1-CU	 in process
OPS2x4-200-12-A-1-CU	 in process
OPS2x4-200-24-A-1-CU	 in process
OPS2x4-200-48-A-1-CU	 in process
OPS3x5-350-12-A-1-CU	 in process
OPS3x5-350-24-A-1-CU	 in process
OPS3x5-350-48-A-1-CU	 in process

Data Converters / Accessories

PRODUCT CODE	CERTIFICATION
AC-USB-RS232-01	CE in process
AC-USB-RS485-02	CE
AC-USB-RS485-03	CE
AC-S2E-03-CE-RoHS	CE
AC-IOEXP-01	CE
AC-IOEXP-03	CE
ACH-001	CE
ACH-002	CE
ACH-003	CE
ACH-004	CE
AC-RS485-RS232-ISO	CE in process



VFD-L



VFD-S

FEATURES	• Compact & powerful AC drives • 0.5HP 0.4KW & 1HP 0.75KW	• Standard General Purpose drives • 0.5HP 0.4KW to 20HP 15KW
RATED INPUT VOLTAGE / FREQUENCY	Single Phase 230 VAC 50Hz / 60 Hz	Single Phase 220V 50Hz / 60Hz, 3 Phase 415 VAC 50Hz / 60Hz
PERMISSIBLE VOLTAGE FLUCTUATION	185 to 275 VAC	187 to 253 VAC for 1 phase & 320 to 460 VAC for 3 Phase
PERMISSIBLE FREQUENCY FLUCTUATION	±5%	
CONTROL MODE	V/F control	
FREQUENCY CONTROL RANGE	0.1 ~ 400 Hz	
FREQUENCY ACCURACY	Digital setting 0.01%, Analog instruction 0.1% (Max frequency)	
FREQUENCY RESOLUTION	Digital instruction 0.1Hz, Analog instruction 0.1 Hz	
ACCELERATION/DECELERATION TIME	0.0 ~ 3600 Sec. Four acceleration/deceleration time settings available	
MULTI SPEED RUNNING	Built-in program using Simple PLC feature	
BUILT-IN PI	Easy to set up a simple automatic control system	
BUILT-IN COUNTER	Automatically controlled production line can be achieved	
OVERLOAD CAPACITY	150% for 1min, 180% for 10s, 200% for 1s	
V/F MODE	4 pre-set V/F mode and 1 User Defined V/F program	
AUTOMATIC ENERGY SAVING OPERATION	Changes the V/F curve according to the load to reduce energy consumption	
AUTOMATIC VOLTAGE REGULATION	Regulates the voltage automatically whenever there is a change in grid voltage	
OPERATION COMMANDS	Keypad, External terminals, External communication using MODBUS	
FREQUENCY SETTING	Keypad Up/Down keys, Keypad potentiometer, External potentiometer, Analog inputs (4-20mA/0-10V), MODBUS communication	
INPUT SIGNAL	4 User Selectable (PNP/NPN) Multifunction Inputs	5 User Selectable (PNP/NPN) Multifunction Inputs
OUTPUT SIGNAL	1 User Selectable Multifunction Relay Output (250V/5A Contact),	1 User Selectable Multifunction Relay Output (250V/5A Contact), 1 User Selectable Multifunction Open Collector Output
PROTECTION FUNCTIONS	Over Current, Over Voltage, Under Voltage, Overheat, Overload, Under Current, System Error	
DISPLAY	Non-removable HMI with 5 keys, 4x7 segment LED display and 5 status LEDs setting, Running status and fault display	Removable HMI with 7 keys, 1 switch enabled encoder, 5x7segment LED display and 7 status LEDs
OPERATING ENVIRONMENT	Temperature : -10 ~ +50°C, Humidity : < 90%, No condensation, IP20	
STORAGE TEMPERATURE	-20 ~ +60°C	
VIBRATION	<5.9 m/s ² (0.6g)	
APPLICATIONS	Suitable for fans, pumps, Conveyor, Food & drink packaging machinery, Industrial washing machine and most general industries etc.	

Ordering information

Variable Frequency Drive (VFD-L)

PRODUCT CODE	DESCRIPTION	CERTIFICATION
VFD-L-1-005-230V	1 Phase 230V, 0.5HP/0.4KW Economic Series (4DI, 1AI, POT, RS485, 1RO SPST, Built in display)	---
VFD-L-1-010-230V	1 Phase 230V, 1HP/0.75KW Economic Series (4DI, 1AI, POT, RS485, 1RO SPST, Built in display)	---

Variable Frequency Drive (VFD-S)

PRODUCT CODE	DESCRIPTION	CERTIFICATION
VFD-S-1-005-230V	1 phase input 230V AC, 3 phase output 0 to rated Input voltage 0.5HP / 0.4KW, General Purpose series (5DI, 2AI, RS485, 1RO SPDT, 1TO, Detachable display)	---
VFD-S-1-010-230V	1 phase input 230V AC, 3 phase output 0 to rated Input voltage 1HP/0.75KW, General Purpose series (5DI, 2AI, RS485, 1RO SPDT, 1TO, Detachable display)	---
VFD-S-1-020-230V	1 phase input 230V AC, 3 phase output 0 to rated Input voltage 2HP/1.5KW, General Purpose series (5DI, 2AI, RS485, 1RO SPDT, 1TO, Detachable display)	---
VFD-S-3-010-415V	3 phase input 415V AC, 3 phase output 0 to rated Input voltage 1HP/0.75KW, General Purpose series (5DI, 2AI, RS485, 1RO SPDT, 1TO, Detachable display)	---
VFD-S-3-020-415V	3 phase input 415V AC, 3 phase output 0 to rated Input voltage 2HP/1.5KW, General Purpose series (5DI, 2AI, RS485, 1RO SPDT, 1TO, Detachable display)	---
VFD-S-3-030-415V	3 phase input 415V AC, 3 phase output 0 to rated Input voltage 3HP/2.2KW, General Purpose series (5DI, 2AI, RS485, 1RO SPDT, 1TO, Detachable display)	---



FD100



FD300

FEATURES	• Compact & powerful AC drives • 1HP 0.75KW to 5HP 3.7KW	• Compact & powerful AC drives • 2HP 1.5KW to 650HP 500KW
RATED INPUT VOLTAGE / FREQUENCY	Single Phase 220 VAC 50Hz / 60Hz, 3 Phase 415 VAC 50Hz / 60Hz	
PERMISSIBLE VOLTAGE FLUCTUATION	187V to 253 VAC for 1 phase & 320 to 460 VAC for 3 Phase	
PERMISSIBLE FREQUENCY FLUCTUATION	±5%	
CONTROL MODE	V/F control	V/F Control, flux vector control V/F Control, flux vector control
FREQUENCY CONTROL RANGE	0.1 ~ 400 Hz	
FREQUENCY ACCURACY	Digital setting 0.01%, Analog instruction 0.1% (Max frequency)	
FREQUENCY RESOLUTION	Digital instruction 0.1Hz, Analog instruction 0.1 Hz	
ACCELERATED / DECELERATED TIME	0.0 ~ 3600 Sec. Four accelerate / decelerate time settings available	
MULTI SPEED RUNNING	Built-in program	
BUILT-IN PI	Easy to set up a simple automatic control system	
OVERLOAD CAPACITY	G Type - 150% rated current for 1 min, P type - 120% rated current for 1 min	
TORQUE BOOST	0-15%	
V/F MODE	3 preset V/F mode and V/F program	
AUTOMATIC ENERGY SAVING OPERATION	Changes the V/F curve according to the load to save energy	
AUTOMATIC VOLTAGE REGULATION	Regulates the voltage automatically whenever there is a change in grid voltage	
OPERATION COMMANDS	Keypad, External terminals and Communication	
FREQUENCY SETTING	Digital setting, Analog voltage setting, Analog current setting, Communication	
INPUT SIGNAL	Forward / Reverse, Jogging selection, Multi speed control, Regular stopping	
OUTPUT SIGNAL	Fault alarm output (250V/2A Contact), Open collector output	
PROTECTION FUNCTIONS	Over current, Over voltage, Under voltage, Over heat, Overload, Phase loss	
DISPLAY	Parameters setting, Running status and fault display	
OPERATING ENVIRONMENT	Temperature : -10 ~ +50°C, Humidity : < 90%, No condensation, IP20	
OPERATIONS AREA	Indoor, <1000m altitude above sea level	
STORAGE TEMPERATURE	-20 ~ +60°C	
VIBRATION	<5.9 m/s ² (0.6g)	
INPUT CHANNEL	5 DI (Internal impedance:3.3kΩ) 2AI	6 DI (Internal impedance:3.3kΩ) 2AI
OUTPUT CHANNEL	1 RO, 1 TO	1 RO, 2 TO
APPLICATIONS	Suitable for fans, pumps, Conveyor, Food & drink packaging machinery, Industrial washing machine and most general industries etc.	Suitable for fans, Pumps, Conveyor, Mixer, Textile machine, Dyeing machine, Lithographic printing machine Metal workin

Ordering information

Variable Frequency Drive (FD100)

PRODUCT CODE	DESCRIPTION	CERTIFICATION
FD100-1-010-C-CE	1 Phase 220V, 1HP 0.75 KW	CE
FD100-1-020-C-CE	1 Phase 220V, 2HP 1.5 KW	CE
FD100-1-030-C-CE	1 Phase 220V, 3HP 2.2 KW	CE
FD100-3-010-C-CE	3 Phase 415V, 1HP 0.75 KW	CE
FD100-3-020-C-CE	3 Phase 415V, 2HP 1.5 KW	CE
FD100-3-030-C-CE	3 Phase 415V, 3HP 2.2 KW	CE
FD100-3-050-C-CE	3 Phase 415V, 5HP 3.7 KW	CE

Variable Frequency Drive (FD300)

PRODUCT CODE	DESCRIPTION	CERTIFICATION
FD300-3-050-C-CE	3 Phase 415V, 5HP 3.75 KW	CE
FD300-3-075-C-CE	3 Phase 415V, 7.5HP 5.5 KW	CE
FD300-3-100-C-CE	3 Phase 415V, 10HP 7.5 KW	CE
FD300-3-150-C-CE	3 Phase 415V, 15HP 11.2 KW	CE
FD300-3-200-C-CE	3 Phase 415V, 20HP 15 KW	CE
FD300-3-250-C-CE	3 Phase 415V, 25HP 18.8 KW	CE
FD300-3-300-C-CE	3 Phase 415V, 30HP 22.4 KW	CE
FD300-3-400-C-CE	3 Phase 415V, 40HP 30 KW	CE
FD300-3-500-C-CE	3 Phase 415V, 50HP 37.5 KW	CE
FD300-3-750-C-CE	3 Phase 415V, 75HP 55KW	CE
FD300-3-1000-C-CE	3 Phase 415V, 100HP 75 KW	CE



FD9

FEATURES	- General Purpose AC Drives 1HP 0.75KW to 10HP 7.5KW
RATED INPUT VOLTAGE / FREQUENCY	Single Phase 230 VAC 50Hz / 60Hz, 3 Phase 415 VAC 50Hz / 60Hz
PERMISSIBLE VOLTAGE FLUCTUATION	-20 % ~ +15 %
PERMISSIBLE FREQUENCY FLUCTUATION	±5%
CONTROL MODE	V/F, Sensorless vector control (SVC), Speed Sensor vector control (FVC)
FREQUENCY CONTROL RANGE	0.1 ~ 5000 Hz
FREQUENCY ACCURACY	Digital setting 0.01%, Analog instruction 0.1% (Max frequency)
FREQUENCY RESOLUTION	Digital instruction 0.1Hz, Analog instruction 0.1 Hz
ACCELERATED / DECELERATED TIME	0.0 ~ 6000 Sec. Four accelerate / decelerate time settings available
MULTI SPEED RUNNING	Built-in program
BUILT-IN PI	Easy to set up a simple automatic control system
OVERLOAD CAPACITY	150% rated current for 1minute, 180% rated current for 3 seconds
TORQUE BOOST	0-30%(Manual & Auto boost)
V/F MODE	Five ways: constant torque V/F curve, 1 kind of user defined V/F curve, 3 kinds of down torque curve (2.0 / 1.7 / 1.2times the power)
AUTOMATIC ENERGY SAVING OPERATION	Saving energy by auto optimizing V/F curve according to the load
AUTOMATIC VOLTAGE REGULATION	Regulates the voltage automatically whenever there is a change in grid voltage
OPERATION COMMANDS	Keypad, External terminals and Communication
FREQUENCY SETTING	Digital setting, Analog voltage setting, Analog current setting, Communication
INPUT SIGNAL	Forward / Reverse, Jogging selection, Multi speed control, Regular stopping
OUTPUT SIGNAL	Fault alarm output (250V/2A Contact), Open collector output
PROTECTION FUNCTIONS	Over current, Over voltage, Under voltage, Over heat, Overload, Phase loss
DISPLAY	Parameters setting, Running status and fault display
OPERATING ENVIRONMENT	Temperature : -10 ~ +50°C, Humidity : < 90%, No condensation, IP20
OPERATIONS AREA	Indoor, <1000m altitude above sea level
STORAGE TEMPERATURE	-20 ~ +60°C
VIBRATION	<5.9 m/s ² (0.6g)
INPUT CHANNEL	6 DI (Internal impedance:3.3kΩ) 2AIs
OUTPUT CHANNEL	1 RO, 2 TO
APPLICATIONS	Suitable for fans, pumps, Conveyor, Food & drink packaging machinery, Industrial washing machine, Winder application, Hoists, Paper Mills, Textile Applications and most general industries etc.

Ordering information

Variable Frequency Drive (FD9)

PRODUCT CODE	DESCRIPTION	CERTIFICATION
FD9-1-010-C-CE	1 Phase 230V, 1HP 0.75 KW	CE
FD9-3-020-C-CE	3 Phase 415V, 2HP 1.5 KW	CE
FD9-3-030-C-CE	3 Phase 415V, 3HP 2.2 KW	CE
FD9-3-050-C-CE	3 Phase 415V, 5HP 3.75 KW	CE
FD9-3-075-C-CE	3 Phase 415V, 7.5 HP 5.5 KW	CE
FD9-3-100-C-CE	3 Phase 415V, 10HP 7.5 KW	CE



Standard Duty Capacitor

Heavy Duty Capacitor

FEATURES	- Protection - Over pressure disconnection system - Over current : HD - 1.5 times, SD - 1.3 times capacity - Internal fuse for protection - Dry type - Polyurethane self - extinguishing resin V0 developed under standard UL 94 - Fire proof
VOLTAGE	440, 480, 525 V
OVER VOLTAGE (HD)	1.10 x Un (8 h/day) ; 1.15 x Un (30 min/day) ; 1.20 x Un (5 min/day) ; 1.30 x Un (1 min/day) ; 1.10 x Un (8 h/day) ; 1.15 x Un (30 min/day) ; 1.20 x Un (5 min/day) ; 1.30 x Un (1 min/day)
OVER CURRENT	1.3 x In
DISCHARGE RESISTANCE	Incorporated
FREQUENCY	50 Hz
MAX %THD IN CURRENT	25
CAPACITOR TOLERANCE	-5% +10%
TYPE	Delta
DISCHARGE RESISTANCE	MOR
VOLTAGE TEST BETWEEN TERMINAL	2.15 x Un 10s
VOLTAGE TEST BETWEEN TERMINAL & CASE	3kV AC for 1 min
INRUSH CURRENT	up to 200 x In (HD)
INTERNAL FUSES	Yes
IP PROTECTION CLASS	IP 2x
DIELECTRIC LOSSES	≤ 0.2 W / KVA _r
TOTAL LOSSES	≤ 0.45 W / KVA _r
HUMIDITY	Max. 95%
TEMPERATURE	-20°C to +55°C
ALTITUDE	Max 2000 m.a.s.l
MOUNTING POSITION	Vertical



Wall Mount

Rack Type

FEATURES

- Available in 50kVAr & 100kVAr
- Real time, dynamic step-less compensation
- Instant response time of 50 μ sec & full response in less than 1 cycle
- Capacitive (Leading) & Inductive (Lagging) reactive power mitigation
- Advance feature- Harmonic correction up to 15th order
- Compensates current unbalance created by the load

SINGLE - MODULE
COMPENSATION CAPACITY

50kVAr

100 kVAr

RATED VOLTAGE

308V to 480V $\pm 15\%$

FREQUENCY

50/60 Hz (± 2.5 Hz)

PARALLEL OPERATION

8

OVERALL EFFICIENCY

> 97%

POWER GRID STRUCTURE

3P3W / 3P4W

CT RATIO

Selectable through HMI up to 10000/5A

CT LOCATION

Grid side / Load side

CIRCUIT TOPOLOGY

3 level inverters (I type)

RESPONSE TIME

50 μ sec and full response less than 1 cycle

TARGET POWER FACTOR

Adjustable from -1 to +1

COOLING MODE

Forced air cooling

NOISE LEVEL

< 65 dB

NORMAL SPECTRUM OF
COMPENSATION

Up to 15th harmonics

PROTECTION

Over current, over voltage, over temperature, IGBT saturation protection, Grid fault

COMMUNICATION PORTS

MODBUS-RTU over RS485, Possible using LAN, WiFi (Paid basis)

COMMUNICATION PROTOCOLS

MODBUS-RTU over RS485, Possible using LAN, WiFi (Paid basis)

COMMUNICATION INTERFACE

4.3" Touch screen HMI (7" available on request)

SOFTWARE UPDATES

Possible through WIFI or Laptop

MOUNTING

Rack type, Wall Mount

DIMENSIONS

Rack Mount : 226(H) x 470(W) x 670(D)mm
Wall Mount : 670(H) x 470(W) x 226(D)mm

Rack Mount : 220(H) x 571(W) x 862(D)mm
Wall Mount : 862(H) x 571(W) x 220(D)mm

WEIGHT

45 kg

75 kg

COLOR

RAL 7035

ALTITUDE

Less than 2000m (Higher altitudes on special request)

OPERATING TEMPERATURE

-10°C to 45°C

RELATIVE HUMIDITY


95%, no condensation

IP PROTECTION CLASS

IP 2x



FEATURES	- Mitigates voltage sags & swell - Voltage spike & noise control - Real-time voltage compensation - Fault correction within 20msec	
RATINGS	Single Phase - 2.5kVA to 10kVA	Three Phase - 7.5kVA to 30kVA
NOMINAL INPUT VOLTAGE	230V AC	400V AC
NORMAL OPERATING VOLTAGE (Typical output regulation within 1% of nominal)	180 - 280V AC for full regulation	320 - 480V AC for full regulation
OPERATING FREQUENCY	47-65 Hz	
MAXIMUM RATED INPUT CURRENT	For 2.5kVA - 14A, For 5kVA - 27A For 7.5kVA - 42A, For 10kVA - 55A	For 7.5kVA - 14A per phase, For 15kVA - 27A per phase For 22.5kVA - 42A per phase, For 30kVA - 55A per phase
INPUT MCB RATING	For 2.5kVA - 20A, For 5kVA - 32A For 7.5kVA - 50A, For 10kVA - 63A	For 7.5kVA - 20A, For 15kVA - 32A For 22.5kVA - 50A, For 30kVA - 63A
INPUT CONNECTION	Terminal block (R, N and E)	Terminal block (R, Y, B, N and E)
INPUT WIRE SIZE	For 2.5kVA 4 sq.mm (AWG 12) ; For 5kVA - 6 sq.mm (AWG 10) For 7.5kVA - 6 sq.mm (AWG 10) ; For 10kVA - 10 sq.mm (AWG 8)	For 7.5kVA - 4 sq.mm (AWG 12) ; For 15kVA - 6 sq.mm (AWG 10) For 22.5kVA 6 sq.mm (AWG 10) ; For 30kVA - 10 sq.mm (AWG 8)
ELIMINATES VOLTAGE SAGS	Up to 50V (22 % considering 230V nominal)	
SWELL COMPENSATION	Up to 50V (20% considering 230V nominal)	
COMPENSATION IRRESPECTIVE OF PHASE	Yes	
NOMINAL OUTPUT VOLTAGE	230V AC	400V AC
OUTPUT VOLTAGE RANGE	220-230-240V AC (Selectable)	400VAC Ph - Ph (220-230-240V Ph- Neutral Selectable)
POWER EFFICIENCY	Typically over 97% (with 20-100 % load conditions)	
CORRECTION	Less than 20 msec	
VOLTAGE COMPENSATION	Up to 50V	
MAXIMUM RATED OUTPUT CURRENT	For 2.5kVA - 11A, For 5kVA - 22A For 7.5kVA - 33A, For 10kVA - 44A	For 7.5kVA - 11A/Ph, For 15kVA - 22A/Ph For 22.5kVA - 33A/Ph, For 30kVA - 44A/Ph
VOLTAGE REGULATION	±1%	
RELAXED OPERATING VOLTAGE FOR ±10% COMPENSATION	160 - 300V AC	277 - 520V AC
OUTPUT CONNECTION	Terminal block (L, N and E)	Terminal block (L1, L2, L3, N and E)
LOAD BYPASS	Auto (activated within 5 sec of fault detection) / Manual selectable	
7 SEGMENT LED DISPLAY	Regular input and output	
BAR GRAPH LED	Load indication with resolution of 10%	
LED INDICATION	Overload, Overvoltage, Undervoltage, Overcurrent	
BUZZER INDICATION	Power on, Overload, Overvoltage, Undervoltage, Overcurrent, Over temp	
CAPACITY	2.5kVA, 5kVA, 7.5kVA, 10kVA	7.5kVA, 15kVA, 22.5kVA, 30kVA
POWER CONSUMPTION	100VA	100VA per phase
DIMENSIONS	For 2.5kVA & 5kVA - 353(H) x 282(W) x 282(D) mm For 7.5kVA & 10kVA - 445(H) x 353(W) x 347(D) mm approx.	For 7.5kVA & 15kVA - 617.3(H) x 368(W) x 530(D)mm For 22.5kVA & 30kVA - 643 (H) x 470(W) x 780(D)mm approx.
WEIGHT	For 2.5kVA - 18 kg approx. , For 5kVA - 28 kg approx. For 7.5kVA - 35 kg approx. , For 10kVA - 50 kg approx.	For 7.5kVA - 60 kg approx. , For 15kVA - 85 kg approx. For 22.5kVA - 100 kg approx. , For 30kVA - 120 kg approx.
MOUNTING	4 High Quality Castor wheels	
WARRANTY	3 years	
INPUT PROTECTION	Line overcurrent, overvoltage, undervoltage	
OUTPUT PROTECTION	Overload, Over current trip	
OVERLOAD & SHORT-CIRCUIT	Through suitable input circuit breaker	
SURGE TEST CONDITIONS	As per class 2 Surge (Combination wave)	
SURGE LET-THROUGH VOLTAGES	1.2 X 50µs, 6kV, 8 X 20µs, 3 kA waveform. L - N < 300V	
AMBIENT TEMP.	0 - 50°C, 10 to 90% RH non-condensing	
IP PROTECTION CLASS	IP 2x	



FEATURES	• Anti-Islanding protection • Wider MPPT range • Low start-up voltage • >97% Efficiency • Ingress protection - IP65 • Natural cooling convection • Remote monitoring				
MAX. DC INPUT POWER	3kW	6kW*	10kW*	50kW	100kW
MAX. ALLOWABLE PV POWER	4.2kW	7.5kW	12.5kW	75kW	150kW
NOMINAL PV VOLTAGE	360V	630V		600V	
MAX. DC INPUT VOLTAGE	600V	1000V		1100V	
START-UP VOLTAGE	80V	180V		200V	
OPERATING RANGE	65 - 550V	160 - 1000V		200 - 1000V	
MPPT VOLTAGE RANGE	65 - 550V	160 - 1000V		200 - 1000V	
MAX INPUT CURRENT PER MPPT	13A	11.6 / 11.6A		26A	
NUMBER OF MPPT	1	2		5	10
MAX INPUT STRINGS NUMBER	1	2			
MAXIMUM PV SHORT CIRCUIT CURRENT PER MPPT (Isc)		16		50	40
RATED OUTPUT POWER	3kW	6kW	10kW	50kW	100kW
MAX. OUTPUT POWER	3.3kW	6.6kW	11kW	55kW	110kW
NOMINAL AC CURRENT, RMS	13.6 / 13A	8.33A	13.9A	76.0 / 72.2A	152.0 / 144.3A
MAX. OUTPUT CURRENT	15A	10A	16A	83.3A	167A
GRID VOLTAGE RANGE	184 - 276V	320 - 480V		277 - 460V	
GRID FREQUENCY RANGE	50 / 60 Hz (45 - 55Hz / 55 - 65 Hz)				
POWER FACTOR (AT RATED OUTPUT POWER)	~ 1 (Adjustable from 0.8 leading to 0.8 lagging)				
TOTAL HARMONIC DISTORTION (THDi)	<3% at rated load				
FEED-IN PHASE/CONNECTION PHASE	Single Phase	Three Phase			
MAX. EFFICIENCY	97.6%	98.3%		98.9%	99%
MPPT EFFICIENCY	>99.5%	>99.5%		>99.9%	
EURO EFFICIENCY	97.1%	97.7%	97.9%	98.4%	98.6%
PROTECTIONS	DC Reverse Polarity, Short Circuit, Over Current, Over voltage / Under Voltage, Over frequency / Under Frequency, Insulation resistance monitoring, Residual current detection, Surge protection, Islanding Protection, Temperature Protection, Integrated DC Switch, Integrated AFCI (DC arc-fault circuit protection)				
DC CONNECTION	MC4 Connectors	2 Pairs of MC4		MC4 Connectors	H4 / MC4 (Optional)
DISPLAY	LCD & LED	LCD (16 x 2)		LCD with LED indications	
DATALOGGER & COMM.	RS485 / Wi-Fi / GSM* (Optional)			RS485 / Wi-Fi / GPRS* / PLC* (Optional)	
TOPOLOGY	Transformerless				
CONSUMPTION @ NIGHT	< 1W				
OPERATING TEMPERATURE RANGE	-25°C to 60°C				
COOLING METHOD	Natural convection				
RELATIVE HUMIDITY	0 to 100% non-condensing				
MAX. OPERATIONAL ALTITUDE	4000 m	3000 m		4000 m	
NOISE	<25 dBA	< 30 dBA		<60 dBA	
DESIGNED LIFETIME	> 20 years				
WARRANTY	5 years			10 years	
IP PROTECTION CLASS	IP65				
DIMENSIONS	260(H) x 280(W) x 140(D)mm	500(H) x 500(W) x 200(D)mm		600(H) x 800(W) x 300(D)mm	625(H) x 1080(W) x 380(D)mm
WEIGHT	7 kg approx.	26 kg approx.		65 kg approx.	80 kg approx.
MOUNTING	Wall mount				

NOTE : * BIS Certified



Standard Duty Capacitor Banks

PRODUCT CODE	POWER	VOLTAGE	FREQUENCY	CURRENT	CAPACITANCE	DIMENSIONS
	kVAr	V	Hz	A	μF	mm
SDCAP01440	1	440	50	1.31	8.22	40 x 130
SDCAP02440	2	440	50	2.62	16.44	45 x 130
SDCAP03440	3	440	50	3.93	24.66	50 x 130
SDCAP04440	4	440	50	5.24	32.88	57 x 130
SDCAP05440	5	440	50	6.55	41.10	63 x 130
SDCAP07440	7.5	440	50	9.825	61.65	68 x 190
SDCAP10440	10	440	50	13.10	82.20	75 x 200
SDCAP12440	12	440	50	15.72	98.64	85 x 200
SDCAP15440	15	440	50	19.65	123.30	75 x 300
SDCAP20440	20	440	50	20.26	164.40	85 x 300
SDCAP25440	25	440	50	32.75	205.40	90 x 300

Heavy Duty Capacitor Banks

PRODUCT CODE	POWER	VOLTAGE	FREQUENCY	CURRENT	CAPACITANCE	DIMENSIONS
	kVAr	V	Hz	A	μF	mm
Heavy Duty - 440V						
HDCAP01440	1	440	50	1.31	8.22	40 x 130
HDCAP02440	2	440	50	2.62	16.44	45 x 130
HDCAP03440	3	440	50	3.93	24.66	50 x 130
HDCAP04440	4	440	50	5.24	32.88	57 x 130
HDCAP05440	5	440	50	6.55	41.10	63 x 130
HDCAP07440	7.5	440	50	9.825	61.65	68 x 190
HDCAP10440	10	440	50	13.10	82.20	75 x 200
HDCAP12440	12 / 12.5	440	50	15.72	98.64	85 x 200
HDCAP15440	15	440	50	19.65	123.30	75 x 300
HDCAP20440	20	440	50	20.26	164.40	85 x 300
HDCAP25440	25	440	50	32.75	205.40	90 x 300
Heavy Duty - 480V						
HDCAP05480	5	480	50	6.01	34.56	63 x 200
HDCAP10480	10	480	50	12.02	69.11	85 x 200
HDCAP15480	15	480	50	18.03	103.67	85 x 300
HDCAP20480	20	480	50	24.04	138.22	90 x 300
HDCAP25480	25	480	50	30.05	172.78	100 x 300
Heavy Duty - 525V						
HDCAP05525	5	525	50	5.49	28.85	63 x 200
HDCAP10525	10	525	50	10.99	57.7	85 x 200
HDCAP15525	15	525	50	16.48	86.55	85 x 300
HDCAP20525	20	525	50	21.98	115.4	90 x 300
HDCAP25525	25	525	50	27.47	144.25	100 x 300

Advanced Static VAR Generators


PRODUCT CODE	DESCRIPTION
ASVG-050-WLL-4P-04	Advanced Static VAR Generator, 50 kVAR, Wall mounting, 3P-4W, with HMI Display 4.3 inch
ASVG-050-RCK-4P-04	Advanced Static VAR Generator, 50 kVAR, Rack mounting, 3P-4W, with HMI Display 4.3 inch
ASVG-050-WLL-4P-XX	Advanced Static VAR Generator, 50 kVAR, Wall mounting, 3P-4W, without display
ASVG-050-RCK-4P-XX	Advanced Static VAR Generator, 50 kVAR, Rack mounting, 3P-4W, without display
ASVG-050-WLL-3P-04	Advanced Static VAR Generator, 50 kVAR, Wall mounting, 3P-3W, with HMI Display 4.3 inch
ASVG-050-RCK-3P-04	Advanced Static VAR Generator, 50 kVAR, Rack mounting, 3P-3W, with HMI Display 4.3 inch
ASVG-050-WLL-3P-XX	Advanced Static VAR Generator, 50 kVAR, Wall mounting, 3P-3W, without display
ASVG-050-RCK-3P-XX	Advanced Static VAR Generator, 50 kVAR, Rack mounting, 3P-3W, without display
ASVG-100-WLL-4P-04	Advanced Static VAR Generator, 100 kVAR, Wall mounting, 3P-4W, with HMI Display 4.3 inch
ASVG-100-RCK-4P-04	Advanced Static VAR Generator, 100 kVAR, Rack mounting, 3P-4W, with HMI Display 4.3 inch
ASVG-100-WLL-4P-XX	Advanced Static VAR Generator, 100 kVAR, Wall mounting, 3P-4W, without display
ASVG-100-RCK-4P-XX	Advanced Static VAR Generator, 100 kVAR, Rack mounting, 3P-4W, without display
ASVG-100-WLL-3P-04	Advanced Static VAR Generator, 100 kVAR, Wall mounting, 3P-3W, with HMI Display 4.3 inch
ASVG-100-RCK-3P-04	Advanced Static VAR Generator, 100 kVAR, Rack mounting, 3P-3W, with HMI Display 4.3 inch
ASVG-100-WLL-3P-XX	Advanced Static VAR Generator, 100 kVAR, Wall mounting, 3P-3W, without display
ASVG-100-RCK-3P-XX	Advanced Static VAR Generator, 100 kVAR, Rack mounting, 3P-3W, without display

Static Voltage Regulators


PRODUCT CODE	DESCRIPTION
SINE-1P-2.5-180/280V	Static Voltage Regulator, 1 phase 2.5kVA, 180 / 280V
SINE-1P-5-180/280V	Static Voltage Regulator, 1 phase 5kVA, 180 / 280V
SINE-1P-7.5-180/280V	Static Voltage Regulator, 1 phase 7.5kVA, 180 / 280V
SINE-1P-10-180/280V	Static Voltage Regulator, 1 phase 10kVA, 180/280V
SINE-3P-7.5-340/480V	Static Voltage Regulator, 3 phase 7.5kVA, 340 / 480V
SINE-3P-15-340/480V	Static Voltage Regulator, 3 phase 15kVA, 340 / 480V
SINE-3P-22.5-340/480V	Static Voltage Regulator, 3 phase 22.5kVA, 340 / 480V
SINE-3P-30-340/480V	Static Voltage Regulator, 3 phase 30kVA, 340 / 480V

Solar On Grid Inverter


PRODUCT CODE	DESCRIPTION
GTI003WLM1PW	Grid Tie Inverter - 1 Phase/ 3 kW, Wall mounted with Wifi Module
GTI006WLM3PW	Grid Tie Inverter - 3 Phase/ 6 kW, Wall mounted with Wifi Module
GTI010WLM3PW	Grid Tie Inverter - 3 Phase/ 10 kW, Wall mounted with Wifi Module
GTI050WLM3PW	Grid Tie Inverter - 3 Phase/ 50 kW, Wall mounted with Wifi Module
GTI100WLM3PW	Grid Tie Inverter - 3 Phase/ 100 kW, Wall mounted with Wifi Module




MRJ4M / SMRD4M1 / MiBRX 4M




PPRD-4M-3 / PPRA-4M-3




600 SERIES




PPRD-4M-1-230V / PPRA-4M-1-230V / PPRWD-4M-1




800 SERIES




ELCTR35




900 SERIES / TS2M1-1-16A / ATS2M1-1-16A / TPRA2M1/ MiBRX 2M




MPR-3M




(140x93.4x72mm)




ANNUNCIATOR




RP-2M-1.1A-24VDC




BC1-1210




RPS60 / RPS120




OPS2x3-40




RPS240




OPS2x4-60




OPS2x4-150




RPS480




OPS2x4-200






BC1-1210




OPS3x5-350



Note : This open frame power supply should preferably be mounted horizontally on 4 metal stand-offs having diameter not more than 6mm and height not less than 5mm



Product code	Mounting dimension		Dimension			Pore diameter (mm)
	A	B	H	W	D	
VFD-S-1-005-230V	141	80.5	150	89	123	5.2
VFD-S-1-010-230V						
VFD-S-1-020-230V						
VFD-S-3-010-415V						
VFD-S-3-020-415V						
VFD-S-3-030-415V						
VFD-L-1-005-230V	141	80.5	152	90	123	5.2
VFD-L-1-010-230V						



Product code	Dimension			Installation (mm)			
	H	W	D	H2	H1	W1	Mount hole
FD9-3-010-C-CE	184	98	98	---	174	88	5
FD9-3-020-C-CE							
FD9-3-030-C-CE							
FD9-3-050-C-CE	184	98	98	---	174	88	5
FD9-3-075-C-CE	230	118	118	---	220	108	5
FD9-3-100-C-CE	230	118	118	---	220	108	5

Subsidiaries : **Selec GmbH** | **Selec USA** | **Selec Australia**

Head Office :

Selec Controls Pvt. Ltd.

EL-27/1, Electronic Zone, TTC Industrial Area, MIDC, Mahape, Navi Mumbai 400710, INDIA.

Tel.: +91-22-4141 8468 / 452. Fax: +91-22-41418 408. Email: sales@selec.com | www.selec.com

Selec USA : www.selec.com/us/en/ | **Selec GmbH :** www.selec-europe.com | **Selec Australia :** www.selecaustralia.com

Hotline: 1900.6536 - Website: HOPLONGTECH.COM