



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Lexium 32 Altivar Process ATV600 Altivar Machine ATV340 Altivar Machine ATV320 Altivar 32 Altivar Easy 610 Altivar Process ATV900
Communication port protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission rate	9.6 kbps...12 Mbps
Addressing	Configuration settings 1...126 configurable by graphic terminal/SoMove software
Communication service	4 configurable telegrams Mapping of the process data from the master Parameters management compliant with PROFIdrive V4.1 Several DP V1 messaging modes Drive profile native ATV32 conforming to IEC 61800-7-201 (CiA 402)
Display type	1 LED RUN 1 LED bus fault (BF)
Alarm function	Host drive handled from two masters (MS0 and MS1) Standard identification and maintenance requests Diagnostic data with VSD status
Bus profile	CiA 402 PROFIdrive
Standards	IEC 61800-7-201 (CiA 402)

Ordering and shipping details

Category	18263 - LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	00785901952886
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14000000000000001
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0936 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------

