

### Main

Range of product	Altivar
Product or component type	Communication module

### Complementary


Range compatibility	Altivar 32 Altivar Process ATV600 Altivar Process ATV900 Altivar Machine ATV320 Altivar Machine ATV340
Communication port protocol	DeviceNet
Electrical connection	1 connector 1 removable 5-way screw connector
Transmission rate	125 kbps, 250 kbps and 500 kbps configurable
Cable length	328.08 ft (100 m) (500 kbps) 1640.42 ft (500 m) (125 kbps)
Addressing	1...63 configurable by graphic terminal/SoMove software
Communication service	Inputs : polled, change of state, cyclic Outputs : polled ODVA AC drive and CiA 402 profile Auto device replacement Communication monitoring time out adjustable by DeviceNet configurator
Display type	1 LED MS (Module Status) 1 LED NS (Network Status)
Alarm function	Control mode received by graphic terminal Received instruction by graphic terminal
Bus profile	CiA 402 CIP AC Drive

### Ordering and shipping details

Category	22152 - ATV312 / ATV32 (.25 - 7.5 HP)
Discount Schedule	CP4B

GTIN	00785901651499
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14999999999999999
Returnability	Y
Country of origin	SE

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1020 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------

