



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar 32 Altivar Machine ATV320 Lexium 32
Communication port protocol	Ethernet/IP Modbus TCP
Electrical connection	1 connector RJ45 Ethernet/IP 1 connector RJ45 Modbus TCP
Transmission rate	10/100 Mbps
Addressing	IP addressing manual, BOOTP or DHCP
Exchange mode	Half duplex and full duplex
Communication service	Up to 8 connections (includes connections of Modbus TCP/Ethernet IP) Ethernet IP/Modbus TCP FDR Agent Ethernet IP/Modbus TCP Read holding registers (03), 63 words max Modbus TCP Read input registers (04), 63 words max Modbus TCP Write single register (06) Modbus TCP Write multiple registers (16), 63 words max Modbus TCP Read/Write multiple registers (23) Modbus TCP Read device identification (43) Modbus TCP Diagnostics (08) Modbus TCP I/O scanner : read/write, 6 words maximum Modbus TCP Communication monitoring Modbus TCP SNMP agent Ethernet IP Master/Slave hierarchy ODVA AC drive profile and CiA 402 profile Ethernet IP Fixed communication monitoring adjusted by Ethernet IP scanner adaptor (Master) Ethernet IP
Web server	Embedded HTTP server
Web services	Ethernet/IP scanner setup Security Ethernet/IP setup Drive parameters

	Drive monitor Message statistics Ethernet statistics
Display type	1 LED MS (Module Status) 1 LED NS (Network Status) 1 LED Ethernet port activity 1 LED Modbus TCP port activity
Product weight	0.66 lb(US) (0.3 kg)

Ordering and shipping details

Category	18263 - LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	00785901924975
Nbr. of units in pkg.	1
Package weight(Lbs)	0.13
Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0936 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------

