



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar Process ATV600 Altivar Machine ATV340 Altivar 32 Altivar Machine ATV320 Altivar Process ATV900
Communication port protocol	Link Layer Discovery Protocol Profinet
Electrical connection	2 connectors RJ45 Ethernet
Transmission rate	100 Mbits
Web server	Embedded HTTP server
Web services	Drive recorder Ethernet statistics IPar client settings Drive parameters Drive monitor Data editor Save/Restore drive configuration
Display type	1 LED MS (Module Status) 1 LED NS (Network Status) 1 LED TX/RX (Transmit/Receive port 1) 1 LED TX/RX (Transmit/Receive port 2)
Bus profile	PROFIdrive
Standards	IEC 61800-7-201 (CiA 402)
Product weight	0.66 lb(US) (0.3 kg)

Ordering and shipping details

Category	22154 - ATV312 / ATV32 ACCESSORIES
----------	------------------------------------

Discount Schedule	CP4B
GTIN	00785901983330
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14999999999999999
Returnability	Y
Country of origin	SE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1404 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity

